

**CENTER CORNER SECTION 09, TOWNSHIP 19 SOUTH, RANGE 10 EAST**

- 1) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 44 RECORDED IN SURVEY BOOK "A" ON PAGE 140 AND DATED MAY 1, 1868 FOR A SURVEY OF LAND OWNED BY W. L. PHILIPS AND OTHERS, BEING SECTION 9-19-10, TO ESTABLISH THE CENTER CORNER, DIVIDE THE SOUTHWEST 1/4 INTO TWO 80'S RUNNING EAST AND WEST, AND TO DIVIDE THE SOUTHEAST 1/4 INTO AN 80 RUNNING NORTH AND SOUTH AND TWO 40'S, SAID THAT **HE SET A STONE** FOR THE CENTER CORNER OF SECTION 9-19-10 AT THE INTERSECTION OF THE LINES FROM THE STONES THAT HE FOUND OR HE SET AT THE OPPOSITE 1/4 CORNERS ON THIS SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 80 RODS, 8 LINKS EAST TO THE STONE HE SET FOR THE NORTH 1/2/4 CORNER OF THE SE1/4 OF SECTION 9-19-10
  - 2) 160 RODS, 16 LINKS EAST TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 9-19-10
  - 3) 161 RODS, 5 LINKS WEST TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 9-19-10
- 2) L. A. HAMBLIN, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 113, A ROAD SURVEY RECORDED IN SURVEY BOOK "B" ON PAGE 112 DATED APRIL 10, 1871 FOR A ROAD THROUGH THE NORTH & SOUTH CENTERLINE OF SECTION 9-19-10, SAID THAT **HE FOUND THE STONE CENTER CORNER** OF SECTION 9-19-10 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 39.98 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 9-19-10
- 2) 19.93 CHAINS SOUTH TO THE STONE HE FOUND AT THE WEST 1/2/4 CORNER OF THE SE1/4 OF SECTION 9-19-10
- 3) 40.01 CHAINS SOUTH TO THE STONE CORNER HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 9-19-10

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 194 TO 196 [PACKET 41 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY ASA M. WEESNER FOR A COUNTY ROAD IN SECTION 9-19-10 THAT HE SURVEYED APRIL 11, 1871, AND WAS ESTABLISHED AND FILED FOR RECORD AS A 40 FOOT WIDE ROAD BY ORDER OF THE BOARD OF COUNTY COMMISSIONERS ON JANUARY 8, 1872, SAID THAT **HE FOUND THE STONE** AT THE CENTER CORNER OF SECTION 9-19-10 ON THIS ROAD SURVEY.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 39.98 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 9-19-10 TO END THIS ROAD SURVEY
  - 2) 20.08 CHAINS SOUTH TO A. M. WEESNER'S NORTHWEST CORNER
  - 3) 40.01 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 9-19-10 TO BEGIN THIS ROAD SURVEY
- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGE 215 [PACKET 76 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY CHARLES C. LYNCH FOR A COUNTY ROAD IN TOWNSHIP 19-10 THAT HE SURVEYED JUNE 5, 1873, AND WAS ESTABLISHED AT A WIDTH FROM 30 FEET TO 50 FEET AS SET FORTH ON THE SURVEY PLAT, APPARENTLY FOUND THE CENTER CORNER OF SECTION 9-19-10 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

HIS INFORMATION IS CONTINUED ON PAGE 2

- 1) THIS ROAD EXTENDS WEST ON THE 1/2 SECTION LINE FOR 160 RODS TO THE EAST 1/4 CORNER OF SECTION 8-19-10 AT 50 FEET WIDE, 15' ON THE SOUTH AND 35' ON THE NORTH OF THE 1/2 SECTION LINE; THENCE
  - 2) WEST ON THE 1/2 SECTION LINE FOR 160 RODS TO THE CENTER CORNER OF SECTION 8-19-10 AT 50 FEET WIDE, 25' EACH SIDE OF THE 1/2 SECTION LINE, TO BEGIN THIS ROAD SURVEY
  - 3) THIS ROAD CONTINUES EAST ON THE 1/2 SECTION LINE FOR 80 RODS AT 40 FEET WIDE, 20' ON EACH SIDE OF THE 1/2 SECTION LINE; THENCE
  - 4) EAST ON THE 1/2 SECTION LINE FOR 80 RODS TO THE EAST 1/4 CORNER OF SECTION 9-19-10 AT 30 FEET WIDE, 15' ON EACH SIDE OF THE 1/2 SECTION LINE; THENCE
  - 5) EAST ON THE 1/2 SECTION LINE FOR 160 RODS TO THE CENTER CORNER OF SECTION 10-19-10 AT 40 FEET WIDE, 26' ON THE NORTH AND 14' ON THE SOUTH SIDE OF THE 1/2 SECTION LINE; THENCE
  - 6) EAST ON THE 1/2 SECTION LINE FOR 303-1/4 RODS TO THE WEST LINE OF THE LOT OF THE COTTONWOOD MEETING HOUSE LOT AT 40 FEET, 20' ON EACH SIDE OF THE 1/2 SECTION LINE, AT A TURN TO THE SOUTH
  - 7) THIS ROAD INTERSECTS THE 1/2 SECTION LINE AT THE CENTER CORNER OF SECTION 11-19-10 AND CONTINUES EAST ON THE 1/2 SECTION LINE FOR 160 RODS TO THE EAST 1/4 CORNER OF SECTION 11-19-10 AT 40 FEET WIDE, 13' ON THE NORTH AND 27' ON THE SOUTH; THENCE
  - 8) EAST ON THE 1/2 SECTION LINE FOR ONE MILE TO THE EAST 1/4 CORNER OF SECTION 12-19-10 ON THE RANGE LINE AT 40 FEET WIDE, 20' ON EACH SIDE OF THE 1/2 SECTION LINE, TO END THIS ROAD SURVEY
- 5) COMMISSIONER'S ROAD JOURNAL BOOK "A", PAGE 106  
ON OCTOBER 26, 1928 A PETITION SIGNED BY E. M. THOMAS AND OTHERS FOR THE VACATION OF A ROAD IN TOWNSHIP 19-10 WAS PRESENTED TO THE BOARD OF COUNTY COMMISSIONERS. THE ROAD WAS VIEWED ON JANUARY 25, 1929, AND THE FINAL ORDER WAS ISSUED ON JANUARY 25, 1929 TO VACATE THE FOLLOWING ROAD:
- 1) BEGINNING AT THE CENTER OF SECTION 9-19-10; THENCE RUNNING SOUTH ON THE HALF SECTION LINE TO WHERE SAID ROAD CONNECTS WITH HIGHWAY 50 SOUTH
- 6) O. D. HENRY, COUNTY SURVEYOR, IN A ROAD SURVEY FOR ROAD NUMBER 746 RECORDED IN ROAD RECORD BOOK "E" ON PAGE 106 PETITIONED BY E. M. THOMAS AND OTHERS FOR THE CLOSING OF A ROAD IN TOWNSHIP 19-10 THAT WAS VIEWED BY THE COUNTY COMMISSIONERS AND THE COUNTY SURVEYOR ON MARCH 21, 1930, THE VIEWERS RECOMMENDED THAT THE ROAD SHOULD BE CLOSED AS PETITIONED FOR.  
THE FOLLOWING ROAD WAS CLOSED [VACATED]:  
BEGINNING AT THE CENTER OF SECTION 9-19-10; FROM THENCE RUNNING SOUTH ON THE HALF-SECTION LINE TO WHERE SAID LINE CONNECTS WITH HIGHWAY 50 SOUTH AND TERMINATING THERE
- 7) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 12, 1991, FOR JOB NUMBER 90329, SURVEY F09007 IN THE SURVEY FILE FOR TOWNSHIP 19-10 FOR A SURVEY OF THE WEST LINE OF THE EAST 95 ACRES OF THE NORTHWEST QUARTER OF SECTION 9-19-10, SAID THAT **HE SET A 1/2" X 24" REBAR WITH HIS "LS 752" CAP** FOR THE CENTER CORNER OF SECTION 9-19-10 AT THE INTERSECTION OF THE LINES FROM THE OPPOSITE 1/4 CORNERS.

HIS TIES ARE ON PAGE 3

- 1) 34.9' SSW TO A SPIKE & WASHER IN AN 18" ELM TREE
- 2) 22.4' NW TO A SPIKE & WASHER IN A 20" ELM TREE
- 3) 15.5' NNE TO THE CENTERLINE OF THE NORTH END OF A CORRUGATED METAL PIPE [CMP] CULVERT
- 4) 12.5' SSE TO THE CENTERLINE OF THE SOUTH END OF A CMP CULVERT

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,565.50' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP THAT HE SET FOR THE SOUTHWEST CORNER OF THE EAST 95 ACRES OF THE NW1/4 OF SECTION 9-19-10
- 2) 2,659.91' WEST TO THE 1/2" REBAR WITH A KDOT ALUMINUM CAP THAT HE FOUND AT THE WEST 1/4 CORNER OF SECTION 9-19-10
- 3) 2,639.56' NORTH TO THE 1/2" REBAR WITH A KDOT ALUMINUM CAP THAT HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 9-19-10
- 4) 2,657.18' EAST TO A 1/2" REBAR WITH A KDOT ALUMINUM CAP THAT HE FOUND AT THE EAST 1/4 CORNER OF SECTION 9
- 5) 2,542.23' SOUTH TO THE 1/2" REBAR WITH A KDOT ALUMINUM CAP THAT HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 9-19-10

- 8) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 09, 2005, FOR PROJECT NUMBER 05184-02, SURVEY F09008 IN THE SURVEY FILE FOR TOWNSHIP 19-10 FOR THE SURVEY OF A TRACT IN THE NORTHEAST QUARTER OF SECTION 9-19-10 FOR MERT DEBOER, SAID THAT **HE FOUND THE 1/2" REBAR WITH HIS "LS 752" CAP** AT THE CENTER CORNER OF SECTION 9-19-10 FROM HIS EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE FOR JOB NUMBER 90329 IN 1990.

- 1) 4.0' EAST TO THE CENTERLINE OF A 6' CORRUGATED METAL PIPE [CMP] CULVERT
- 2) 15.5' NNE TO THE CENTERLINE OF THE NORTH END OF THE CMP CULVERT
- 3) 12.5' SSE TO THE CENTERLINE OF THE SOUTH END OF THE CMP CULVERT
- 4) 27.0' NE TO A 40 D NAIL & WASHER IN A 16" ELM TREE
- 5) 26.7' SW TO A 40 D NAIL & WASHER IN A 14" ELM TREE
- 6) 2.0' NORTH TO THE CENTERLINE TRAVELED WAY OF GRAVEL COUNTY ROAD 175 EAST-WEST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,319.78' NORTH TO THE THEORETICAL POSITION FOR THE SOUTHWEST CORNER OF THE N1/2 OF THE NE1/4 OF SECTION 9-19-10
- 2) 2,639.56' NORTH TO THE KDOT ALUMINUM CAP THAT HE FOUND AT THE NORTHWEST CORNER OF THE N1/2 OF THE NE1/4 OF SECTION 9-19-10
- 3) 2,657.29' EAST TO THE KDOT ALUMINUM CAP THAT HE FOUND AT THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 9-19-10

- 9) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JANUARY 30, 2013, FOR PROJECT NUMBER 12318, SAID THAT **HE FOUND THE 1/2" IRON PIN WITH HIS "LS 752" CAP** AT THE CENTER CORNER OF SECTION 9-19-10 FROM HIS EXISTING REFERENCE TIES ON FILE AT THE COUNTY SURVEYORS OFFICE. HE NOTED THAT HE HAD SET THIS MONUMENT IN 1991.

- 1) 15.41' NNE TO THE CENTER OF THE NORTH END OF A CMP
- 2) 12.41' SSE TO THE CENTER OF THE SOUTH END OF A CMP
- 3) 1,319.83' NORTH TO A 5/8" IRON PIN WITH A LYON COUNTY CAP THAT HE SET **[HORIZONTAL TIE]**
- 4) 2' NORTH TO THE CENTER OF THE TRAVEL WAY OF COUNTY ROAD 175 EAST-WEST
- 5) 4' EAST TO THE CENTER OF THE CMP

CENTER CORNER SECTION 09-19-10