

NORTHWEST CORNER SECTION 09, TOWNSHIP 19 SOUTH, RANGE 10 EAST

- 1) ON PAGE 213 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 15" X 9" X 4"** FOR THE CORNER TO SECTIONS 4, 5, 8 & 9-19-10 ON APRIL 12, 1857.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS NORTH TO THE 18" X 8" X 5" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 4 & 5-19-10
 - 2) 80.08 CHAINS NORTH TO THE 23" X 13" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 4 & 5-19-10 ON THE NORTH TOWNSHIP BOUNDARY
 - 3) 40.22-1/2 CHAINS EAST TO THE 15" X 10" X 4" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 4 & 9-19-10
 - 4) 80.45 CHAINS EAST TO THE 24" X 15" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 3, 4, 8 & 9-19-10
 - 5) 40.00 CHAINS SOUTH TO THE 14" X 8" X 7" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 8 & 9-19-10
 - 6) 80.00 CHAINS SOUTH TO THE 17" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 8, 9, 16 & 17-19-10
- 2) E. B. KIRKENDALL, COUNTY SURVEYOR FROM 1863 TO 1865, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "A" ON PAGES 45 & 46 [PACKET 155 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] FOR THE "COUNTY ROAD FROM SECTION 23-18-11 VIA FREMONT TO PLYMOUTH ROAD" PETITIONED BY JOHN LOY AND OTHERS THAT WAS SURVEYED APRIL 14 & 23, 1864 AND ESTABLISHED IN THE COMMISSIONERS JOURNAL ON JULY 4-6, 1864 ON PAGE 71, APPARENTLY **FOUND THE STONE** AT THE NORTHEAST CORNER OF THE TOWN OF PLYMOUTH AT THE TERMINUS OF THIS ROAD SURVEY FOR THE 66 FOOT WIDE ROAD. THIS IS THE NORTHEAST CORNER OF SECTION 8-19-10 BY HIS SURVEY PLAT.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS N. 37° E FOR 4-3/5 MILES TO THE NORTHEAST CORNER OF THE NORTHWEST 1/4 OF SECTION 25-18-10; THENCE 9.50 CHAINS EAST ON THE SECTION LINE TO THE FORD ON THE NEOSHO RIVER; THENCE IN A NORTHERLY DIRECTION ON THE AMERICUS ROAD 40.00 CHAINS TO THE MIDDLE SECTION LINE OF SECTION 24-18-11; THENCE EAST ON THE MIDDLE SECTION LINE FOR 24.50 CHAINS TO JOHN LOY'S [WEST 1/4 CORNER OF SECTION 19-18-11?]; THENCE EAST ON THE MIDDLE SECTION LINES 4-1/2 MILES TO THE CENTER CORNER OF SECTION 23-18-11 TO BEGIN THIS ROAD SURVEY
- 3) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 38 RECORDED IN SURVEY BOOK "A" ON PAGE 134 FOR THE SURVEY OF A COUNTY ROAD PETITIONED BY E. B. PLUMB AND OTHERS, THAT HE SURVEYED ON THE 15TH DAY OF APRIL, 1868, APPARENTLY FOUND THE NORTHWEST CORNER OF SECTION 9, TOWNSHIP 19, RANGE 10 AS HE RAN THE SECTION LINES FROM THE NORTHWEST CORNER OF SECTION 7, TOWNSHIP 19, RANGE 10 ON THE RANGE LINE AND THE LYON AND CHASE COUNTY LINE EAST TO THE INTERSECTION OF THE AMERICUS AND EMPORIA ROAD BETWEEN SECTIONS 4 & 9, TOWNSHIP 19, RANGE 11 ON THIS ROAD SURVEY.

HIS FIELD NOTES ARE AS FOLLOWS:

- 1) COMMENCED ON THE WEST LINE OF RANGE 10, TOWNSHIP 19, AT A STONE SET IN THE GROUND, BEING THE CORNER TO SECTIONS 6-7-1 & 2; FROM WHICH I RAN EAST ON LINE BETWEEN SECTIONS 6 & 7, AT 82 RODS A RAVINE, AT 134 RODS A RAVINE, AT 320 RODS SET 1 MILE STONE; THENCE EAST ON LINE BETWEEN SECTIONS 5 & 8 AT 640 RODS SET 2 MILE STONE; THENCE EAST ON LINE BETWEEN SECTIONS 4 & 9 AT 18 RODS CARTERS BRANCH, THENCE EAST 288 RODS TO HAMMONDS RAVINE, THENCE EAST AT 960 RODS SET 3 MILE STONE; THENCE EAST ON LINE BETWEEN 3 & 10 AT 310 RODS A RAVINE, AT 1,280 RODS SET 4 MILE STONE; THENCE EAST ON LINE BETWEEN SECTIONS 2 & 11 AT 232 RODS MOON CREEK, THENCE EAST AT 1,600 RODS SET 5 MILE

STONE; THENCE EAST ON LINE BETWEEN SECTIONS 1 & 12, AT 308 RODS A RAVINE, AT 1,920 RODS SET 6 MILE STONE; THENCE EAST ON LINE BETWEEN SECTIONS 6 & 7, RANGE 11 AT 220 RODS A RAVINE, AT 2,240 RODS SET 7 MILE STONE; THENCE EAST ON LINE BETWEEN SECTIONS 5 & 8 AT 2,560 RODS SET 8 MILE STONE; THENCE EAST ON LINE BETWEEN SECTIONS 4 & 9 AT 2,709 RODS INTERSECT THE AMERICUS AND EMPORIA ROAD AT A STONE SET IN THE GROUND DENOTING THE TERMINUS OF THE ROAD,

- 2) THE ABOVE ROAD IS 8 MILES AND 149 RODS IN LENGTH AND 50 FEET IN WIDTH.
 - 3) THERE WAS NO PLAT OF SURVEY FOR THIS ROAD SURVEY
- 4) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 84 & 85 [PACKET 169 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY P. B. PLUMB AND OTHERS THAT WAS SURVEYED APRIL 15, 1868 AND WAS ESTABLISHED IN THE COMMISSIONERS JOURNAL ON PAGE 225 AS A 50 FOOT WIDE ROAD ON JULY 21, 1868, AND RECORDED AND FILED ON JULY 21, 1868 BY J. L. WILLIAMS, LYON COUNTY CLERK, APPARENTLY FOUND THE NORTHWEST CORNER OF SECTION 9, TOWNSHIP 19, RANGE 10 AS HE RAN THE SECTION LINES FROM THE NORTHWEST CORNER OF SECTION 7, TOWNSHIP 19, RANGE 10 ON THE RANGE LINE AND THE LYON AND CHASE COUNTY LINE EAST TO THE INTERSECTION OF THE AMERICUS AND EMPORIA ROAD BETWEEN SECTIONS 4 & 9, TOWNSHIP 19, RANGE 11 ON THIS ROAD SURVEY.
- HIS FIELD NOTES AND PLAT OF SURVEY SHOWS THE FOLLOWING INFORMATION:
- 1) COMMENCING ON THE WEST LINE OF RANGE 10, TOWNSHIP 19 AT A STONE SET IN THE GROUND BEING THE CORNER TO SECTIONS 6, 7, 1 & 2, FROM WHICH I RUN EAST ON LINE BETWEEN SECTIONS 6 & 7 AT 82 RODS VARIATION – AT 134 RODS VARIATION – AT 320 RODS SET 1 MILE STONE; THENCE EAST ON LINE BETWEEN SECTION 5 & 8 AT 640 RODS SET 2 MILES STONE; THENCE EAST ON LINE BETWEEN SECTIONS 4 & 9 AT 18 RODS TO CARTERS BRANCH, THENCE EAST 288 RODS TO HAMMERS RAVINE, THENCE EAST AT 960 RODS SET 3 MILE STONE; THENCE EAST ON LINE BETWEEN SECTION 3 & 10 AT 310 RODS A RAVINE AT 1,280 RODS SET 4 MILE STONE; THENCE EAST ON LINE BETWEEN SECTIONS 2 & 10 AT 232 RODS MOON CREEK, THENCE EAST AT 1,600 RODS SET 5 MILE STONE; THENCE EAST ON LINE BETWEEN SECTIONS 1 & 12 AT 308 RODS A RAVINE, AT 1,920 RODS SET 6 MILE STONE; THENCE EAST ON LINE BETWEEN SECTIONS 6 & 7 RANGE 11 EAST AT 220 RODS A RAVINE AT 2,240 RODS SET 7 MILE STONE; THENCE EAST ON LINE BETWEEN SECTIONS 5 & 8 AT 2,560 RODS SET 8 MILE STONE; THENCE EAST ON LINE BETWEEN SECTIONS 4 & 9 AT 2,709 RODS INTERSECT THE AMERICUS AND EMPORIA ROAD AT A STONE SET IN THE GROUND DENOTING THE TERMINATION OF THE ROAD.
 - 2) THE ABOVE ROAD IS 8 MILES AND 149 RODS IN LENGTH AND 50 FEET IN WIDTH
- 5) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY IN TOWNSHIP 19 SOUTH, RANGE 10 EAST RECORDED IN SURVEY BOOK "C" ON THE LEFT SIDE OF PAGE 154 DATED MARCH 18, 1878, APPARENTLY **FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 8-19-10 ON THIS ROAD SURVEY.
- THE ROAD IS DESCRIBED AS FOLLOWS:
- 1) COMMENCING AT THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION N8-19-10; I RAN N. 10°30' W. [ON THE SECTION LINE] 2,640 FEET TO THE NORTHEAST CORNER OF SECTION 8-19-10; THENCE NORTH 10°30' W. [ON THE SECTION LINE] 5,280 FEET TO THE NORTHEAST CORNER OF SECTION 5-19-10 [ON THE TOWNSHIP LINE AT THE TERMINUS OF THIS ROAD SURVEY]
 - 6) IN ROAD RECORD BOOK "A" ON PAGE 20 AND DATED FEBRUARY 1934, IT SHOWS A "**CROSS IN A STONE CULVERT**" AT THE NORTHWEST CORNER OF SECTION 9-19-10 FOR ROAD NUMBER 764, BUT THE SURVEY IS NOT SIGNED AND THERE ARE ON TIES ON THIS PAGE.

CONTINUED ON PAGE 3

- 7) REA BOOK 31 ON PAGE 7 SAYS THAT **THEY DROVE AN IRON PIN** FOR THE SOUTHWEST CORNER OF SECTION 4-19-10 AT 5,318 FEET SOUTH OF THE SOUTHWEST CORNER OF SECTION 33-18-10.
 - 1) 27' NE TO A GUARD POST
 - 2) 27' SE TO A GUARD POST

- 8) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 19-10 SHOWS A **REA PIN** AT THE "SW CORNER SECTION 4-19-10", BUT THERE IS NO DATE ON THIS ENTRY.
 - 1) 31' NE TO A WITNESS [REA]
 - 2) 33' NW TO A WITNESS [REA]

- 9) THE KRETSINGER REFERENCE TIE BOOKS FOR TOWNSHIP 19-10 SHOWS A **1/2" IRON PIN** AT THE "NE CORNER NE1/4 OF SECTION 8-19-10, BUT THERE IS NO DATE ON THIS ENTRY.
 - 1) 40.55' NW TO A SPIKE IN A POWER POLE
 - 2) 42.30' NW TO A SPIKE IN CEDAR TREE
 - 3) 37.65' SW TO A SPIKE IN A POWER POLE

- 10) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 19-10 SHOWS AN **IRON PIN** AT THE "SE CORNER SECTION 5-19-10", BUT THERE IS NO DATE ON THIS ENTRY.
 - 1) 40.5' NE TO A SPIKE IN A POWER POLE
 - 2) 42.2' NW TO A SPIKE IN THE BASE OF A CEDAR TREE

- 11) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 18, 1983, SAID THAT **HE FOUND AN EXISTING 5/8" REBAR** AT THE NORTHEAST CORNER OF SECTION 8-19-10 THAT WAS SET BY AI CHAMNESS IN A 1939 REA SURVEY AFTER CHAMNESS SAID THAT HE DID **NOT** FIND THE STONE AT THE NORTHWEST CORNER OF SECTION 8-19-10.
 - 1) 28.0' NORTH TO A LINE OF CEDAR TREES TO THE WEST
 - 2) 21.0' WEST TO A LINE OF FENCE TO THE SOUTH
 - 3) 25.0' WEST TO A LINE OF FENCE TO THE NORTH
 - 4) 21.5' NORTH TO A LINE OF FENCE TO THE EAST
 - 5) 20.0' EAST TO A LINE OF FENCE TO THE NORTH
 - 6) 23.0' EAST TO A LINE OF FENCE TO THE SOUTH

- 12) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 12, 1991, FOR JOB NUMBER 90329, SURVEY F09007 IN THE SURVEY FILE FOR TOWNSHIP 19-10 FOR A SURVEY OF THE WEST LINE OF THE EAST 95 ACRES OF THE NORTHWEST QUARTER OF SECTION 9-19-10, SAID THAT **HE FOUND THE EXISTING 5/8" REBAR** AT THE NORTHWEST CORNER OF SECTION 9-19-10 FROM HIS 1983 TIES OF RECORD IN THE COUNTY SURVEYORS OFFICE.
 - 1) 29.8' NE TO A SPIKE & WASHER IN A CORNER FENCE POST
 - 2) 41.7' NW TO THE NEAR FACE OF A 16" DIAMETER CEDAR TREE
 - 3) 22.5' NORTH TO A LINE OF FENCE TO THE EAST
 - 4) 20.5' WEST TO A LINE OF FENCE TO THE SOUTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

 - 1) 1,101.49' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF THE EAST 95 ACRES OF THE NW1/4 OF SECTION 9-19-10
 - 2) 2,666.99' EAST TO THE 1/2" REBAR WITH A KDOT ALUMINUM CAP HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 9-19-10
 - 3) 2,653.72' SOUTH TO THE 1/2" REBAR WITH A KDOT ALUMINUM CAP HE FOUND AT THE WEST 1/4 CORNER OF SECTION 9-19-10

- 13) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED SEPTEMBER 30, 1994, FOR JOB NUMBER 94318-02, SURVEY F09006 IN THE SURVEY FILE FOR TOWNSHIP 19-10 FOR TWO TRACTS IN THE NORTHWEST QUARTER OF SECTION 9-19-10, SAID THAT **HE FOUND THE EXISTING 5/8" REBAR** AT THE

NORTHWEST CORNER OF SECTION 9-19-10 FROM HIS TIES OF RECORD DATED MARCH 1983 AND FEBRUARY 1991 ON FILE IN THE COUNTY ENGINEER'S OFFICE.

- 1) 29.8' NE TO A SPIKE & WASHER IN A CORNER FENCE POST
- 2) 41.7' NW TO THE NEAR FACE OF AN 18" DIAMETER CEDAR TREE
- 3) 22.5' NORTH TO A LINE OF FENCE TO THE EAST EXTENDED
- 4) IN THE CENTERLINE OF THE TRAVELED WAY OF COUNTY ROAD 180 EAST-WEST
- 5) IN THE CENTERLINE OF THE TRAVELED WAY OF COUNTY ROAD "C" NORTH-SOUTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,699.15' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE 42.79 ACRE TRACT
- 2) 2,653.71' SOUTH TO THE 1/2" REBAR WITH AN ALUMINUM KDOT CAP HE FOUND AT THE SOUTHWEST CORNER OF THE NW1/4 OF SECTION 9-19-10, BEING THE SOUTHWEST CORNER OF THE 24.0 ACRE TRACT
- 3) 1,105.92' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE FOUND AT THE NORTHEAST CORNER OF THE 42.79 ACRE TRACT FROM A PREVIOUS SURVEY

- 14) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 19, 1998, FOR JOB NUMBER 97429-02, SAID THAT **HE FOUND THE EXISTING 5/8" REBAR AT 4" BELOW THE ROAD SURFACE** AT THE NORTHWEST CORNER OF SECTION 9-19-10 FROM HIS NUMEROUS TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE.

- 1) 41.70' NW TO A PK NAIL & SHINER IN A TREE
- 2) 29.90' NE TO A 40 D SPIKE & WASHER IN A CORNER FENCE POST
- 3) 1.5' SOUTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 180 EAST-WEST
- 4) 3.5' EAST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "C" TO THE SOUTH

- 15) AARON C. DAVIS, L.S. 1368, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 03, 2003, FOR JOB NUMBER 03026-02, SAID THAT **HE FOUND THE EXISTING SQUARE 1/2" REBAR AT 4" DEEP** AT THE SOUTHEAST CORNER OF SECTION 5-19-10 FROM EXISTING REFERENCE TIES ON FILE IN THE COUNTY ENGINEERS OFFICE.

- 1) 53.80' NW TO A CONCRETE NAIL & WASHER IN THE ROOT OF A 20" CEDAR TREE
- 2) 30.15' NE TO A 40 D SPIKE & WASHER IN A CORNER FENCE POST
- 3) 1.5' SOUTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 180 EAST-WEST
- 4) 3.5' EAST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "C" TO THE SOUTH

- 16) AARON C. DAVIS, L.S. 1368, IN A **CORRECTED** LAND SURVEY REFERENCE REPORT DATED FEBRUARY 20, 2003, FOR PROJECT NUMBER 03026-02, SURVEY F05001 IN THE SURVEY FILE FOR TOWNSHIP 19-10 FOR A SURVEY OF THE NORTH HALF OF THE SOUTH HALF OF THE NORTH HALF OF THE WEST HALF OF THE SOUTHEAST QUARTER OF SECTION 5-19-10, REVISED THE MONUMENT DESCRIPTION FOR THE SOUTHEAST CORNER OF SECTION 5-19-10 TO A **5/8" REBAR FOUND AT 4" DEEP IN GRAVEL SURFACING.**

- 1) 53.80' NW TO A CONCRETE NAIL & WASHER IN THE ROOT OF A 20" CEDAR TREE
 - 2) 30.15' NE TO A 40 D SPIKE & WASHER IN A CORNER FENCE POST
 - 3) 1.5' SOUTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 180 EAST-WEST
 - 4) 3.5' EAST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "C" TO THE SOUTH
- THE SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,325.48' WEST TO THE THEORETICAL POSITION FOR THE SOUTHWEST CORNER OF THE SE1/4 OF THE SE1/4 OF SECTION 5-19-10
- 2) 2,650.96' WEST TO THE 1/2" REBAR HE FOUND AT THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 5-19-10
- 3) 1,327.49' NORTH TO THE THEORETICAL POSITION FOR THE NORTHEAST CORNER OF THE SE1/4 OF THE SE1/4 OF SECTION 5-19-10
- 4) 2,654.98' NORTH TO THE 1/2" REBAR WITH A "MACON COMPANY" CAP HE FOUND AT THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 5-19-10

CONTINUED ON PAGE 5

- 17) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED SEPTEMBER 17, 2007 FOR PROJECT NUMBER 07319-02, SURVEY F08001 IN THE SURVEY FILE FOR TOWNSHIP 19-10 FOR A SURVEY OF THE EAST HALF OF THE NORTHEAST QUARTER AND THE NORTH HALF OF THE NORTHWEST QUARTER OF THE NORTHEAST QUARTER OF SECTION 8-19-10 FOR MERT DEBOER, SAID THAT **HE FOUND THE EXISTING 5/8" REBAR** AT THE NORTHEAST CORNER OF SECTION 8-19-10 FROM HIS EXISTING REFERENCE TIES ON FILE AT THE COUNTY ENGINEER'S OFFICE.
- 1) 53.80' NW TO A CONCRETE NAIL & WASHER IN THE ROOT OF A 20" CEDAR TREE
 - 2) 30.15' NE TO A 40 D SPIKE & WASHER IN A CORNER FENCE POST
 - 3) 1.5' SOUTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 180 EAST-WEST
 - 4) 3.5' EAST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "C" TO THE SOUTH
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,325.48' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF THE E1/2 OF THE NE1/4 OF SECTION 8-19-10
 - 2) 2,650.97' WEST TO THE 1/2" REBAR WITH A "GEOTECH" CAP HE FOUND AT THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 8-19-10
 - 3) 2,653.93' SOUTH TO THE 5/8" REBAR WITH A KDOT CAP HE FOUND AT THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 8-19-10
- 18) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED NOVEMBER 18, 2016 FOR PROJECT NUMBER 16286-02, SURVEY F09001 IN THE SURVEY FILE FOR TOWNSHIP 19-10 FOR THE SURVEY OF THE WEST RIGHT-OF-WAY LINE ON THE ROAD ON THE WEST SIDE OF THE SOUTH HALF OF SECTION 9, TOWNSHIP 19 SOUTH, RANGE 10 EAST, AKA COUNTY ROAD "C", SAID THAT **HE FOUND THE EXISTING RECORD 5/8" REBAR** AT THE NORTHEAST CORNER OF SECTION 8-19-10 FROM HIS EXISTING REFERENCE TIES ON FILE AT THE COUNTY ENGINEER'S OFFICE. HE NOTED THAT HE HAD FOUND THIS 5/8" REBAR IN 1983 AND BY THE KDOT.
- 1) 30.1' NE TO A 40 D SPIKE & WASHER IN A CORNER FENCE POST
 - 2) 40.3' NE TO A SPIKE & KDOT WASHER IN A POWER POLE
 - 3) 59.3' NE TO A SPIKE & BOTTLECAP IN A 20" CEDAR TREE
 - 4) 2.5' EAST TO THE CENTERLINE OF GRAVEL COUNTY ROAD "C" TO THE SOUTH
 - 5) 20' EAST TO A LINE OF FENCE TO THE NORTH
- HIS REPORT OF SURVEY SHOWS THE FOLLOWING INFORMATION:
- 1) 2,653.60' SOUTH TO THE 5/8" REBAR WITH A 2" ALUMINUM CAP THAT HE FOUND FROM REFERENCE TIES AT THE NORTHWEST CORNER OF THE SW1/4 OF SECTION 9-19-10
 - 2) 5,292.72' SOUTH TO THE 1/2" REBAR WITH HIS "752" CAP OVER THE 5/8" REBAR WITH 2" ALUMINUM CAP THAT HE FOUND FROM REFERENCE TIES AT THE **WITNESS CORNER AT 10.00 FEET NORTH** OF THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 9-19-10
 - 3) 5,302.72' SOUTH TO THE LOCATION FOR THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 9-19-10

NORTHWEST CORNER SECTION 09-19-10