

WEST 1/16TH CORNER OF THE SOUTHEAST QUARTER OF SECTION 09, TOWNSHIP 19 SOUTH, RANGE 10 EAST

- 1) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 44 RECORDED IN SURVEY BOOK "A" ON PAGE 140 AND DATED MAY 1, 1868 FOR A SURVEY OF LAND OWNED BY W. L. PHILIPS AND OTHERS, BEING SECTION 9-19-10, TO ESTABLISH THE CENTER CORNER, DIVIDE THE SOUTHWEST 1/4 INTO TWO 80'S RUNNING EAST AND WEST, AND TO DIVIDE THE SOUTHEAST 1/4 INTO AN 80 RUNNING NORTH AND SOUTH AND TWO 40'S, SAID THAT **HE SET A STONE** FOR THE 1/2/4 CORNER ON THE EAST SIDE OF THE SOUTHWEST 1/4 CORNER OF SECTION 9 EQUIDISTANT BETWEEN THE STONES HE SET FOR THE SOUTH 1/4 CORNER AND THE CENTER OF SECTION 9 ON THIS SURVEY.

- 2) L. A. HAMBLIN, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 113, A ROAD SURVEY RECORDED IN SURVEY BOOK "B" ON PAGE 112 DATED APRIL 10, 1871 FOR A ROAD THROUGH THE NORTH & SOUTH CENTERLINE OF SECTION 9-19-10, SAID THAT **HE FOUND THE STONE** AT THE 1/2/4 CORNER ON THE WEST SIDE OF THE SOUTHEAST 1/4 OF SECTION 9 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOW THE FOLLOWING DISTANCES:
 - 1) 20.08 CHAINS SOUTH TO THE STONE CORNER THAT HE FOUND AT THE 1/4 CORNER BETWEEN SECTIONS 9 & 16
 - 2) 19.93 CHAINS NORTH TO THE STONE CORNER THAT HE FOUND AT THE CENTER OF SECTION 9
 - 3) 59.91 CHAINS NORTH TO THE STONE CORNER THAT HE FOUND AT THE 1/4 CORNER BETWEEN SECTIONS 4 & 9

WEST SIXTEENTH CORNER SOUTHEAST QUARTER OF SECTION 09-19-10