

**WEST 1/16<sup>TH</sup> CORNER OF THE NORTHWEST QUARTER OF SECTION 10, TOWNSHIP 19 SOUTH, RANGE 10 EAST**

- 1) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 8, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 8 DATED FEBRUARY 26-27, 1884 AT THE ORDER OF A. QUAKENBUSH AND J. H. THOMAS TO SUBDIVIDE SECTION 10-19-10, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE** AT THE 1/8<sup>TH</sup> CORNER ON THE WEST SIDE OF THE NORTHWEST 1/4 OF SECTION 10-19-10 ON THIS **PERMANENT SURVEY**.
  
- 2) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN A ROAD SURVEY FOR ROAD NUMBER 671 RECORDED IN ROAD RECORD BOOK "E" ON PAGE 28 PETITION BY A. MYERS AND OTHERS FOR THE RELOCATION OF A ROAD IN SECTION 9-19-10 [PACKET 926 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT WAS VIEWED BY THE COUNTY COMMISSIONERS AND THE COUNTY SURVEYOR ON APRIL 9, 1912, RECORDED ON APRIL 9, 1912 BY MATTHEW BROWN, COUNTY SURVEYOR, AND GRANTED ON MAY 10, 1912 AS NOTED BY R. B. SHEPHERD, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 9-19-10 ON THIS ROAD SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) THIS ROAD BEGINS AT A POINT 40 FEET WEST OF THE NORTHEAST CORNER OF SECTION 9-19-10; THENCE SOUTH PARALLEL TO THE SECTION LINE TO A POINT 71 FEET SOUTH OF AN EAST AND WEST HEDGE; THENCE SOUTHWESTERLY AND SOUTHEASTERLY AROUND A PLUMB THICKET 445 FEET TO A POINT ON THE WEST LINE OF THE NORTH AND SOUTH ROAD AT 79 FEET SOUTH OF AN ELM TREE AND THERE ENDING
  - 2) IRON PINS WERE DRIVEN AT EACH POINT MENTIONED ABOVE
  - 3) ROAD 40 FEET WIDE, 20 FEET ON EACH SIDE OF THE ABOVE DESCRIBED POINTS
  
- 3) COMMISSIONER'S ROAD JOURNAL BOOK "A", PAGE 16  
ON MARCH 4, 1912 A PETITION SIGNED BY A. MEYERS AND OTHERS FOR THE RELOCATION OF A ROAD IN TOWNSHIP 19-10 WAS PRESENTED TO THE BOARD OF COUNTY COMMISSIONERS. THE ROAD WAS VIEWED ON APRIL 9, 1912, AND THE FINAL ORDER FOR RELOCATING THE FOLLOWING ROAD WAS ISSUED ON APRIL 9, 1912.
  - 1) BEGINNING AT A POINT FORTY FEET WEST OF THE NORTHEAST CORNER OF SECTION 9-19-10; THENCE SOUTH 80 RODS PARALLEL TO THE SECTION LINE; THENCE IN A SOUTHWESTERLY DIRECTION AROUND A PLUMB THICKET; THENCE IN A SOUTHEASTERLY DIRECTION TO THE PUBLIC ROAD ENTERING SAID ROAD AT AN ELM TREE ABOUT ONE HUNDRED RODS SOUTH OF THE SAID NORTHEAST CORNER OF SAID SECTION
  - 2) THE RELOCATED ROAD TO BE 40 FEET WIDE
  
- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 9, 2005, FOR PROJECT NUMBER 05184-02, SURVEY F09008 IN THE SURVEY FILE FOR TOWNSHIP 19-10 FOR THE SURVEY OF A TRACT IN THE NORTHEAST QUARTER OF SECTION 9-19-10 FOR MERT DEBOER, SAID THAT **HE FOUND A 1/2" REBAR WITH HIS "LS 752" CAP** AT THE EAST 1/16<sup>TH</sup> CORNER OF THE NORTHEAST 1/4 OF SECTION 9-19-10 FROM HIS PREVIOUS SURVEY FOR PROJECT NUMBER 96315-02 [1996].
  - 1) FALLS ON THE EAST EDGE OF A CREEK/DITCH
  - 2) 1,312.95' NORTH TO THE NORTHEAST CORNER OF SECTION 9-19-10
  - 3) 1,312.95' SOUTH TO THE EAST QUARTER CORNER OF SECTION 9-19-10

HIS TIES ARE CONTINUED ON PAGE 2

4) 60.0' WEST TO A 1/2" REBAR WITH HIS "LS 752" CAP SET

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,312.95' NORTH TO THE 5/8" REBAR HE FOUND AT THE NORTHEAST CORNER OF THE N1/2 OF THE NE1/4 OF SECTION 9-19-10
- 2) 1,312.95' SOUTH TO THE KDOT ALUMINUM CAP HE FOUND AT THE SOUTHEAST CORNER OF THE S1/2 OF THE NE1/4 OF SECTION 9-19-10
- 3) 2,662.15' WEST TO THE THEORETICAL POSITION FOR THE SOUTHWEST CORNER OF THE N1/2 OF THE NE1/4 OF SECTION 9-19-10

WEST SIXTEENTH CORNER NORTHWEST QUARTER OF SECTION 10-19-10