

WEST 1/16TH CORNER OF THE NORTHWEST QUARTER OF SECTION 16, TOWNSHIP 19 SOUTH, RANGE 10 EAST

- 1) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 1, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 199 DATED APRIL 10, 1900 AT THE ORDER OF W. H. EARL AND THE ATCHISON, TOPEKA & SANTA FE RAILROAD COMPANY TO LOCATE THE SOUTH BOUNDARY LINE OF SECTION 8-19-10, SAID THAT **HE FOUND THE STONE** AT THE 1/8TH CORNER BETWEEN THE NORTHWEST 1/4 OF SECTION 16 AND THE NORTHEAST 1/4 OF SECTION 17 ON THIS **PERMANENT SURVEY**. THERE IS ADDITIONAL INFORMATION IN PACKET "M 6" IN MISCELLANEOUS DRAWER NUMBER 1 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING DISTANCES:

- 1) 20.13 CHAINS SOUTH TO THE STONE HE FOUND AT THE 1/4 CORNER BETWEEN SECTIONS 16 & 17
 - 2) 20.12 CHAINS NORTH TO THE 24" X 9" X 5" STONE HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 8
 - 3) 60.36 CHAINS NORTH TO THE STONE HE FOUND AT THE 1/4 CORNER BETWEEN SECTIONS 8 & 9
- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 25, 1991, FOR JOB NUMBER 91253, SAID THAT **HE FOUND A 5" X 9" X 16" LIMESTONE AT 12" BELOW THE ROAD SURFACE** AT THE ENE 1/16TH CORNER OF SECTION 17. **HE SET 1/2" X 24" REBARS WITH HIS CAPS ON THE EAST AND WEST SIDES OF THE STONE.**
- 1) 1,329.02' NORTH OF THE EAST 1/4 CORNER OF SECTION 17
 - 2) 1,335.72' SOUTH OF THE **WITNESS CORNER** AT THE NORTHEAST CORNER OF SECTION 17

WEST SIXTEENTH CORNER NORTHWEST QUARTER OF SECTION 16-19-10