

CENTER CORNER OF SECTION 19, TOWNSHIP 19 SOUTH, RANGE 10 EAST

- 1) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 96 RECORDED IN SURVEY BOOK "A" ON PAGE 191 DATED MARCH 11, 1869 FOR A SURVEY OF LAND SITUATED IN SECTION 19-19-10, TO ESTABLISH THE CENTER CORNER OF THE SECTION, AND THE CENTER CORNER OF THE NORTHEAST 1/4, AND THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF THE NORTHEAST 1/4, AND THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 19, SAID THAT **HE SET A STONE** FOR THE CENTER CORNER OF SECTION 19-19-10 AT THE INTERSECTION OF THE LINES FROM THE OPPOSITE 1/4 CORNERS ON THIS SURVEY.

- 2) LESLIE M. GOULD, L.S 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN A REPORT OF A **PERMANENT SURVEY** IN SECTION 19-19-10 MADE PRIMARILY TO LOCATE THE BOUNDARIES OF THE EAST 1/2 OF THE WEST 1/2 OF SECTION 19-19-10 THAT WAS BEGUN ON APRIL 16, 1969 AND WAS COMPLETED ON APRIL 24, 1969 AND RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 53 AND RECORDED IN VOLUME 2 OF PLATS ON PAGE 58 IN THE REGISTER OF DEEDS OFFICE ON AUGUST 27, 1969, SHOWS ON HIS SURVEY DRAWING THAT **HE SET AN IRON PIN** FOR THE PERMANENT CENTER CORNER OF SECTION 19-19-10 ON THIS **PERMANENT SURVEY**. THERE ARE NO TIES ON THE SURVEY.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,320' WEST TO THE IRON PIN HE SET FOR THE PERMANENT SOUTH 1/16TH CORNER OF THE NW1/4 OF SECTION 19-19-10
 - 2) 2,625.5' WEST TO THE IRON PIN HE SET FOR THE SOUTHWEST CORNER OF THE NW1/4 OF SECTION 19-19-10 ON THE RANGE LINE AND THE LYON AND CHASE COUNTY LINE
 - 3) 1,320' EAST TO THE IRON PIN SET FOR THE PERMANENT SOUTH 1/16TH CORNER OF THE NE1/4 OF SECTION 19-19-10
 - 4) 2,640' EAST TO THE THEORETICAL LOCATION FOR THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 19-19-10

CENTER CORNER SECTION 19-19-10