

NORTH 1/16TH CORNER OF THE SOUTHWEST QUARTER OF SECTION 19, TOWNSHIP 19 SOUTH, RANGE 10 EAST

- 1) LESLIE M. GOULD, L.S 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN A REPORT OF A **PERMANENT SURVEY** IN SECTION 19-19-10 MADE PRIMARILY TO LOCATE THE BOUNDARIES OF THE EAST 1/2 OF THE WEST 1/2 OF SECTION 19-19-10 THAT WAS BEGUN ON APRIL 16, 1969 AND WAS COMPLETED ON APRIL 24, 1969 AND RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 53 AND RECORDED IN VOLUME 2 OF PLATS ON PAGE 58 IN THE REGISTER OF DEEDS OFFICE ON AUGUST 27, 1969, SHOWS ON HIS SURVEY DRAWING THAT **HE SET AND IRON PIN** FOR THE PERMANENT NORTH 1/16TH CORNER OF THE SOUTHWEST 1/4 OF SECTION 19-19-10 AT 3,960 FEET WEST OF THE TEMPORARY POINT THAT HE SET FOR THE SOUTHEAST CORNER OF THE NORTHEAST 1/4 OF SECTION 19-19-10 ON THIS **PERMANENT SURVEY**. HE NOTED ON THIS SURVEY "STATE STATUTE RULES THAT WHEN CLOSING ON A BASE LINE THE EAST HALF OF THE SOUTH HALF OF THE SECTION MUST BE 40 CHAINS OR 2,640 FEET. IN THIS CASE THE WEST COUNTY LINE IS THAT BASE LINE, THUS THE 80 ACRE TRACTS RUNNING NORTH AND SOUTH WOULD BE STANDARD WIDTH EXCEPT THE WESTERN TIER WHICH TAKES THE SHORTAGE OR THE EXCESS." THERE ARE NO TIES ON THE SURVEY.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,305.5' WEST TO THE IRON PIN HE SET FOR THE PERMANENT SOUTHWEST CORNER OF THE NW1/4 OF SECTION 19-19-10 ON THE RANGE LINE AND THE LYON AND CHASE COUNTY LINE
- 2) 1,320' EAST TO THE IRON PIN HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 19-19-10
- 3) 2,640' EAST TO THE IRON PIN HE SET FOR THE PERMANENT NORTH 1/16TH CORNER OF THE SE1/4 OF SECTION 19-19-10
- 4) 3,960' EAST TO THE TEMPORARY POINT HE SET FOR THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 19-19-10

NORTH SIXTEENTH CORNER SOUTHWEST QUARTER OF SECTION 19-19-10