

**WEST 1/4 CORNER SECTION 20, TOWNSHIP 19 SOUTH, RANGE 10 EAST**

- 1) ON PAGE 217 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 14" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 19 & 20-19-10.
- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 95 RECORDED IN SURVEY BOOK "A" ON PAGE 190 DATED MARCH 9 & 10, 1869 FOR A SURVEY OF LAND SITUATED IN SECTION 20-19-10, TO ESTABLISH THE NORTHWEST CORNER OF THE SOUTHWEST 1/4 OF THE NORTHWEST 1/4, AND THE NORTHEAST CORNER OF THE SOUTHWEST 1/4 OF THE NORTHEAST 1/4, AND THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF THE SOUTHEAST 1/4 OF SAID SECTION 20-19-10, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 20-19-10 ON THIS SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 159 RODS, 9 LINKS NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 20-19-10
- 3) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 96 RECORDED IN SURVEY BOOK "A" ON PAGE 191 DATED MARCH 11, 1869 FOR A SURVEY OF LAND SITUATED IN SECTION 19-19-10, TO ESTABLISH THE CENTER CORNER OF THE SECTION, AND THE CENTER CORNER OF THE NORTHEAST 1/4, AND THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF THE NORTHEAST 1/4, AND THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SAID SECTION 19-19-10, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 19-19-10 ON THIS SURVEY.
- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 115, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 195 DATED FEBRUARY 1905 FOR TRACTS IN THE NORTH 1/2 OF THE NORTHWEST 1/4 OF SECTION 20, TOWNSHIP 19, RANGE 10, SAID THAT **HE FOUND AN EAST-WEST FENCE** FOR THE WEST 1/4 CORNER OF SECTION 20-19-10 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK 2 ON PAGE 130 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 87" IN MISCELLANEOUS DRAWER NUMBER 4 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 20.10 CHAINS NORTH TO THE STAKE HE SET FOR THE WEST 1/2/4 CORNER OF THE NW1/4 OF SECTION 20-19-10
  - 2) 40.20 CHAINS NORTH TO THE STONE HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 20-19-10
- 5) LESLIE M. GOULD, L.S 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN A REPORT OF A **PERMANENT SURVEY** IN SECTION 19-19-10 MADE PRIMARILY TO LOCATE THE BOUNDARIES OF THE EAST 1/2 OF THE WEST 1/2 OF SECTION 19-19-10 THAT WAS BEGUN ON APRIL 16, 1969 AND WAS COMPLETED ON APRIL 24, 1969 AND RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 53 AND RECORDED IN VOLUME 2 OF PLATS ON PAGE 58 IN THE REGISTER OF DEEDS OFFICE ON AUGUST 27, 1969, SHOWS ON HIS SURVEY DRAWING THAT **HE SET A TEMPORARY POINT** FOR THE SOUTHEAST CORNER OF THE NORTHEAST 1/4 OF SECTION 19-19-10 ON THIS **PERMANENT SURVEY**. HE NOTED THAT ACCORDING TO GOVERNMENT SURVEY NOTES THE EAST LINE OF SECTIONS 19-19-10 AND 30-19-10 IS ON A TANGENT OR STRAIGHT LINE FOR 5 MILES. THEREFORE THE EAST LINE OF SECTION 30-19-10 WAS PRODUCED NORTH TO ARRIVE AT THE RESULTS AS SHOWN ON THIS PERMANENT SURVEY.

HIS INFORMATION IS CONTINUED ON PAGE 2

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,645.25' NORTH TO THE POSITION OF THE NORTHEAST CORNER OF SECTION 19-19-10 – NO CORNER SET DUE TO CROP
- 2) 2,645.25' SOUTH TO THE TEMPORARY POINT HE SET FOR THE SOUTHEAST CORNER OF SECTION 19-19-10
- 3) 3,967.87' SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE N1/2 OF THE NE1/4 OF SECTION 30-19-10
- 4) 1,320' WEST TO THE IRON PIN HE SET FOR THE PERMANENT NORTH 1/16<sup>TH</sup> CORNER OF THE SE1/4 OF SECTION 19-19-10
- 5) 2,640' WEST TO THE IRON PIN HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 19-19-10
- 6) 3,960' WEST TO THE IRON PIN SET FOR THE PERMANENT NORTH 1/16<sup>TH</sup> CORNER OF THE SW1/4 OF SECTION 19-19-10
- 7) 5,265.5' WEST TO THE IRON PIN HE SET FOR THE PERMANENT SOUTHWEST CORNER OF THE NW1/4 OF SECTION 19-19-10 ON THE RANGE LINE AND CHASE COUNTY LINE

WEST QUARTER CORNER SECTION 20-19-10