

NORTH 1/4 CORNER OF SECTION 21, TOWNSHIP 19 SOUTH, RANGE 10 EAST

- 1) ON PAGE 212 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 19" X 13" X 2-1/2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 16 & 21-19-10.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.88-1/2 CHAINS WEST TO THE 16" X 14" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 16, 17, 20 & 21-19-10
 - 2) 39.88-1/2 CHAINS EAST TO THE 16" X 11" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 15, 16, 21 & 22-19-10

- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, BY D. W. BOWMAN, DEPUTY, IN SURVEY NUMBER 46 RECORDED IN SURVEY BOOK "A" ON PAGE 142 DATED MAY 2 & 6, 1868 FOR A SURVEY OF LAND OWNED BY PHILLIPS, LEWIS, STOUT AND OTHERS, BEING SECTION 16-19-10, TO ESTABLISH THE CENTER CORNER, TO DIVIDE THE NORTHWEST 1/4 INTO TWO 80'S RUNNING NORTH & SOUTH, AND TO LAY OFF A PORTION OF LAND 20 RODS WIDE ON THE EAST SIDE OF THE WEST 1/2 OF THE NORTHEAST 1/4 OF SAID SECTION 16, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 16-19-10 ON THIS SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 320 RODS, 17 LINKS NORTH TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 16-19-10

- 3) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, BY D. W. BOWMAN, DEPUTY, IN SURVEY NUMBER 61 RECORDED IN SURVEY BOOK "A" ON PAGES 160 & 161 DATED MAY 28, 1868 FOR A SURVEY OF LAND OWNED BY NEWITT AND OTHERS, BEING SECTION 16-19-10, TO DIVIDE THE SOUTHWEST 1/4 INTO TWO EQUAL PARTS BY A LINE RUNNING NORTH & SOUTH, TO DIVIDE THE WEST 1/2 OF THE 1/4 INTO TWO EQUAL PARTS BY A LINE RUNNING EAST AND WEST, AND TO DIVIDE THE SOUTHWEST 1/4 OF THE SOUTHWEST 1/4 INTO 5 LOTS, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 16-19-10 ON THIS SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 80 RODS WEST TO THE STONE HE SET FOR THE SOUTHEAST CORNER OF THE W1/2 OF THE SW1/4 OF SECTION 16-19-10
 - 2) 160 RODS WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 16-19-10
 - 3) 80 RODS, 12 LINKS NORTH TO THE STONE HE SET FOR THE DIVISIONAL CORNER
 - 4) 160 RODS, 24 LINKS NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF THE W1/2 OF THE SE1/4 OF SECTION 16-19-10

- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 35 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 90 DATED JULY 23, 1874 TO ESTABLISH THE CENTER CORNER OF SECTION 21-19-10 AND SUBDIVIDE THE NORTHEAST 1/4 INTO 4 EQUAL PARTS, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 21-16-10 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 981-1/8' EAST TO THE 16" X 12" X 3" STONE HE SET FOR A PROPERTY DIVISION CORNER

NORTH QUARTER CORNER OF SECTION 21-19-10