

**NORTHWEST CORNER SECTION 21, TOWNSHIP 19 SOUTH, RANGE 10 EAST**

- 1) ON PAGE 210 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 5-1/2" X 4"** FOR THE CORNER TO SECTIONS 16, 17, 20 & 21-19-10.  
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 39.88-1/2 CHAINS EAST TO THE 19" X 13" X 2-1/2" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 16 & 21-19-10
  - 2) 79.77 CHAINS EAST TO THE 16" X 11" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 15, 16, 21 & 22-19-10
  
- 2) E. B. KIRKENDALL, SURVEYOR, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 6 & 7 [PACKET 392 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] FOR THE "PLYMOUTH AND COHOLA ROAD" SURVEYED AUGUST 21, 1858, AND RECORDED IN THE COMMISSIONER'S JOURNAL ON PAGE 24 ON AUGUST 30, 1858, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 16-19-10 TO START THIS ROAD SURVEY. NO WIDTH IS RECORDED AND BY THE TERRITORIAL LAW IN EFFECT AT THE TIME THE ROAD WOULD BE FORTY FEET WIDE.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES TO THE WEST 1/4 CORNER OF SECTION 16-19-10, THEN TURNS WEST
  
- 3) H. S. SLEEPER, BRECKENRIDGE COUNTY SURVEYOR FROM 1859 TO 1862, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGE 29 [PACKET 911 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] FOR A TOWNSHIP ROAD IN PIKE TOWNSHIP PETITIONED BY WILLIAM EIKENBERRY AND OTHERS THAT WAS SURVEYED ON OCTOBER 24, 1860 AND ESTABLISHED OCTOBER 29, 1860 IN COMMISSIONERS JOURNAL ON PAGE 125, APPARENTLY **FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 20-19-10 AT THE TERMINUS OF THIS ROAD SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES WITH A DEVIATION IN THE NORTHEAST 1/4 OF SECTION 20-19-10 DUE TO THE COTTONWOOD RIVER AND INTERSECTS THE EAST LINE OF THE NORTHEAST 1/4 OF SECTION 20-19-10 AT AN ANGLE POINT 44 RODS NORTH OF THE EAST 1/4 CORNER OF SECTION 20-19-10 THEN CONTINUES SOUTH ON THE SECTION LINES TO THE SOUTHEAST CORNER OF SECTION 32-19-10 ON THE TOWNSHIP LINE TO COMMENCE THIS ROAD SURVEY
  
- 4) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, BY D. W. BOWMAN, DEPUTY, IN SURVEY NUMBER 46 RECORDED IN SURVEY BOOK "A" ON PAGE 142 DATED MAY 2 & 6, 1868 FOR A SURVEY OF LAND OWNED BY PHILLIPS, LEWIS, STOUT AND OTHERS, BEING SECTION 16-19-10, TO ESTABLISH THE CENTER CORNER, TO DIVIDE THE NORTHWEST 1/4 INTO TWO 80'S RUNNING NORTH & SOUTH, TO DIVIDE THE NORTHEAST 1/4 INTO TWO 80'S RUNNING NORTH & SOUTH, AND TO LAY OFF A PORTION OF LAND 20 RODS WIDE ON THE EAST SIDE OF THE WEST 1/2 OF THE NORTHEAST 1/4 OF SECTION 16-19-10, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 16-19-10 ON THIS SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 321 RODS, 17 LINKS NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 16-19-10
  
- 5) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, BY D. W. BOWMAN, DEPUTY, IN SURVEY NUMBER 61 RECORDED IN SURVEY BOOK "A" ON PAGES 160 & 161 DATED MAY 28, 1868 FOR A SURVEY OF LAND OWNED BY NEWITT AND

OTHERS, BEING SECTION 16-19-10, TO DIVIDE THE SOUTHWEST 1/4 INTO TWO EQUAL PARTS BY A LINE RUNNING NORTH & SOUTH, TO DIVIDE THE WEST 1/2 OF THE 1/4 INTO TWO EQUAL PARTS BY A LINE RUNNING EAST AND WEST, AND TO DIVIDE THE SOUTHWEST 1/4 OF THE SOUTHWEST 1/4 INTO 5 LOTS, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 16-19-10 ON THIS SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 80 RODS, 10-1/2 LINKS TO THE **TRUE LOCATION** FOR THE SOUTHWEST CORNER OF THE NW1/4 OF THE SW1/4 OF SECTION 16-19-10 – FALLS IN THE COTTONWOOD RIVER
  - 2) 160 RODS, 21 LINKS NORTH TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 16-19-10
  - 3) 80 RODS EAST TO THE STONE HE SET FOR THE SOUTHEAST CORNER OF THE W1/2 OF THE SW1/4 OF SECTION 16-19-10
  - 4) 160 RODS EAST TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 16-19-10
- 6) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 95 RECORDED IN SURVEY BOOK “A” ON PAGE 190 DATED MARCH 9 & 10, 1869 FOR A SURVEY OF LAND SITUATED IN SECTION 20-19-10, TO ESTABLISH THE NORTHWEST CORNER OF THE SOUTHWEST 1/4 OF THE NORTHWEST 1/4, AND THE NORTHEAST CORNER OF THE SOUTHWEST 1/4 OF THE NORTHEAST 1/4, AND THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF THE SOUTHEAST 1/4 OF SAID SECTION 20-19-10, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 20-19-10 ON THIS SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 159 RODS, 8 LINKS WEST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 20-19-10
  - 2) 320 RODS, 11 LINKS SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 20-19-10
- 7) **REA PIN—MUST VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY JUST "HEELED-IN" FOR UTILITY USE ONLY – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR** REA BOOK 31 ON PAGE 16 SHOWS THAT **THEY DROVE AN IRON PIN** FOR THE NORTHWEST CORNER OF SECTION 21-19-10.
- 1) 19’ EAST TO A WITNESS PIN
  - 2) 23.25’ NE TO A WITNESS PIN
- 8) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 19-10 SHOWS A **REA PIN** AT THE “SE CORNER SECTION 17-19-10” AND “NE CORNER SECTION 20-19-10” AND “NW CORNER SECTION 21-19-10”. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY JUST "HEELED-IN" FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
- 1) 19’ EAST TO A WITNESS [REA]

NORTHWEST CORNER SECTION 21-19-10