

**NORTH 1/4 CORNER SECTION 22, TOWNSHIP 19 SOUTH, RANGE 10 EAST**

- 1) ON PAGE 205 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 10" X 2-1/2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 15 & 22-19-10.  
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 40.03-1/2 CHAINS WEST TO THE 16" X 11" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 15, 16, 21 & 22-19-10
  - 2) 40.03-1/2 CHAINS EAST TO THE 25" X 7" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 14, 15, 22 & 23-19-10
  
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 10 OF THE 8<sup>TH</sup> TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 65 DATED MARCH 7, 1874 TO ESTABLISH THE CENTER CORNER AND SUBDIVIDE THE SOUTHWEST 1/4 OF SECTION 15-19-10 INTO VARIOUS PARTS, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 15-19-10 ON THIS **PERMANENT SURVEY**.
  
- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 2, 1999, FOR PROJECT NUMBER 99029-02, [LYON COUNTY PROJECT NUMBER 98-2Z, SITE 2], LARGE SURVEY SR #22001 IN THE SURVEY DRAWER FOR TOWNSHIP 19-10, SAID THAT **HE FOUND THE GLO STONE WITH A REBAR BENT OVER THE TOP OF THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 22-19-10.
  - 1) 34.9' SW TO A PK NAIL & WASHER IN A POWER POLE
  - 2) 24.8' SOUTH TO A LINE OF POWER POLES EAST-WEST
  - 3) IN THE CENTERLINE TRAVELED WAY OF THE ROADHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 2,648.25' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHWEST CORNER OF SECTION 22-19-10
  - 2) 5,293.53' EAST TO THE GLO STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 23-19-10

NORTH QUARTER CORNER SECTION 22-19-10