

**NORTHWEST CORNER SECTION 22, TOWNSHIP 19 SOUTH, RANGE 10 EAST**

- 1) ON PAGE 204 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 11" X 4"** FOR THE CORNER TO SECTIONS 15, 16, 21 & 22-19-10.  
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 40.03-1/2 CHAINS EAST TO THE 24" X 20" X 2" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 15 & 22-19-10
  - 2) 80.07 CHAINS EAST TO THE 25" X 7" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 15, 16, 21 & 22-19-10
  
- 2) IN ROAD RECORD BOOK "A" ON PAGE 153 [PACKET 313 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE] BY THE PETITION OF MARK PATTY AND OTHERS FOR A SECTION LINE ROAD IN TOWNSHIP 19-10 WITHOUT A SURVEY, IT WAS ORDERED BY THE BOARD OF COUNTY COMMISSIONERS THAT THE FOLLOWING SECTION LINE BE ESTABLISHED AS PETITIONED FOR, AND THE SAME OPENED TO PUBLIC TRAVEL ON JULY 11, 1870 AS NOTED BY DAVID S. GILMORE, COUNTY CLERK.  
THE SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) THIS SECTION LINE ROAD ENDS AT THE NORTHWEST CORNER OF SECTION 22-19-10 AND EXTENDS EAST ON THE SECTION LINE TO THE WESTERN TERMINUS OF THE PUBLIC ROAD NOW LOCATED ON SAID SECTION LINE TO THE BEGINNING OF THIS SECTION LINE ROAD
  
- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 10 OF THE 8<sup>TH</sup> TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 65 DATED MARCH 7, 1874 TO ESTABLISH THE CENTER CORNER AND SUBDIVIDE THE SOUTHWEST 1/4 OF SECTION 15-19-10 INTO VARIOUS PARTS, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTIONS 15-19-10 ON THIS **PERMANENT SURVEY**.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 238-3/4' NORTH TO THE 14" X 12" X 3" STONE HE SET FOR THE PERMANENT NORTHWEST CORNER OF A 4 ACRE LOT
  - 2) 700' EAST TO THE 14" X 5" X 3" STONE HE SET AT 25 FEET WEST OF THE LEFT BANK OF THE COTTONWOOD RIVER
  
- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 35 OF THE 8<sup>TH</sup> TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 90 DATED JULY 23, 1874 TO ESTABLISH THE CENTER CORNER OF SECTION 21-19-10 AND SUBDIVIDE THE NORTHEAST 1/4 INTO 4 EQUAL PARTS, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 21-19-10 ON THIS **PERMANENT SURVEY**.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 330' SOUTH TO THE NORTHEAST CORNER OF JOSEPH KEYES ESTATE
  
- 5) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 226 & 227 FOR A PETITION BY JAMES STOUT AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 19-10 [PACKET 180 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON DECEMBER 14, 1875, AND WAS GRANTED ON JANUARY 3, 1876 AND THE TRUSTEE NOTIFIED TO OPEN, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 22-19-10 TO BEGIN THIS ROAD SURVEY. IT WAS NOTED THAT "FROM THE STARTING POINT TO WHERE WE INTERSECTED THE SECTION LINE A DISTANCE OF 1,640 FEET THE ROAD SHALL BE 30 FEET WIDE AND FROM THERE TO THE TERMINATION OF THE ROAD IT SHALL BE 40 FEET WIDE".  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES FOR 643 FEET TO A TURN TO THE NORTHEASTERLY DUE TO THE COTTONWOOD RIVER, AND FROM THE BEGINNING OF THIS ROAD SURVEY TO WHERE IT INTERSECTS THE SECTION LINE AT 3,695' SOUTH OF THE NORTHWEST CORNER OF SECTION 15-19-10 IT IS 30 FEET WIDE; AND CONTINUES NORTH ON THE SECTION LINES AT 40 FEET WIDE FOR 3,695' TO THE NORTHWEST CORNER OF SECTION 15-19-10 TO THE TERMINATION OF THIS ROAD SURVEY
  
- 6) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON PAGE 145 FOR A PETITION BY JAMES STOUT ET. AL DATED DECEMBER 14, 1875, APPARENTLY **FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 15-19-10 ON THIS ROAD SURVEY.
  
- 7) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1875 TO 1882, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A SURVEY RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 76 TO SET **WITNESS STONES** TO MARK THE SPOT FROM WHICH A CORNER STONE WAS REMOVED IN MAKING THE FILL WEST OF PATTY'S MILL BRIDGE [THE NORTHWEST CORNER OF SECTION 22-19-10], SAID THAT HE SET THE FOLLOWING **WITNESSES** ON THIS **PERMANENT SURVEY**. THE SURVEY WAS ENTERED ON DECEMBER 30, 1910.
  - 1) SOUTH FOR 49 FEET AND HE PLANTED A STONE 15" X 8" X 4"
  - 2) S. 45° W. FOR 59.2 FEET AND HE DROVE AN IRON PIN 1/2" IN DIAMETER AND 15" LONG
  - 3) N. 45° W. FOR 68.2 FEET AND HE DROVE AN IRON GAS PIPE 3 FEET LONG AND 3/4" IN DIAMETER
  
- 8) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 02, 1999, FOR PROJECT NUMBER 99029-02, [LYON COUNTY PROJECT NUMBER 98-2Z, SITE 2], LARGE SURVEY SR #22002 IN THE SURVEY DRAWER FOR TOWNSHIP 19-10, SAID THAT HE EXCAVATED FOR THE STONE AT THE NORTHWEST CORNER OF SECTION 22-19-10, BUT HE DID **NOT** FIND THE STONE. **HE SET A 5/8" REBAR WITH A LYON COUNTY CAP** FOR THE NORTHWEST CORNER OF SECTION 22-19-10.
  - 1) 7.0' EAST TO A 40 D SPIKE IN A 16" DIAMETER HACKBERRY TREE
  - 2) 1.3' SOUTH TO A 40 D SPIKE IN A 14" DIAMETER HACKBERRY TREE
  - 3) 6.8' WSW TO A 40 D SPIKE IN AN 8" DIAMETER HACKBERRY TREE
  - 4) 144.8' ESE TO THE TOP CENTER OF A TELEPHONE PEDESTAL

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

  - 1) 2,648.25' EAST TO THE GLO STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 22-19-10

NORTHWEST CORNER SECTION 22-19-10