

**NORTHWEST CORNER SECTION 23, TOWNSHIP 19 SOUTH, RANGE 10 EAST**

- 1) ON PAGE 199 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 25" X 7" X 5"** FOR THE CORNER TO SECTIONS 14, 15, 22 & 23-19-10.  
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 39.99 CHAINS EAST TO THE 19" X 12" X 2-1/2" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 14 & 23-19-10
  - 2) 79.98 CHAINS EAST TO THE 20" X 12" X 2-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 14, 15, 22 & 23-19-10
  
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 151 TO 153 [PACKET 313 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE] ON THE PETITION OF JOEL HAWORTH AND OTHERS FOR A ROAD IN TOWNSHIP 19-10 THAT HE FILED ON JULY 2, 1870 THAT WAS APPROVED AND ORDERED BY THE BOARD OF COUNTY COMMISSIONERS ON JULY 5, 1870 AS NOTED BY DAVID S. GILMORE, COUNTY CLERK, SHOWS ON HIS SURVEY DRAWING FOR A 50 FOOT WIDE ROAD THAT ENDS AT THE NORTHWEST CORNER OF SECTION 23-19-10.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINE FOR 256-3/4 RODS TO A TURN TO THE SOUTH AND SOUTHWESTERLY AROUND THE COTTONWOOD RIVER
  
- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 72 OF THE 7<sup>TH</sup> TERM, A ROAD SURVEY RECORDED IN SURVEY BOOK "B" ON PAGE 220 DATED NOVEMBER 25, 1872 FOR A ROAD BETWEEN SECTIONS 14 & 15-19-10, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 14-19-10 TO BEGIN THIS ROAD SURVEY.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 2,080' NORTH TO AN ANGLE POST HE SET ON THE SECTION LINE
  
- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGE 206 [PACKET 78 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY JOHN MOORE AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 19-10 THAT HE SURVEYED NOVEMBER 23, 1872, AN WAS ORDERED ESTABLISHED A PUBLIC HIGHWAY BY THE COUNTY COMMISSIONERS ON JANUARY 6, 1873 SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 23-19-10 TO BEGIN THIS ROAD SURVEY. THE ROAD WAS 50 FEET WIDE FROM THE BEGINNING OF THIS ROAD SURVEY AT THE NORTHWEST CORNER OF SECTION 23-19-10 TO THE NORTH BANK OF THE COTTONWOOD RIVER, AND THEN 40 FEET WIDE TO THE TERMINUS OF THIS ROAD SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINE FOR 126 RODS TO THE SOUTH BANK OF THE COTTONWOOD RIVER AT A TURN TO THE EASTERLY DUE TO THE COTTONWOOD RIVER
  
- 5) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 2, 1999, FOR PROJECT NUMBER 99029-02, FOR THE LYON COUNTY ROAD & BRIDGE DEPARTMENT FOR PROJECT 98-2Z, SITE 2, LARGE SURVEY SR #22002 IN THE SURVEY DRAWER FOR TOWNSHIP 19-10, SAID THAT **HE FOUND A 3/4" REBAR** AT THE NORTHEAST CORNER OF SECTION 22-9-10 ON THIS SURVEY.

HIS TIES ARE ON PAGE 2

- 1) IN THE CENTERLINE TRAVELED WAY OF THE ROAD TO THE SOUTH
  - 2) 3' NORTH TO THE CENTERLINE TRAVELED WAY OF THE ROAD EAST-WEST
  - 3) 19.6' ESE TO A 1/2" REBAR AT THE EDGE OF THE ROADWAY
  - 4) 18.4' ENE TO A 1/2" REBAR AT THE EDGE OF THE ROADWAY
- 6) WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 14, 2006, FOR PROJECT NUMBER 06-LA, **FOUND THE 3/4" REBAR AT 2" BELOW THE ROAD SURFACE** AT THE NORTHWEST CORNER OF SECTION 23-19-10 FROM THE TIES OF STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, DATED APRIL 1999. **I LOWERED THE TOP OF THE REBAR TO 4" BELOW THE ROAD SURFACE.**
- 1) 19.6' ESE TO A 1/2" REBAR FOUND AT THE EDGE OF THE ROADWAY
  - 2) 18.4' ENE TO A 1/2" REBAR FOUND AT THE EDGE OF THE ROADWAY
  - 3) IN THE CENTERLINE TRAVELED WAY OF GRAVEL COUNTY ROAD "E" NORTH-SOUTH
  - 4) 3' WEST TO THE CENTERLINE TRAVELED WAY OF GRAVEL COUNTY ROAD 160 TO THE WEST

NORTHWEST CORNER SECTION 23-19-10