

NORTH 1/4 CORNER SECTION 26, TOWNSHIP 19 SOUTH, RANGE 10 EAST

- 1) ON PAGE 198 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 12" X 2-1/2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 23 & 26-19-10.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.03-1/2 CHAINS WEST TO THE 23" X 10" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 22, 23, 26 & 27-19-10
 - 2) 40.03-1/2 CHAINS EAST TO THE 18" X 11" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 23, 24, 25 & 26-19-10

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 13 IN THE 12TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 13 DATED FEBRUARY 22, 1882 TO ESTABLISH THE CORNER TO SECTIONS 23, 24, 25 AND 26-19-10, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 26-19-10 ON THIS **PERMANENT SURVEY**. HE NOTED THAT THE REPORT OF THIS SURVEY WAS FILED WITH THE REGISTER OF DEEDS ON MARCH 6, 1882.

- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 140, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 221 DATED JANUARY 16, 1906 AT THE ORDER OF S. C. GILBERT FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE NORTHWEST 1/4 OF SECTION 26-19-10 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE SET A 16" X 10" X 4" STONE ABOUT 4 FEET WEST OF FENCES TO THE NORTH AND SOUTH, 23 FEET NORTH OF THE FENCE ON THE SOUTH SIDE OF THE ROAD, AND 17 FEET FROM THE FENCE ON THE NORTH SIDE OF THE ROAD**, FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 26-19-10 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 26-19-10 AND THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 26-19-10 ON THIS **PERMANENT SURVEY**. SEE ALSO BOOK "E" IN THE KRETSINGER COLLECTION FOR THE GILBERT SURVEY DATED JANUARY 16, 1906 ON PAGES 6-9, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 170" IN MISCELLANEOUS DRAWER NUMBER 8 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.97-1/2 CHAINS WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 26-19-10, AT 20 FEET SOUTH OF A FENCE TO THE WEST, 20-1/2 FEET SOUTH OF A FENCE TO THE EAST, AND 19'-8" @ S. 29°15' E. TO A HOLE DRILLED IN A LARGE STONE ON THE WEST END OF A CULVERT
 - 2) 39.97-1/2 CHAINS EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 26-19-10, AT 22 FEET WEST OF A HEDGE, 19 FEET SOUTH OF A FENCE TO THE WEST, AND 19-1/2 FEET NORTH OF A FENCE TO THE WEST
 - 3) 20.06-1/2 CHAINS SOUTH TO THE **TRUE POSITION** FOR THE WEST 1/2/4 CORNER OF THE NE1/4 OF SECTION 26-19-10, AS WITNESSED BY THE 1" GAS PIPE 6 FEET LONG HE SET AT THE WATERS EDGE ON THE SOUTH SIDE OF A CREEK AT 15' SOUTH OF THE **TRUE CORNER**
 - 4) 40.13 CHAINS SOUTH TO THE 22" X 8" X 4" STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 26-19-10, AT 32-1/2' FEET NORTH OF A LARGE OSAGE TREE IN THE HEDGE
 - 5) 60.17 CHAINS SOUTH TO THE 18" X 6" X 4" STONE HE SET FOR THE PERMANENT WEST 1/2/4 CORNER OF THE SE1/4 OF SECTION 26-19-10, ON THE SLOPE OF A CREEK BANK AND AN 8" WALNUT TREE STANDS 3 FEET SOUTH AND 1 FOOT WEST OF THE STONE

HIS INFORMATION IS CONTINUED ON PAGE 2

- 6) 80.21 CHAINS SOUTH TO THE 18" X 9" X 3" STONE HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 26-19-10, BY THE AFFIDAVIT OF W. C. WORKMAN, AT 21 FEET BETWEEN HEDGES NORTH AND SOUTH, AND MIDWAY BETWEEN LINES OF HEDGE EXTENDING NORTH AND SOUTH

- 4) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 19-10 SHOWS A **STONE** AT THE "SW CORNER SE1/4 SECTION 23-19-10".
 - 1) 19.5' NORTH TO A SPIKE & WASHER
 - 2) 30.5' SOUTH TO A SPIKE & WASHER
 - 3) 31.5' EAST OF SOUTH TO A SPIKE & WASHER

- 5) KRETSINGER REFERENCE TIE BOOK 13 ON PAGE 61 AT THE MIDDLE OF THE PAGE SHOWS A **STONE** AT THE "N1/4 CORNER SECTION 26-19-10".
 - 1) 30' NW TO AN IRON PIN
 - 2) 25.6' NNW TO THE NEAR FACE OF AN 8" ASH TREE
 - 3) 17.0' NNE TO THE CORNER OF A STUMP
 - 4) 30.0' NE TO AN IRON PIN
 - 5) 22.3' SSE TO THE CORNER OF A STUMP

- 6) LARGE SURVEY SR #26001 IN THE SURVEY DRAWER FOR TOWNSHIP 19-10 WITH NO NAME OR DATE SHOWS A **STONE** AT THE NORTH 1/4 CORNER OF SECTION 26-19-10.
 - 1) 19.5' NORTH TO A SPIKE & WASHER
 - 2) 30.0' SOUTH TO A SPIKE & WASHER
 - 3) 31.5' EAST OF SOUTH TO A SPIKE & WASHER

- 7) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED NOVEMBER 30, 1982, SAID THAT **HE FOUND A 4" X 10" LIMESTONE** AT THE NORTH 1/4 CORNER OF SECTION 26-19-10 THAT WAS SET BY ALVA J. SMITH IN A 1906 PERMANENT SURVEY. **HE SET 5/8" REBARS WITH LYON COUNTY CAPS ON THE NORTH AND SOUTH SIDES OF THE STONE.**
 - 1) 31.1' SSE TO A SPIKE & WASHER IN A FENCE POST
 - 2) 30.4' SOUTH TO A SPIKE & 2 WASHERS IN A FENCE POST
 - 3) 31.0' SOUTH TO A LINE OF WIRE FENCE TO THE EAST
 - 4) 20.0' NORTH TO A LINE OF WIRE FENCE TO THE WEST
 - 5) **1.7' ENE TO A 1/2" REBAR FOUND**
 - 6) 31.5' SOUTH TO A LINE OF POWER POLES TO THE WEST

HIS DRAWING ON HIS REFERENCE REPORT SHOWS THE FOLLOWING

 - 1) 2,638.05' WEST TO THE NORTHWEST CORNER OF SECTION 26-19-10
 - 2) 2,637.35' EAST TO THE NORTHEAST CORNER OF SECTION 26-19-10

- 8) WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 21, 2001, **FOUND THE 4" X 10" LIMESTONE AT 13" BELOW THE ROAD SURFACE WITH 5/8" REBARS WITH LYON COUNTY CAPS ON THE NORTH AND SOUTH SIDES OF THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 26-19-10 FROM EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE BY STEVEN S. BROSEMER, L.S. 752, DATED NOVEMBER 30, 1982. THE STONE WAS SET BY COUNTY SURVEYOR ALVA J. SMITH IN A 1906 PERMANENT SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 221 IN THE COUNTY ENGINEER'S OFFICE.
 - 1) 31.3' SSE TO A SPIKE & WASHER IN A RAILROAD TIE BRACE POST
 - 2) 30.8' SOUTH TO A SPIKE & 2 WASHERS IN A RAILROAD TIE CORNER FENCE POST
 - 3) 31.8' SE TO A MAG NAIL IN THE NORTHWEST FACE OF A POWER POLE
 - 4) 31' SOUTH TO A LINE OF WIRE FENCE TO THE EAST
 - 5) 31.5' SOUTH TO A LINE OF POWER POLES EAST-WEST

NORTH QUARTER CORNER SECTION 26-19-10