

WEST 1/16TH CORNER OF THE SOUTHWEST QUARTER OF SECTION 27, TOWNSHIP 19 SOUTH, RANGE 10 EAST

- 1) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 80, A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 112 DATED JULY 28, 1903 FOR A COUNTY ROAD IN TOWNSHIP 19, RANGE 10, SAID THAT **HE FOUND THE STONE** AT THE 1/2/4 CORNER ON THE WEST SIDE OF THE SOUTHWEST 1/4 OF SECTION 27-19-10. HE USED THIS STONE AND THE STONE THAT HE FOUND AT THE 1/4 CORNER BETWEEN SECTIONS 27 & 28-19-10, AND THE STONE THAT HE FOUND AT THE 1/4 CORNER BETWEEN SECTIONS 33 & 35-19-10 TO SET A 16" X 12" X 4" STONE MARKED "R" ON THE WEST FACE FOR THE NORTHEAST CORNER OF SECTION 33-19-10 ON THIS ROAD SURVEY. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 188 IN THE "KRETSINGER COLLECTION". THERE IS NO WIDTH RECORDED ON THIS ROAD SURVEY.

HIS NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

HIS NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 19.96 CHAINS NORTH TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 27-19-10
 - 2) 19.96 CHAINS SOUTH TO THE 16" X 12" X 4" ROAD STONE MARKED "R" HE SET FOR THE NORTHEAST CORNER OF SECTION 33-19-10 FOR THE ROAD BEGINNING AT THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 30-19-10 ON THE TOWNSHIP LINE AND THE LYON AND CHASE COUNTY LINE EXTENDING EAST ON THE SECTION LINES FOR 4 MILES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 34-19-10 AT THE END OF THIS ROAD SURVEY FOR A 40 FOOT WIDE ROAD, BEING 20 FEET EACH SIDE OF THE SECTION LINES
 - 3) 60.00 CHAINS SOUTH TO THE STONE HE FOUND AT THE 1/4 CORNER BETWEEN SECTIONS 33 & 34-19-10 IN LINE WITH THE FENCES AND 20 FEET WEST OF A STONE WALL
- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY FOR ROAD NUMBER 584 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 205 THROUGH 208 PETITION BY WILLIAM EVANS AND OTHERS FOR REMARKING A ROAD IN TOWNSHIP 19-10 [PACKET 726 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JULY 28, 1903, SAID THAT **HE FOUND THE STONE** AT THE 1/2/4 CORNER ON THE WEST SIDE OF THE SOUTHWEST 1/4 OF SECTION 27-19-10 ON THIS ROAD SURVEY.
- HIS NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 4) 19.96 CHAINS NORTH TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 27-19-10
 - 5) 19.96 CHAINS SOUTH TO THE 16" X 12" X 4" ROAD STONE MARKED "R" HE SET FOR THE NORTHEAST CORNER OF SECTION 33-19-10 FOR THE ROAD BEGINNING AT THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 30-19-10 ON THE TOWNSHIP LINE AND THE LYON AND CHASE COUNTY LINE EXTENDING EAST ON THE SECTION LINES FOR 4 MILES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 34-19-10 AT THE END OF THIS ROAD SURVEY FOR A 40 FOOT WIDE ROAD, BEING 20 FEET EACH SIDE OF THE SECTION LINES
 - 6) 60.00 CHAINS SOUTH TO THE STONE HE FOUND AT THE 1/4 CORNER BETWEEN SECTIONS 33 & 34-19-10 IN LINE WITH THE FENCES AND 20 FEET WEST OF A STONE WALL
- 3) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR, IN SURVEY F27001 IN THE SURVEY FILE FOR TOWNSHIP 19-10 FOR A TRACT OF LAND IN THE NORTHWEST QUARTER OF THE SOUTHWEST QUARTER OF SECTION 27-19-10 DATED OCTOBER 30, 1974, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE** AT THE

SOUTHWEST CORNER OF THE NORTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 27-19-10.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,317.36' NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF THE SW1/4 OF SECTION 27-19-10
 - 2) 1,317.36' SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 27-19-10
 - 3) 605' EAST TO THE "MONUMENT" HE SET FOR THE SOUTHWEST TRACT CORNER – NOT IDENTIFIED
- 4) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 19-10 SHOWS A **STONE** AT THE "SW CORNER NW1/4 SW1/4 SECTION 27-19-10".
- 1) 34.4' NORTH TO THE CORNER OF A TELEPHONE RISER
 - 2) 26.6' SE TO A SPIKE IN A POWER POLE
 - 3) 49.5' EAST TO A SPIKE IN A POWER POLE

WEST SIXTEENTH CORNER SOUTHWEST QUARTER OF SECTION 27-19-10