

NORTH 1/4 CORNER SECTION 28, TOWNSHIP 19 SOUTH, RANGE 10 EAST

- 1) ON PAGE 209 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 13" X 12" X 6"** FOR THE 1/4 CORNER BETWEEN SECTIONS 21 & 28-19-10.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.11 CHAINS WEST TO THE 20" X 11" X 6" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 20, 21, 28 & 29-19-10
 - 2) 40.11 CHAINS EAST TO THE 18" X 13" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 21, 22, 27 & 28-19-10
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A PERMANENT SURVEY RECORDED IN SURVEY BOOK "C" ON PAGE 90 AND DATED JULY 1874, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 28-19-10 ON THIS **PERMANENT SURVEY**.
- 3) **REA PIN—MUST VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY JUST "HEELED-IN" FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR** REA BOOK 31 ON PAGE 19 SAYS THAT **THEY DROVE AN IRON PIN** FOR THE NORTH 1/4 CORNER OF SECTION 28-19-10 AT 2,660 FEET EAST OF THE NORTHWEST CORNER OF SECTION 28-19-10 ON JUNE 10, 1939.
 - 1) 26' NORTH TO A WITNESS PIN
- 4) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 19-10 SHOWS A **REA PIN** AT THE "SW CORNER SE1/4 SECTION 21-19-10" AND "NW CORNER NE1/4 SECTION 28-19-10".
 - 1) 26' WEST TO WITNESS [REA]
- 5) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 19-10 SHOWS AN **IRON PIN** AT THE "N1/4 CORNER SECTION 28-19-10". **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN MAY BE THE REA PIN – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
 - 1) 25.6' NNE TO A SPIKE IN A TELEPHONE POLE
 - 2) 20.9' SSW TO A 1/2" REBAR
 - 3) 2,649.5' PER 1/2 MILE
- 6) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 1, 2011 FOR PROJECT NUMBER 11309-02, A SURVEY FOR JAYSON DAVIS IN THE EAST 1/2 OF THE NORTHWEST 1/4 OF SECTION 28, SURVEY F28001 IN THE SURVEY FILE FOR TOWNSHIP 19-10, SAID THAT HE FOUND AN IRON PIN AT THE NORTH 1/4 CORNER OF SECTION 28-19-10 AT AICALMNESS'S DISTANCE WEST OF THE NORTHEAST CORNER [2,642.72'] AND AT THE NORTHWEST CORNER OF SECTION 28-19-10 RESET [2,642.72']. HE ALSO FOUND A 5/8" ROUND IRON PIN OF RECENT AND UNKNOWN ORIGIN THAT WAS **NOT** ACCEPTED. HE EXCAVATED WITH A COUNTY MAINTAINER AND FOUND OLD STONE WALL REMAINS BELOW THE IRON PIN. **HE SET A 5/8" X 30" IRON PIN WITH A LYON COUNTY CAP** FOR THE NORTH 1/4 CORNER OF SECTION 28-19-10.
 - 1) **14.85' ENE TO A 5/8" IRON PIN FOUND AND NOT ACCEPTED**
 - 2) 25.00' SOUTH TO A 1/2" X 24" IRON PIN WITH "LS 752" CAP SET FOR A WITNESS AT RIGHT ANGLES TO THE NORTH LINE OF THE NW1/4 OF SECTION 28-19-10 **[HORIZONTAL TIE]**
 - 3) 58.2' NNE TO A SPIKE & BOTTLECAP IN THE EAST FACE OF A 14" ELM TREE
 - 4) 4' NORTH TO THE CENTERLINE TRAVELED WAY OF ROAD 150 EAST-WEST

HIS TIES ARE CONTINUED ON PAGE 2

- 5) 2,642.72' EAST TO A 7/8" IRON PIN [NORTHEAST CORNER OF SECTION 28-19-10 – **HORIZONTAL TIE**]
- 6) 2,642.72' WEST TO A 5/8" IRON PIN WITH LYON COUNTY CAP [NORTHWEST CORNER SECTION 28-19-10 – **HORIZONTAL TIE**]

NORTH QUARTER CORNER SECTION 28-19-10