

WEST 1/16TH CORNER OF THE NORTHWEST QUARTER OF SECTION 28, TOWNSHIP 19 SOUTH, RANGE 10 EAST

- 1) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 145 & 146 ON THE PETITION OF MILTON LINDLEY AND OTHERS FOR A ROAD IN TOWNSHIP 19-10 THAT WAS SURVEYED ON JANUARY 22, 1870 AND ESTABLISHED AND RECORDED ON FEBRUARY 15, 1970 BY DAVID S. GILMORE, COUNTY CLERK, SAID THAT HE ENDED THIS ROAD SURVEY **AT THE STONE** ON THE 1/16TH CORNER BETWEEN THE NORTHEAST CORNER OF SECTION 28-19-10 AND THE NORTHEAST 1/4 OF SECTION 29-19-10 FOR THIS 50 FOOT WIDE ROAD. SEE THE COMMISSIONERS JOURNAL ON PAGE 311.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE 1/16TH SECTION LINE FO 47.37 CHAINS TO THE STONE HE SET FOR AN ANGLE TO THE NORTHWESTERLY DUE TO JACOB'S CREEK, THEN RETURNS TO THE 1/16TH SECTION LINE AT A POINT 42.12 CHAINS WEST OF THE CENTER OF THE NE1/4 OF SECTION 30-19-10, THEN CONTINUES WEST ON THE 1/16TH SECTION LINE TO THE STONE AT THE CENTER OF THE NE1/4 OF SECTION 30-19-10 AT A TURN TO THE NORTH
- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 80, A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 112 DATED JULY 28, 1903 FOR A COUNTY ROAD IN TOWNSHIP 19, RANGE 10, SAID THAT **HE FOUND THE STONE AT THE 1/2/4 CORNER** ON THE EAST SIDE OF THE NORTHEAST 1/4 OF SECTION 29-19-10. HE USED THIS STONE, THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 29-19-10 AND THE STONE THAT HE FOUND AT THE 1/4 CORNER BETWEEN SECTIONS 28 & 29-19-10 TO SET THE 27" X 6" X 4" STONE MARKED "R" ON THE WEST FACE FOR THE NORTHEAST CORNER OF SECTION 32-19-10. HIS FIELD NOTES ARE IN HIS BOOK 3 ON PAGE 188.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 19.98 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 29-19-10
- 2) 19.96 CHAINS SOUTH TO THE STONE HE FOUND AT THE 1/4 CORNER BETWEEN SECTIONS 28 & 29-19-10
- 3) 59.91 CHAINS SOUTH TO THE 27" X 6" X 4" ROAD STONE MARKED "R" ON THE WEST SIDE HE SET FOR THE NORTHEAST CORNER OF SECTION 32-19-10 FOR THIS ROAD SURVEY BEGINNING AT THE SOUTHWEST CORNER OF SECTION 30-19-10 ON THE RANGE LINE AND THE LYON AND CHASE COUNTY LINE AND RUNNING EAST ON THE SECTION LINES FOR 4 MILES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 34-19-10 TO END THIS ROAD SURVEY FOR A 40 FOOT WIDE ROAD, BEING 20 FEET EACH SIDE OF THE SECTION LINE
- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY FOR ROAD NUMBER 584 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 205 THROUGH 208 PETITION BY WILLIAM EVANS AND OTHERS FOR REMARKING A ROAD IN TOWNSHIP 19-10 [PACKET 726 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JULY 28, 1903, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/2/4 CORNER OF THE NORTHWEST 1/4 OF SECTION 28-19-10. HE USED THIS STONE, THE STONE THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 28-19-10 AND THE STONE THAT HE FOUND AT THE WEST 1/4 CORNER OF SECTION 28-19-10 TO RESET THE NORTHEAST CORNER OF SECTION 32-19-10.

HIS NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 19.98 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 29-19-10

HIS INFORMATION IS CONTINUED ON PAGE 2

- 2) 19.96 CHAINS SOUTH TO THE STONE HE FOUND AT THE 1/4 CORNER BETWEEN SECTIONS 28 & 29-19-10
- 3) 59.91 CHAINS SOUTH TO THE 27" X 6" X 4" ROAD STONE MARKED "R" ON THE WEST SIDE HE SET FOR THE NORTHEAST CORNER OF SECTION 32-19-10 FOR THIS ROAD SURVEY BEGINNING AT THE SOUTHWEST CORNER OF SECTION 30-19-10 ON THE RANGE LINE AND THE LYON AND CHASE COUNTY LINE AND RUNNING EAST ON THE SECTION LINES FOR 4 MILES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 34-19-10 TO END THIS ROAD SURVEY FOR A 40 FOOT WIDE ROAD, BEING 20 FEET EACH SIDE OF THE SECTION LINE
- 4) **REA PIN—MUST VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING; THIS CORNER WAS PROBABLY JUST "HEELED-IN" FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
 REA BOOK 31 ON PAGE 18 SHOWS THAT **THEY DROVE AN IRON PIN** FOR THIS CORNER AT 1,318.3 FEET SOUTH OF THE NORTHWEST CORNER OF SECTION 28-19-10.
 - 1) 26' EAST TO A WITNESS PIN IN A LINE OF FENCE
- 5) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 19-10 SHOWS A **REA PIN** AT THE "SE CORNER NE1/4 NE1/4 SECTION 29-19-10". **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING; THIS CORNER WAS PROBABLY JUST "HEELED-IN" FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
 - 1) 35.5' BASE OF N. W. C P
 - 2) 38.3' SW TO A POWER POLE
 - 3) 22.1' BASE OF EAST POWER POLE [NORTH POLE]

WEST SIXTEENTH CORNER NORTHWEST QUARTER OF SECTION 28-19-10