

NORTH 1/4 CORNER SECTION 29, TOWNSHIP 19 SOUTH, RANGE 10 EAST

- 1) ON PAGE 217 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 14" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 20 & 29-19-10.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.26-1/2 CHAINS WEST TO THE 24" X 21" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19, 20, 29 & 30-19-10
 - 2) 40.26-1/2 CHAINS EAST TO THE 24" X 21" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 20, 21, 28 & 29-19-10

- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 95 RECORDED IN SURVEY BOOK "A" ON PAGE 190 DATED MARCH 9 & 10, 1869 FOR A SURVEY OF LAND SITUATED IN SECTION 20-19-10, TO ESTABLISH THE NORTHWEST CORNER OF THE SOUTHWEST 1/4 OF THE NORTHWEST 1/4, AND THE NORTHEAST CORNER OF THE SOUTHWEST 1/4 OF THE NORTHEAST 1/4, AND THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF THE SOUTHEAST 1/4 OF SAID SECTION 20, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 20-19-10 ON THIS SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 160 RODS WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 20-19-10
 - 2) 80 RODS, 9 LINKS EAST TO THE STONE HE SET FOR THE SOUTHEAST CORNER OF THE SW1/4 OF THE SE1/4 OF SECTION 20-19-10
 - 3) 160 RODS, 18 LINKS EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 10-19-10

- 3) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 98 RECORDED IN SURVEY BOOK "A" ON PAGE 192 DATED MARCH 12, 1869 TO SURVEY SOME LAND IN SECTION 29-19-10, TO ESTABLISH THE CENTER CORNER AND THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF THE NORTHEAST 1/4 OF SECTION 29, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 29-19-10 ON THIS SURVEY.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 318 RODS, 14 LINKS SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 29-19-10

NORTH QUARTER CORNER SECTION 29-19-10