

NORTHWEST CORNER SECTION 29, TOWNSHIP 19 SOUTH, RANGE 10 EAST

- 1) ON PAGE 216 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 21" X 2"** FOR THE CORNER TO SECTIONS 19, 20, 29 & 30-19-10.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.26-1/2 CHAINS EAST TO THE 20" X 14" X 2" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 20 & 29-19-10
 - 2) 80.53 CHAINS EAST TO THE 20" X 11" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 20, 21, 28 & 29-19-10

- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 95 RECORDED IN SURVEY BOOK "A" ON PAGE 190 DATED MARCH 9 & 10, 1869 FOR A SURVEY OF LAND SITUATED IN SECTION 20-19-10, TO ESTABLISH THE NORTHWEST CORNER OF THE SOUTHWEST 1/4 OF THE NORTHWEST 1/4, AND THE NORTHEAST CORNER OF THE SOUTHWEST 1/4 OF THE NORTHEAST 1/4, AND THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF THE SOUTHEAST 1/4 OF SAID SECTION 20-19-10, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 20-19-10 ON THIS SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 160 RODS EAST TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 20-19-10
 - 2) 240 RODS, 9 LINKS EAST TO THE STONE HE SET FOR THE SOUTHEAST CORNER OF THE SW1/4 OF THE SE1/4 OF SECTION 20-19-10
 - 3) 320 RODS, 18 LINKS EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 20-19-10

- 3) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 96 RECORDED IN SURVEY BOOK "A" ON PAGE 191 DATED MARCH 11, 1869 FOR A SURVEY OF LAND SITUATED IN SECTION 19-19-10, TO ESTABLISH THE CENTER CORNER OF THE SECTION, AND THE CENTER CORNER OF THE NORTHEAST 1/4, AND THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF THE NORTHEAST 1/4, AND THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 19-19-10, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 19-19-10 ON THIS SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 80 RODS, 14 LINKS WEST TO THE STONE HE SET FOR THE SOUTHWEST CORNER OF THE SE1/4 OF THE SE1/4 OF SECTION 19-19-10
 - 2) 160 RODS, 28 LINKS WEST TO THE STONE HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 19-19-10

- 4) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 97 RECORDED IN SURVEY BOOK "A" ON PAGE 192 DATED MARCH 12, 1869 FOR A SURVEY OF LAND SITUATED IN SECTION 30-19-10, TO SURVEY THE NORTHEAST 1/4 OF THE NORTHEAST 1/4 OF SECTION 30, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 30-19-10 ON THIS SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 159 RODS, 20 LINKS SOUTH TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 30-19-10

- 5) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, BY MATTHEW BROWN, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 163, A SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 130 DATED NOVEMBER 23-25, 1887 TO ESTABLISH THE EAST LINE AND THE CORNERS OF THE WEST 1/2 OF THE NORTHWEST 1/4 AND THE SOUTHWEST 1/4 OF SECTION 30-19-10, SAID THAT HE DID **NOT** FIND THE STONE AT

THE NORTHEAST CORNER OF SECTION 30-19-10. **HE SET A TEMPORARY STAKE** FOR THE NORTHEAST CORNER OF SECTION 30-19-10 ON THIS SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 5,280' EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 29-19-10
- 2) 3,973' WEST TO THE 24" X 8" X 2-1/2" LIMESTONE MARKED "1/8" ON THE NORTH FACE HE SET FOR THE NORTHEAST CORNER OF THE NW1/4 OF THE NW1/4 OF SECTION 30-19-10
- 3) 5,284' WEST TO A "STONE SET BY SOMEONE" HE FOUND AT THE NORTHWEST CORNER OF SECTION 30-19-10 ON THE RANGE LINE AND THE LYON AND CHASE COUNTY LINE, THAT HE FOUND TO BE 9" TOO FAR NORTH AND 18" TOO FAR WEST OF THE LINE FROM THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 19-19-10 TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 30-19-10

- 6) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, IN SURVEY NUMBER 182, A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 REQUESTED BY SOL WILLIAMS TO MAKE A SURVEY OF THE LINE BETWEEN SECTIONS 29 & 30-19-10 AND ESTABLISH THE SAME, SAID THAT **HE SET A SMALL HEDGE POST IN THE GROUND** FOR THE PERMANENT NORTHEAST CORNER OF SECTION 30-19-10 ON THIS **PERMANENT SURVEY**. THE SURVEY WAS COMPLETED ON MARCH 21, 1907 AND ENTERED IN THE PERMANENT SURVEY BOOK ON APRIL 30, 1907.

HIS SURVEY NOTES /DRAWING SHOW THE FOLLOWING INFORMATION:

- 1) 1,320' SOUTH TO THE STAKE HE SET FOR THE PERMANENT EAST 1/8TH CORNER OF THE NE1/4 OF SECTION 30-19-10, AT 30 FEET EAST OF HEDGES
- 2) 2,640' SOUTH TO THE 4" X 9" X 30" STONE HE SET FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 30-19-10, FROM WHICH AN ELM TREE IS S. 30° W. AT 18-9/10 FEET, AND AN ASH TREE IS S. 44°30' E. AT 17 FEET
- 3) 5,280' SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 30-19-10

- 7) LESLIE M. GOULD, L.S 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN A REPORT OF A **PERMANENT SURVEY** IN SECTION 19-19-10 MADE PRIMARILY TO LOCATE THE BOUNDARIES OF THE EAST 1/2 OF THE WEST 1/2 OF SECTION 19-19-10 THAT WAS BEGUN ON APRIL 16, 1969 AND WAS COMPLETED ON APRIL 24, 1969 AND RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 53 AND RECORDED IN VOLUME 2 OF PLATS ON PAGE 58 IN THE REGISTER OF DEEDS OFFICE ON AUGUST 27, 1969, SHOWS ON HIS SURVEY DRAWING THAT HE SET A **TEMPORARY POINT** FOR THE SOUTHEAST CORNER OF SECTION 19-19-10 ON THIS **PERMANENT SURVEY**. HE ALSO NOTED THAT ACCORDING TO GOVERNMENT SURVEY NOTES THE EAST LINE OF SECTIONS 19-19-10 AND 30-19-10 IS ON A TANGENT OR STRAIGHT LINE FOR 5 MILES. THEREFORE THE EAST LINE OF SECTION 30-19-10 WAS PRODUCED NORTH TO ARRIVE AT THE RESULTS AS SHOWN ON THIS PERMANENT SURVEY.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,322.62' SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE N1/2 OF THE NE1/4 OF SECTION 30-19-10
- 2) 2,645.5' NORTH TO THE TEMPORARY POINT HE SET FOR THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 19-19-10
- 3) 5,290.50' NORTH TO THE TEMPORARY POINT HE SET FOR THE NORTHEAST CORNER OF SECTION 19-19-10 – THE LOCATION FALLS IN A CROP
- 4) 1,320' WEST TO THE IRON PIN HE SET FOR THE PERMANENT SOUTH 1/16TH CORNER OF THE SE1/4 OF SECTION 19-19-10

HIS INFORMATION IS CONTINUED ON PAGE 3

- 5) 2,640' WEST TO THE IRON PIN HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 19-19-10
- 6) 3,960' WEST TO AN IRON PIN HE SET FOR THE PERMANENT SOUTH 1/16TH CORNER OF THE SW1/4 OF SECTION 19-19-1
- 7) 5,275.8' WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 19-19-10 ON THE RANGE LINE AND THE LYON AND CHASE COUNTY LINE

NORTHWEST CORNER SECTION 29-19-10