

**WEST 1/16<sup>TH</sup> CORNER OF THE NORTHEAST QUARTER OF SECTION 29, TOWNSHIP 19 SOUTH, RANGE 10 EAST**

- 1) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 98 RECORDED IN SURVEY BOOK "A" ON PAGE 192 DATED MARCH 12, 1869 TO SURVEY SOME LAND IN SECTION 29-19-10, TO ESTABLISH THE CENTER CORNER AND THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF THE NORTHEAST 1/4 OF SECTION 29, SAID THAT **HE SET A STONE** FOR THE 1/2/4 CORNER ON THE WEST SIDE OF THE NORTHEAST 1/4 OF SECTION 29 EQUIDISTANT BETWEEN THE STONE HE FOUND AT THE NORTH 1/4 CORNER AND THE STONE HE SET FOR THE CENTER CORNER OF SECTION 29 ON THIS SURVEY.
- 2) **REA PIN—MUST VERIFY AND CHECK FOR OTHER MONUMENTS BEFORE USING; THIS CORNER WAS PROBABLY JUST "HEELED-IN" FOR UTILITY USE ONLY!!** REA BOOK 31 ON PAGE 18 SHOWS THAT THEY **DROVE AN IRON PIN** FOR THIS CORNER.
  - 1) 21' SOUTH TO A WITNESS PIN
- 3) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 19-10 SHOWS A **REA PIN** AT THE "SW CORNER NW1/4 NE1/4 SECTION 29-19-10". **VERIFY BEFORE USING!!**  
**WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
  - 1) 21' SOUTH TO A WITNESS [REA]

WEST SIXTEENTH CORNER NORTHEAST QUARTER OF SECTION 29-19-10