

WEST 1/16TH CORNER OF THE NORTHWEST QUARTER OF SECTION 29, TOWNSHIP 19 SOUTH, RANGE 10 EAST

- 1) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 97 RECORDED IN SURVEY BOOK "A" ON PAGE 192 DATED MARCH 12, 1869 FOR A SURVEY OF LAND SITUATED IN SECTION 30-19-10, SAID THAT **HE FOUND THE STONE SET BY A PREVIOUS SURVEYOR TO BE CORRECT** FOR THE 1/2/4 CORNER ON THE EAST SIDE OF THE NORTHEAST 1/4 OF SECTION 30-19-10 ON THIS SURVEY. HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 159 RODS, 1 LINK WEST TO THE STONE HE FOUND AT THE 1/2/4 CORNER ON THE WEST SIDE OF THE NE1/4 OF SECTION 30-19-10

- 2) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, IN SURVEY NUMBER 182, A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 REQUESTED BY SOL WILLIAMS TO MAKE A SURVEY OF THE LINE BETWEEN SECTIONS 29 & 30-19-10 AND ESTABLISH THE SAME, SAID THAT **HE SET A STAKE** AT 60 CHAINS NORTH OF THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 30-19-10 ON THIS **PERMANENT SURVEY**. THE SURVEY WAS COMPLETED ON MARCH 21, 1907 AND ENTERED IN THE PERMANENT SURVEY BOOK ON APRIL 30, 1907. HIS NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,320' NORTH TO A SMALL HEDGE POST HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 30-19-10
 - 2) 1,320' SOUTH TO THE 4" X 9" X 30" LIMESTONE HE SET FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 30-19-10, FROM WHICH AN ELM TREE IS S. 30° W. AT 18-9/10 FEET, AND AN ASH TREE IS S. 44°30' E. AT 17 FEET
 - 3) 3,960' SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 30-19-10

- 3) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A SURVEY RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 56 FROM THE NOTICE FROM J. F. COOK REQUIRING HIM TO ESTABLISH THE CORNER STONE AT THE SOUTHWEST CORNER OF THE NORTHWEST 1/4 OF SECTION 29-19-10, WHICH HAD BEEN DISPLACED, AND TO SURVEY THE LINE BETWEEN THE SOUTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 29-19-10, AND THE SOUTHEAST 1/4 OF THE NORTHEAST 1/4 OF SECTION 30-19-10, SAID THAT **HE SET AN 8" X 12" X 18" LIMESTONE** TO PERMANENTLY MARK THE NORTHWEST CORNER OF THE SOUTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 29-19-10 ON THIS **PERMANENT SURVEY**. THE SURVEY WAS MADE ON MARCH 17, 1910 AND WAS ENTERED ON MARCH 24, 1910. HIS NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 1,320' SOUTH TO THE STONE HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 29-19-10
 - 2) 3,960' SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 29-19-10

- 4) REA BOOK 31 ON PAGE 18 SHOWS THAT **THEY DROVE AN IRON PIN** FOR THIS CORNER. **VERIFY BEFORE USING AS IT WAS PROBABLY "HEELED-IN" FOR UTILITY USE ONLY!!** WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR
 - 1) 20' SOUTH TO A WITNESS PIN

- 5) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 19-10 SHOWS A **REA PIN** AT THE "SW CORNER NW1/4 NW1/4 SECTION 29-19-10".
 - 1) 20' SOUTH TO A WITNESS [REA]

CONTINUED ON PAGE 2

- 6) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 19-10 SHOWS AN **IRON PIN** AT THE “SE CORNER NE1/4 NE1/4 SECTION 30-19-10”. **VERIFY BEFORE USING AS THIS MAY BE A REA PIN!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
- 1) 23.01’ SOUTH TO A SPIKE IN A FENCE POST IN LINE
- 7) LESLIE M. GOULD, L.S 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN A REPORT OF A **PERMANENT SURVEY** IN SECTION 19-19-10 MADE PRIMARILY TO LOCATE THE BOUNDARIES OF THE EAST 1/2 OF THE WEST 1/2 OF SECTION 19-19-10 THAT WAS BEGUN ON APRIL 16, 1969 AND WAS COMPLETED ON APRIL 24, 1969 AND RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 53 AND RECORDED IN VOLUME 2 OF PLATS ON PAGE 58 IN THE REGISTER OF DEEDS OFFICE ON AUGUST 27, 1969, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE IN PLACE** AT THE SOUTHEAST CORNER OF THE NORTH 1/2 OF THE NORTHEAST 1/4 OF SECTION 30-19-10 ON THIS **PERMANENT SURVEY**. HE ALSO NOTED THAT ACCORDING TO GOVERNMENT SURVEY NOTES THE EAST LINE OF SECTIONS 19-19-10 AND 30-19-10 IS ON A TANGENT OR STRAIGHT LINE FOR 5 MILES. THEREFORE THE EAST LINE OF SECTION 30-19-10 WAS PRODUCED NORTH TO ARRIVE AT THE RESULTS AS SHOWN ON THIS PERMANENT SURVEY.
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,322.65’ NORTH TO THE TEMPORARY POINT HE SET FOR THE SOUTHEAST CORNER OF SECTION 19-19-10
 - 2) 3,972.12’ NORTH TO THE TEMPORARY POINT HE SET FOR THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 19-19-10
 - 3) 6,617.37’ NORTH TO THE THEORETICAL LOCATION FOR THE NORTHEAST CORNER OF SECTION 19-19-10 – NO CORNER SET DUE TO CROP

WEST SIXTEENTH CORNER NORTHWEST QUARTER OF SECTION 29-19-10