

CENTER CORNER NORTHWEST 1/4 SECTION 30, TOWNSHIP 19 SOUTH, RANGE 10 EAST

- 1) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, BY MATTHEW BROWN, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 163, A SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 130 DATED NOVEMBER 23-25, 1887 TO ESTABLISH THE EAST LINE AND THE CORNERS OF THE WEST 1/2 OF THE NORTHWEST 1/4 AND THE SOUTHWEST 1/4 OF SECTION 30-19-10, SAID THAT **HE SET AN 18" X 10" X 6" LIMESTONE MARKED "1/8" ON THE WEST SIDE** FOR THE NORTHEAST CORNER OF THE SOUTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 30-19-10 ON LINE AND AT THE PROPORTIONATE DISTANCE BETWEEN THE STONE THAT HE SET FOR THE NORTHEAST CORNER OF THE NORTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 30-19-10 AND THE STONE THAT HE SET FOR THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 30-19-10.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,321-3/4' NORTH TO THE 24" X 8" X 2-1/2" LIMESTONE MARKED "1/8" ON THE NORTH FACE HE SET FOR THE NORTHEAST CORNER OF THE NW1/4 OF THE NW1/4 OF SECTION 30-19-10
 - 2) 1,321-3/4' SOUTH TO THE 14" X 12" X 4" LIMESTONE MARKED "1/8" HE SET FOR THE NORTHEAST CORNER OF THE NW1/4 OF THE SW1/4 OF SECTION 30-19-10
 - 3) 2,643-1/2' SOUTH TO THE 18" X 8" X 7" LIMESTONE MARKED "1/8" ON THE WEST FACE HE SET FOR THE NORTHEAST CORNER OF THE SW1/4 OF THE SW1/4 OF SECTION 30-19-10
 - 4) 3,965-1/4' SOUTH TO THE 18" X 11" X 2-1/2" LIMESTONE MARKED "1/8" WITH A BROKEN PINT BOTTLE IN THE HOLE WHEN THE STONE WAS SET FOR THE SOUTHEAST CORNER OF THE SW1/4 OF THE SW1/4 OF SECTION 30-19-10

- 2) LESLIE M. GOULD, L.S 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN A REPORT OF A **PERMANENT SURVEY** IN SECTION 19-19-10 MADE PRIMARILY TO LOCATE THE BOUNDARIES OF THE EAST 1/2 OF THE WEST 1/2 OF SECTION 19-19-10 THAT WAS BEGUN ON APRIL 16, 1969 AND WAS COMPLETED ON APRIL 24, 1969 AND RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 53 AND RECORDED IN VOLUME 2 OF PLATS ON PAGE 58 IN THE REGISTER OF DEEDS OFFICE ON AUGUST 27, 1969, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE IN PLACE** AT THE SOUTHEAST CORNER OF THE NORTHEAST 1/4 OF THE NORTHWEST 1/4 OF SECTION 30-19-10 ON THIS **PERMANENT SURVEY**.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,322.62' NORTH TO THE IRON PIN HE SET FOR PERMANENT SOUTH 1/16TH CORNER OF THE SW1/4 OF SECTION 19-19-10

- 3) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 19-10 SHOW A **STONE AND PIN** AT THE "SE CORNER NW1/4 OF THE NW1/4 OF SECTION 30-19-10".
 - 1) 22.5' NORTH TO THE BASE OF A CORNER POST
 - 2) 34.2' NE TO THE BASE OF THE E. B. P.

CENTER CORNER NORTHWEST QUARTER SECTION 30-19-10