

**NORTH 1/4 CORNER SECTION 30, TOWNSHIP 19 SOUTH, RANGE 10 EAST**

- 1) ON PAGE 217 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 15" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 19 & 30-19-10.  
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 39.46 CHAINS WEST TO THE 27" X 11" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19 & 30-19-10 ON THE WEST TOWNSHIP BOUNDARY AND THE COUNTY LINE
  - 2) 40.00 CHAINS EAST TO THE 24" X 21" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19, 20, 29 & 30-19-10
  
- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 96 RECORDED IN SURVEY BOOK "A" ON PAGE 191 DATED MARCH 11, 1869 FOR A SURVEY OF LAND SITUATED IN SECTION 19-19-10, TO ESTABLISH THE CENTER CORNER OF THE SECTION, AND THE CENTER CORNER OF THE NORTHEAST 1/4, AND THE SOUTHWEST CORNER OF THE SOUTHWEST 1/4 OF THE NORTHEAST 1/4, AND THE SOUTHWEST CORNER OF THE SOUTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SAID SECTION 19-19-10, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 19-19-10 ON THIS SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 80 RODS, 14 LINKS EAST TO THE STONE HE SET FOR THE SOUTHWEST CORNER OF THE SE1/4 OF THE SE1/4 OF SECTION 19-19-10
  - 2) 160 RODS, 28 LINKS EAST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 19-19-10
  
- 3) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, BY MATTHEW BROWN, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 1623, A SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 130 DATED NOVEMBER 23-25, 1887 TO ESTABLISH THE EAST LINE AND THE CORNERS OF THE WEST 1/2 OF THE NORTHWEST 1/4 AND THE SOUTHWEST 1/4 OF SECTION 30, DOES **NOT** MENTION FINDING THE NORTH 1/4 CORNER OF SECTION 30-19-10 WHEN HE RAN THE SECTION LINES FROM THE STONE THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 30-19-10 ON THE RANGE LINE AND THE LYON AND CHASE COUNTY LINE EAST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 28-19-10 ON THIS SURVEY.
  
- 4) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A SURVEY RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 56 AND DATED MARCH 1910, SAID THAT **HE FOUND A STONE BROKEN IN TWO AND NOT IN ITS PROPER LOCATION** AT THE NORTH 1/4 CORNER OF SECTION 30-19-10. **HE RESET THE STONE** TO ITS ORIGINAL POSITION ON THIS **PERMANENT SURVEY** ACCORDING TO WITNESS TIES BY PARKMAN ON MARCH 27, 1907, ON PAGE 2 OF BOOK 1 IN THE SURVEY RECORDS.
  
- 5) LESLIE M. GOULD, L.S 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN A REPORT OF A **PERMANENT SURVEY** IN SECTION 19-19-10 MADE PRIMARILY TO LOCATE THE BOUNDARIES OF THE EAST 1/2 OF THE WEST 1/2 OF SECTION 19-19-10 THAT WAS BEGUN ON APRIL 16, 1969 AND WAS COMPLETED ON APRIL 24, 1969 AND RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 53 AND RECORDED IN VOLUME 2 OF PLATS ON PAGE 58 IN THE REGISTER OF DEEDS OFFICE ON AUGUST 27, 1969, SHOWS ON HIS SURVEY DRAWING THAT **HE SET AN IRON PIN** FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 19-19-10 ON THIS **PERMANENT SURVEY**. THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE BOOKS.  
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

HIS INFORMATION IS CONTINUED ON PAGE 2

- 1) 1,320' WEST TO THE IRON PIN HE SET FOR THE PERMANENT SOUTH 1/16<sup>TH</sup> CORNER OF THE SW1/4 OF SECTION 19-19-10
- 2) 2,635.8' WEST TO THE STONE HE FOUND IN PLACE AT THE SOUTHWEST CORNER OF SECTION 19-19-10 ON THE RANGE LINE AND THE LYON AND CHASE COUNTY LINE
- 3) 1,320' EAST TO THE IRON PIN HE SET FOR THE PERMANENT SOUTH 1/16<sup>TH</sup> CORNER OF THE SE1/4 OF SECTION 19-19-10
- 4) 2,640.0' EAST TO THE TEMPORARY POINT HE SET FOR THE SOUTHEAST CORNER OF SECTION 19-19-10

NORTH QUARTER CORNER SECTION 30-19-10