

NORTH 1/16TH CORNER OF THE NORTHWEST QUARTER OF SECTION 31, TOWNSHIP 19 SOUTH, RANGE 10 EAST

- 1) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, BY MATTHEW BROWN, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 163, A SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 130 DATED NOVEMBER 23-25, 1887 TO ESTABLISH THE EAST LINE AND THE CORNERS OF THE WEST 1/2 OF THE NORTHWEST 1/4 AND THE SOUTHWEST 1/4 OF SECTION 30-19-10, SAID THAT **HE SET AN 18" X 11" X 2-1/2" LIMESTONE MARKED "1/8" ON THE NORTH SIDE** FOR THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 30-19-10. HE SAID THAT "A PINT BOTTLE WAS BROKEN IN THE HOLE WHEN THE STONE WAS SET".

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 1,321-3/4' NORTH TO THE 18" X 8" X 7" LIMESTONE MARKED "1/8" ON THE WEST FACE HE SET FOR THE NORTHEAST CORNER OF THE SW1/4 OF THE SW1/4 OF SECTION 30-19-10
- 2) 2,643-1/2' NORTH TO THE 14" X 12" X 4" LIMESTONE MARKED "1/8" ON THE WEST FACE HE SET FOR THE NORTHEAST CORNER OF THE NW1/4 OF THE SW1/4 OF SECTION 30-19-10
- 3) 3,965-1/4' NORTH TO THE 18" X 10" X 6" LIMESTONE MARKED "1/8" ON THE WEST FACE HE SET FOR THE NORTHEAST CORNER OF THE SW1/4 OF THE NW1/4 OF SECTION 30-19-10
- 4) 5,287' NORTH TO THE 24" X 8" X 2-1/2" LIMESTONE HE SET FOR THE NORTHEAST CORNER OF THE NW1/4 OF THE NW1/4 OF SECTION 30-19-10

- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 80, A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 112 DATED JULY 28, 1903 FOR A COUNTY ROAD IN TOWNSHIP 19, RANGE 10, SAID THAT **HE FOUND THE STONE THAT WAS SET BY MATTHEW BROWN AT 22 FEET NORTH OF A HEDGE** AT THE NORTH 1/2/4 CORNER OF THE NORTHWEST CORNER OF SECTION 31-19-10 ON THIS ROAD SURVEY. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 188 IN THE "KRETSINGER COLLECTION". NO WIDTH WAS RECORDED ON THIS ROAD SURVEY.

HIS NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 20.16 CHAINS TO THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 30-19-10 ON THE RANGE LINE AND THE LYON AND CHASE COUNTY LINE TO BEGIN THIS ROAD SURVEY
- 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 20.00 CHAINS TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 31-19-10, THEN CONTINUES EAST ON THE SECTION LINES FOR 40.05 CHAINS TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 31-19-10, THEN CONTINUES EAST ON THE SECTION LINES FOR 40.07 CHAINS TO THE STONE SET BY BROWN FOR THE NORTH 1/4 CORNER OF SECTION 32-19-10, THEN CONTINUES EAST ON THE SECTION LINES FOR 40.07 CHAINS TO THE 27" X 6" X 4" STONE MARKED "R" ON THE WEST FACE HE SET FOR THE NORTHEAST CORNER OF SECTION 32-19-10; THEN CONTINUES EAST ON THE SECTION LINES FOR 40.01 CHAINS TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 33-19-10 THAT SETS THE WRONG WAY IN THE GROUND; THEN CONTINUES EAST ON THE SECTION LINES FOR 20.05 CHAINS TO THE STONE HE FOUND AT THE 1/2/4 CORNER, THEN CONTINUES EAST ON THE SECTION LINES FOR 20.02 CHAINS TO THE 16" X 12" X 4" STONE MARKED "R" ON THE WEST FACE HE SET FOR THE NORTHEAST CORNER OF SECTION 33-19-10, THEN CONTINUES EAST ON THE SECTION LINES FOR 79.96 CHAINS TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 34-19-10 TO END THIS ROAD SURVEY

CONTINUED ON PAGE 2

- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 78, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 158 DATED JULY 14 & 15, 1903 AT THE REQUEST OF J. ROSECRANTS FOR A SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE EAST 1/2 AND THE EAST 1/2 OF THE SOUTHWEST 1/4 OF SECTION 31-19-10 AND RUN SUCH LINES AS ARE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE 1/2/4 STONE WITH PIECES OF BROKEN GLASS BY THE SIDE OF THE STONE THAT WAS SET BY MATTHEW BROWN AT 8 LINKS WEST OF A FENCE TO THE NORTH AND 33 LINKS NORTH OF A HEDGE** AT THE NORTH 1/2/4 CORNER OF THE NORTHWEST 1/4 OF SECTION 31-19-10 ON THIS **PERMANENT SURVEY**. HE NOTED THAT A STRAIGHT LINE FROM THE STONE THAT HE FOUND AT THIS CORNER TO THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 30-19-10 FELL 5 LINKS NORTH OF THE STONE THAT HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 31-19-10. HIS FIELD NOTES ARE IN HIS BOOK 3 ON PAGE 186 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 69" IN MISCELLANEOUS DRAWER NUMBER 3 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 20.00 CHAINS EAST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 31-19-10, LOCATED 59 LINKS SOUTH OF A HEDGE
- 2) 60.05 CHAINS EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 31-19-10, LOCATED ON LINE WITH A FENCE TO THE NORTH

- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY FOR ROAD NUMBER 584 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 205 THROUGH 208 PETITION BY WILLIAM EVANS AND OTHERS FOR REMARKING A ROAD IN TOWNSHIP 19-10 [PACKET 726 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JULY 28, 1903, SAID THAT **HE FOUND THE STONE THAT WAS SET BY BROWN AT 22 FEET NORTH OF A HEDGE** AT THE NORTH 1/2/4 CORNER OF THE NORTHWEST 1/4 OF SECTION 31-19-10 ON THIS ROAD SURVEY FOR A 40 FOOT WIDE ROAD, BEING 20 FEET EACH SIDE OF THE SECTION LINE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 20.16 CHAINS TO THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 30-19-10 ON THE RANGE LINE AND THE LYON AND CHASE COUNTY LINE TO BEGIN THIS ROAD SURVEY
- 3) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 20.00 CHAINS TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 31-19-10, THEN CONTINUES EAST ON THE SECTION LINES FOR 40.05 CHAINS TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 31-19-10, THEN CONTINUES EAST ON THE SECTION LINES FOR 40.07 CHAINS TO THE STONE SET BY BROWN FOR THE NORTH 1/4 CORNER OF SECTION 32-19-10, THEN CONTINUES EAST ON THE SECTION LINES FOR 40.07 CHAINS TO THE 27" X 6" X 4" STONE MARKED "R" ON THE WEST FACE HE SET FOR THE NORTHEAST CORNER OF SECTION 32-19-10; THEN CONTINUES EAST ON THE SECTION LINES FOR 40.01 CHAINS TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 33-19-10 THAT SETS THE WRONG WAY IN THE GROUND; THEN CONTINUES EAST ON THE SECTION LINES FOR 20.05 CHAINS TO THE STONE HE FOUND AT THE 1/2/4 CORNER, THEN CONTINUES EAST ON THE SECTION LINES FOR 20.02 CHAINS TO THE 16" X 12" X 4" STONE MARKED "R" ON THE WEST FACE HE SET FOR THE NORTHEAST CORNER OF SECTION 33-19-10, THEN CONTINUES EAST ON THE SECTION LINES FOR 79.96 CHAINS TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 34-19-10 TO END THIS ROAD SURVEY

NORTH SIXTEENTH CORNER NORTHWEST QUARTER OF SECTION 31-19-10