

**NORTHWEST CORNER SECTION 32, TOWNSHIP 19 SOUTH, RANGE 10 EAST**

- 1) ON PAGE 214 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 19" X 14" X 2-1/2"** FOR THE CORNER TO SECTIONS 29, 30, 31 & 32-19-10 ON APRIL 16, 1857. THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 40.00 CHAINS SOUTH TO THE 26" X 14" X 2" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 31 & 32-19-10
  - 2) 80.00 CHAINS SOUTH TO THE 32" X 16" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 31 & 32-19-10 ON THE SOUTH TOWNSHIP BOUNDARY
  - 3) 40.05 CHAINS EAST TO THE 21" X 18" X 2" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 29 & 32-19-10
  - 4) 80.10 CHAINS EAST TO THE 21" X 14" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 28, 29, 32 & 33-19-10
  - 5) 40.00 CHAINS WEST TO THE 24" X 14" X 2-1/2" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 30 & 31-19-10
  - 6) 80.18 CHAINS WEST TO THE 30" X 15" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 30 & 31-19-10 ON THE WEST TOWNSHIP BOUNDARY AND THE COUNTY LINE
  
- 2) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, BY MATTHEW BROWN, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 163, A SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 130 DATED NOVEMBER 23-25, 1887 TO ESTABLISH THE EAST LINE AND THE CORNERS OF THE WEST 1/2 OF THE NORTHWEST 1/4 AND THE SOUTHWEST 1/4 OF SECTION 30-19-10, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 30-19-10 ON THIS SURVEY.
  
- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 78, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 158 DATED JULY 14 & 15, 1903 AT THE REQUEST OF J. ROSECRANTS FOR A SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE EAST 1/2 AND THE EAST 1/2 OF THE SOUTHWEST 1/4 OF SECTION 31-19-10 AND RUN SUCH LINES AS ARE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE ON LINE WITH A FENCE TO THE NORTH AND 57 LINKS SOUTH OF A HEDGE** AT THE NORTHEAST CORNER OF SECTION 31-19-10 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK 3 ON PAGE 186 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 69" IN MISCELLANEOUS DRAWER NUMBER 3 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE. HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 40.05 CHAINS WEST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 31-19-10 LOCATED 59 LINKS SOUTH OF A HEDGE
  - 2) 60.05 CHAINS WEST TO THE STONE HE FOUND WITH PIECES OF BROKEN GLASS BY THE SIDE OF THE STONE AT THE NORTH 1/2/4 CORNER OF THE NW1/4 OF SECTION 31-19-10, THAT WAS SET BY BROWN
  - 3) 39.93 CHAINS SOUTH TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 31-19-10, THAT STANDS UNDER A FENCE EXTENDED EAST AND 5 OR 6 FEET EAST OF A NORTH & SOUTH FENCE
  - 4) 79.96 CHAINS SOUTH TO THE STONE HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 31-19-10 ON THE TOWNSHIP LINE, AND WITNESSED BY A "X" MARK HE MADE ON FLAT STONES LOCATED 20 LINKS AND 33 LINKS SOUTH OF THE TRUE CORNER

CONTINUED ON PAGE 2

- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 80, A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 112 DATED JULY 28, 1903 FOR A COUNTY ROAD IN TOWNSHIP 19, RANGE 10, SAID THAT **HE FOUND THE STONE ON LINE WITH A FENCE NORTH AND 38' SOUTH OF A HEDGE** AT THE NORTHEAST CORNER OF SECTION 31-19-10 ON THIS ROAD SURVEY. HIS FIELD NOTES ARE IN HIS BOOK 3 ON PAGE 188. NO WIDTH WAS RECORDED ON THIS SURVEY.

HIS FIELD NOTES AND PLAT SHOWS THE FOLLOWING INFORMATION:

- 1) BEGINNING AT THE COUNTY LINE AT THE SOUTHWEST CORNER OF SECTION 30-19-10, I RAN EAST ON THE SECTION LINE 20.16 CHAINS TO THE STONE SET BY MILLIKEN 22 LINKS NORTH OF A HEDGE, 40.16 CHAINS TO THE 1/4 CORNER, 80.21 CHAINS TO THE SECTION CORNER ON LINE WITH A FENCE NORTH 38 LINKS SOUTH OF A HEDGE; THENCE RUNNING TRANSIT LINE OVER THE 1/4 CORNER 40.07 CHAINS THE 1/4 CORNER SET BY BROWN, 80.14 CHAINS SET STAKE NUMBER 1.
- 2) BEGAN AT THE NORTHEAST CORNER OF SECTION 29-19-10, I RAN SOUTH 19.98 CHAINS THE 1/2/4 CORNER, 39.94 CHAINS THE 1/4 CORNER, 79.98 CHAINS STAKE NUMBER 1. THE VIEWERS BEING SATISFIED THAT THIS WAS THE TRUE CORNER **I SET A STONE 27" X 6" X 4" MARKED "R" ON THE WEST SIDE.** THENCE RAN EAST 40.01 CHAINS THE 1/4 CORNER (?) (SETS WRONG WAY IN GROUND) 6 LINKS WEST OF A HEDGE, 60.06 CHAINS THE 1/2/4 CORNER (?), 80 CHAINS SET STAKE NUMBER 2.
- 3) BEGAN AT THE 1/4 CORNER BETWEEN SECTIONS 27 & 28-19-10, I RAN SOUTH 19.96 CHAINS THE 1/2/4 CORNER, 39.92 CHAINS SET STAKE 8 LINKS EAST OF STAKE NUMBER 2, 79.96 CHAINS THE 1/4 CORNER IN LINE WITH FENCES 20 FEET WEST OF A STONE WALL. THE VIEWERS DECIDED THAT THE LAST STAKE SET AT THE NORTHEAST CORNER OF SECTION 33 WAS CORRECT AND **I SET A STONE 16" X 12" X 4" MARKED "R" ON THE WEST SIDE.** THENCE RAN EAST 79.96 CHAINS TO THE STONE AT THE NORTHEAST CORNER OF SECTION 34-19-10 20 FEET FROM FENCES.

- 5) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY FOR ROAD NUMBER 584 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 205 THROUGH 208 [PACKET 726 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY WILLIAM EVANS AND OTHERS FOR REMARKING A ROAD IN TOWNSHIP 19-10 THAT HE SURVEYED ON JULY 28, 1903, SAID THAT **HE FOUND THE STONE ON LINE WITH A FENCE NORTH AND 38' SOUTH OF A HEDGE** AT THE NORTHEAST CORNER OF SECTION 31-19-10 ON THIS ROAD SURVEY.

HIS FIELD NOTES AND PLAT SHOWS THE FOLLOWING INFORMATION:

- 1) BEGINNING AT THE COUNTY LINE AT THE SOUTHWEST CORNER OF SECTION 30-19-10, I RAN EAST ON THE SECTION LINE 20.16 CHAINS TO THE STONE SET BY MILLIKEN 22 LINKS NORTH OF A HEDGE, 40.16 CHAINS TO THE 1/4 CORNER, 80.21 CHAINS TO THE SECTION CORNER ON LINE WITH A FENCE NORTH 38 LINKS SOUTH OF A HEDGE; THENCE RUNNING TRANSIT LINE OVER THE 1/4 CORNER 40.07 CHAINS THE 1/4 CORNER SET BY BROWN, 80.14 CHAINS SET STAKE NUMBER 1.
- 2) BEGAN AT THE NORTHEAST CORNER OF SECTION 29-19-10, I RAN SOUTH 19.98 CHAINS THE 1/2/4 CORNER, 39.94 CHAINS THE 1/4 CORNER, 79.98 CHAINS STAKE NUMBER 1. THE VIEWERS BEING SATISFIED THAT THIS WAS THE TRUE CORNER **I SET A STONE 27" X 6" X 4" MARKED "R" ON THE WEST SIDE.** THENCE RAN EAST 40.01 CHAINS THE 1/4 CORNER (?) (SETS WRONG WAY IN GROUND) 6 LINKS WEST OF A HEDGE, 60.06 CHAINS THE 1/2/4 CORNER (?), 80 CHAINS SET STAKE NUMBER 2.
- 3) BEGAN AT THE 1/4 CORNER BETWEEN SECTIONS 27 & 28-19-10, I RAN SOUTH 19.96 CHAINS THE 1/2/4 CORNER, 39.92 CHAINS SET STAKE 8 LINKS EAST OF STAKE NUMBER 2, 79.96 CHAINS THE 1/4 CORNER IN LINE WITH FENCES 20

FEET WEST OF A STONE WALL. THE VIEWERS DECIDED THAT THE LAST STAKE SET AT THE NORTHEAST CORNER OF SECTION 33 WAS CORRECT AND **I SET A STONE 16" X 12" X 4" MARKED "R" ON THE WEST SIDE.** THENCE RAN EAST 79.96 CHAINS TO THE STONE AT THE NORTHEAST CORNER OF SECTION 34-19-10 20 FEET FROM FENCES.

- 4) THE VIEWERS SAID THAT THE ROAD IS PRACTICABLE AND OF PUBLIC UTILITY, AND RECOMMENDED THAT IT BE GRANTED AS SURVEYED AND LOCATED, AND THAT IT BE ESTABLISHED AND OPENED ON THE SECTION LINE AS LOCATED ACCORDING TO THE SURVEYORS REPORT AT 40 FEET WIDE, 20 FEET EACH SIDE OF THE SECTION LINE.
  
- 6) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, IN SURVEY NUMBER 182, A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 REQUESTED BY SOL WILLIAMS TO MAKE A SURVEY OF THE LINE BETWEEN SECTIONS 29 & 30-19-10 AND ESTABLISH THE SAME, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 30-19-10 TO BEGIN THIS **PERMANENT SURVEY.** THE SURVEY WAS COMPLETED ON MARCH 21, 1907 AND ENTERED IN THE PERMANENT SURVEY BOOK ON APRIL 30, 1907.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 2,640' NORTH TO THE 4" X 9" X 30" LIMESTONE HE SET FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 30-19-10, FROM WHICH AN ELM TREE IS S. 30° W. AT 18-9/10 FEET, AND AN ASH TREE IS S. 44°30" E. AT 17 FEET
  - 2) 3,960' NORTH TO THE STAKE HE SET FOR THE PERMANENT WEST 1/8<sup>TH</sup> CORNER OF THE NE1/4 OF SECTION 30-19-10
  - 3) 5,280' NORTH TO THE SMALL HEDGE STAKE HE SET IN THE GROUND FOR THE PERMANENT NORTHEAST CORNER OF SECTION 30-19-10
  
- 7) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A SURVEY RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 56 FROM THE NOTICE FROM J. F. COOK REQUIRING HIM TO ESTABLISH THE CORNER STONE AT THE SOUTHWEST CORNER OF THE NORTHWEST 1/4 OF SECTION 29-19-10, WHICH HAD BEEN DISPLACED, AND TO SURVEY THE LINE BETWEEN THE SOUTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 29-19-10, AND THE SOUTHEAST 1/4 OF THE NORTHEAST 1/4 OF SECTION 30-19-10, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 29-19-10 ON THIS **PERMANENT SURVEY.** THE SURVEY WAS MADE ON MARCH 17, 1910 AND ENTERED ON MARCH 24, 1910.  
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
  - 1) 2,640' NORTH TO THE STONE THAT HE FOUND AND **HE RESET** FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 29-19-10
  - 2) 3,960' NORTH TO THE 8" X 12" X 18" LIMESTONE HE SET FOR THE PERMANENT NORTHWEST CORNER OF THE SW1/4 OF THE NW1/4 OF SECTION 29-19-10
  
- 8) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 19-10 SHOWS A **1/2" IRON PIN** AT THE "SE CORNER SECTION 30-19-10". THE NOTE STATES THAT IT WAS "SET AS PER NOTES OF ALVA SMITH IN LINE WITH FENCES NORTH & SOUTH".
  - 2) 50.6' SW TO THE BASE OF THE EAST STEEL GATE POST
  - 3) 40.5' SOUTH TO A SPIKE IN THE TOP OF A CORNER FENCE POST
  
- 9) LESLIE M. GOULD, L.S 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN A REPORT OF A **PERMANENT SURVEY** IN SECTION 19-19-10 MADE PRIMARILY TO LOCATE THE BOUNDARIES OF THE EAST 1/2 OF THE WEST 1/2 OF SECTION 19-19-10 THAT WAS BEGUN ON APRIL 16, 1969 AND WAS COMPLETED ON APRIL 24, 1969 AND RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 53 AND RECORDED IN VOLUME 2 OF PLATS ON PAGE 58 IN THE REGISTER OF DEEDS OFFICE ON AUGUST 27, 1969, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE "CORNER IN**

**PLACE” AT THE SOUTHEAST CORNER OF SECTION 30-19-10 ON THIS PERMANENT SURVEY. HE DID NOT DESCRIBE THE MONUMENT THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 30-19-10. HE ALSO NOTED THAT ACCORDING TO GOVERNMENT SURVEY NOTES THE EAST LINE OF SECTIONS 19-19-10 AND 30-19-10 IS ON A TANGENT OR STRAIGHT LINE FOR 5 MILES. THEREFORE THE EAST LINE OF SECTION 30-19-10 WAS PRODUCED NORTH TO ARRIVE AT THE RESULTS AS SHOWN ON THIS PERMANENT SURVEY. THERE ARE NO TIES ON THE SURVEY.**

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 5,291.4’ WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 30-19-10 ON THE RANGE LINE AND THE LYON AND CHASE COUNTY LINE
- 10) IN A FIELD BOOK MARKED “RT. 1078 HEINZ ROAD” IN THE VAULT IN THE COUNTY ENGINEER’S OFFICE FOR THE ALIGNMENT OF THE HEINZ ROAD [ROAD 140] IN 1957, IT SHOWS A **REBAR** AT THE NORTHWEST CORNER OF SECTION 32-19-10 ON PAGE 9 AT **STATION 52+90**.
- 1) 25.7’ SOUTH TO A STONE POST

- 11) GREGORY ALAN MILES, L.S. 667, IN SURVEY F31001 IN THE SURVEY FILE FOR TOWNSHIP 19-10 FOR A SURVEY OF THE EAST HALF OF THE SOUTHWEST QUARTER OF SECTION 31-19-10 FOR PROJECT NUMBER 82-144 DATED OCTOBER 5, 1982, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND A NAIL** AT THE NORTHEAST CORNER OF SECTION 31-19-10. **[NOTE: THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES. VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THERE IS NO RECORD OF THE ORIGIN OF THIS NAIL. WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]**

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 5,290.46’ WEST TO THE NAIL HE FOUND AT THE NORTHWEST CORNER OF SECTION 31-19-10 ON THE RANGE LINE AND THE LYON AND CHASE COUNTY LINE
- 2) 2,634.53’ SOUTH TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 31-19-10

- 12) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JANUARY 15, 2009 FOR PROJECT NUMBER 08376-02, SURVEY F32001 IN THE SURVEY FILE FOR TOWNSHIP 19-10 FOR A SURVEY OF THE NORTH 495 FEET OF THE NORTHWEST QUARTER OF SECTION 31-19-10 FOR CRESS/BEYER, SAID THAT **HE FOUND A 1” IRON PIN IN A BROKEN STONE** AT THE NORTHWEST CORNER OF SECTION 32-19-10 FROM HIS PREVIOUS SURVEY IN 1989.

- 1) **1.6’ SOUTH TO A 1/2” REBAR FOUND**
- 2) 42’ SOUTH TO A PK NAIL & WASHER IN A CORNER FENCE POST
- 3) 96.9’ SW TO A PK NAIL & WASHER IN A POWER POLE
- 4) IN LINE WITH A FENCE TO THE SOUTH
- 5) 495.00’ SOUTH TO A 1/2” REBAR WITH HIS “LS 752” CAP SET **[HORIZONTAL TIE]**

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,644.15’ EAST TO THE 5/8” REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHEAST CORNER OF THE NW1/4 OF SECTION 32-19-10
- 2) 495.00’ SOUTH TO THE 1/2” REBAR WITH HIS “LS 752” CAP HE SET FOR THE SOUTHWEST CORNER OF THE NORTH 495’ OF THE NW1/4 OF SECTION 32-19-10
- 3) 2,636.12’ SOUTH TO THE 1/2” REBAR WITH “MILES” CAP HE FOUND AT THE SOUTHWEST CORNER OF THE NW1/4 OF SECTION 32-19-10
- 4) 5,268.73’ SOUTH TO THE 5/8” REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 32-19-10 ON THE TOWNSHIP LINE

CONTINUED ON PAGE 5

- 13) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JULY 5, 2012 FOR PROJECT NUMBER 112159-02, SURVEY F32002 IN THE SURVEY FILE FOR TOWNSHIP 19-10 FOR A SURVEY OF THE NORTH 495 FEET AND THE SOUTH LINE OF A 6.7 ACRE TRACT IN THE NORTHWEST QUARTER OF SECTION 31-19-10 FOR MARK REMMERT, SAID THAT **HE FOUND A 1" BENT IRON PIN** AT THE NORTHWEST CORNER OF SECTION 32-19-10 FROM EXISTING REFERENCE TIES ON FILE AT THE COUNTY ROAD AND BRIDGE DEPARTMENT FROM HIS 2009 TIES. [**NOTE:** HIS 2009 TIES INDICATE THAT THIS IRON PIN IS IN A **BROKEN STONE**. WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]
- 1) **1.6' SOUTH TO A 1/2" REBAR FOUND**
  - 2) 42.15' SOUTH TO A CONCRETE NAIL & WASHER IN THE WEST SIDE OF A CORNER FENCE POST
  - 3) 96.9' SW TO A PK NAIL & WASHER IN A POWER POLE
  - 4) IN LINE WITH A FENCE TO THE SOUTH
  - 5) 495.00' SOUTH TO A 1/2" IRON PIN WITH HIS "LS 752" CAP HE FOUND [**HORIZONTAL TIE**]
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,644.15' EAST TO THE 5/8" IRON PIN WITH A LYON COUNTY CAP HE FOUND AT THE NORTHEAST CORNER OF THE NW1/4 OF SECTION 32-19-10
- 14) JASON R. LOADER, P.S. 1462, OF KAW VALLEY ENGINEERING, IN A LAND SURVEY REFERENCE REPORT DATED NOVEMBER 24, 2015 FOR PROJECT NUMBER F14S0058, THE SURVEY OF TWO TRACTS IN THE SOUTHEAST 1/4 OF SECTION 29-19-10 FOR FARM AND HOME REAL ESTATE ON AUGUST 21, 2014, SURVEY F29002 IN THE SURVEY FILE FOR TOWNSHIP 19-10, SAID THAT **HE FOUND THE EXISTENT 3/4" IRON BAR 0.35' BELOW THE GROUND SURFACE** AT THE SOUTHWEST CORNER OF SECTION 29-19-10 FROM SURVEY REFERENCE TIES OBTAINED FROM THE LYON COUNTY HIGHWAY DEPARTMENT. [**NOTE:** THE 2009 TIES FROM STEVEN S. BROSEMER, DEPUTY COUNTY SURVEYOR, INDICATE THAT THIS IRON PIN IS IN A **BROKEN STONE**. WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR] HE SENT THE FOLLOWING **HORIZONTAL TIES:**
- 1) 1.0' SOUTH TO THE CENTERLINE OF EAST-WEST GRAVEL COUNTY ROAD 140
  - 2) 42.55' SOUTH TO A MAG NAIL AND WASHER IN THE TOP OF A CORNER FENCE POST
  - 3) 97.0' SW TO A 60 D NAIL AND WASHER IN THE NORTH FACE OF A POWER POLE WITH A GUY ANCHOR
  - 4) 58.7' NORTH TO A MAG NAIL AND WASHER IN THE EAST FACE OF A CORNER FENCE POST
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,643.88' EAST TO THE 1/2" REBAR WITH A RED LYON COUNTY CAP HE FOUND AT THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 29-19-10
  - 2) 5,288.80' EAST TO THE 1/2" X 24" REBAR WITH "KVE CLS 20" CAP HE SET FOR THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 29-19-10
  - 3) 7,927.23' EAST TO THE 1/2" X 24" REBAR WITH "KVE CLS 20" CAP HE SET FOR THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 28-19-10
  - 4) 10,569.77' EAST TO THE 1/2" X 24" REBAR WITH "KVE CLS 20" CAP HE SET FOR THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 28-19-10

NORTHWEST CORNER SECTION 32-19-10