

WEST 1/4 CORNER SECTION 32, TOWNSHIP 19 SOUTH, RANGE 10 EAST

- 1) ON PAGE 214 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 26" X 14" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 31 & 32-19-10 AT THE FOOT OF A HILL.

- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 78, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 158 DATED JULY 14 & 15, 1903 AT THE REQUEST OF J. ROSECRANTS FOR A SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE EAST 1/2 AND THE EAST 1/2 OF THE SOUTHWEST 1/4 OF SECTION 31-19-10 AND RUN SUCH LINES AS ARE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE UNDER A FENCE EXTENDING EAST AND 5 OR 6 FEET EAST OF A NORTH-SOUTH FENCE** AT THE EAST 1/4 CORNER OF SECTION 31-19-10 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK 3 ON PAGE 186 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 69" IN MISCELLANEOUS DRAWER NUMBER 3 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.93 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 31-19-10, ON LINE WITH A FENCE TO THE NORTH AND 57 LINKS SOUTH OF A HEDGE
 - 2) 39.93 CHAINS SOUTH TO THE STONE HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 31-19-10 ON THE TOWNSHIP LINE, AND WITNESSED BY A "X" HE MADE ON FLAT STONES AT 20 LINKS AND 33 LINKS SOUTH OF THE TRUE CORNER

- 3) GREGORY ALAN MILES, L.S. 667, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 5, 1982 FOR PROJECT NUMBER 82-114, SURVEY F31001 IN THE SURVEY FILE FOR TOWNSHIP 19-10 FOR A SURVEY OF THE EAST HALF OF THE SOUTHWEST QUARTER OF SECTION 31-19-10 SAID THAT **HE FOUND THE GLO STONE** AT THE EAST 1/4 CORNER OF SECTION 31-19-10 FROM CALLS GIVEN IN ALVA J. SMITH'S OFFICIAL SURVEY IN 1903. **HE SET A 1/2" REBAR WITH HIS "LS 667" CAP ON THE NORTH SIDE OF THE STONE.**
 - 1) 36.6' SSE TO A NAIL IN A 26" COTTONWOOD TREE
 - 2) 40.9' SW TO A NAIL IN THE TOP OF A FENCE POST
 - 3) 4.8' WEST TO THE TOP OF A BENT CORNER POST
 - 4) 29.3' NW TO A NAIL IN THE TOP OF A FENCE POST
 - 5) THE STONE AND PIN ARE LOCATED UNDER AN EAST-WEST FENCEHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,639.99' WEST TO THE 1/2" REBAR WITH HIS "LS 667" CAP HE SET FOR THE CENTER CORNER OF SECTION 31-19-10
 - 2) 3,961.35' WEST TO THE #9 REBAR HE FOUND AT THE NORTHWEST CORNER OF THE E1/2 OF THE SW1/4 OF SECTION 31-19-10, AND **HE RESET WITH A 1/2" REBAR WITH HIS "LS 667" CAP**
 - 3) 2,634.53' NORTH TO THE NAIL HE FOUND AT THE NORTHEAST CORNER OF SECTION 31-19-10

- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JANUARY 15, 2009 FOR PROJECT NUMBER 08376-02, SURVEY F32001 IN THE SURVEY FILE FOR TOWNSHIP 19-10 FOR A SURVEY OF THE NORTH 495 FEET OF THE NORTHWEST QUARTER OF SECTION 31-19-10 FOR CRESS/BEYER, SAID THAT **HE FOUND A 1/2" REBAR WITH A "MILES LS 667" CAP** AT THE WEST 1/4 CORNER OF SECTION 32-19-10 FROM REFERENCE TIES ON FILE AT

THE COUNTY ENGINEER'S OFFICE. HE SAID THAT THE STONE THAT WAS SET BY ALVA J. SMITH IN A 1903 PERMANENT SURVEY WAS **NOT** FOUND BY THE REBAR THAT WAS SET BY MILES.

- 1) IN LINE WITH AN EAST-WEST FENCE
- 2) 4.8' WEST TO A FENCE RUNNING NORTH-SOUTH
- 3) 45.75' NNW TO A 6" PIPE CORNER FENCE POST
- 4) 6' WEST TO A CONCRETE NAIL & BOTTLECAP IN THE TOP OF A CORNER FENCE POST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,141.12' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE NORTH 495' OF THE NW1/4 OF SECTION 32-19-10
- 2) 2,636.12' NORTH TO THE 1" PIN AND STONE HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 32-19-10
- 3) 2,632.61' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 32-19-10

WEST QUARTER CORNER SECTION 32-19-10