

WEST 1/4 CORNER SECTION 33, TOWNSHIP 19 SOUTH, RANGE 10 EAST

- 1) ON PAGE 208 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 36" X 8" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 32 & 33-19-10 ON APRIL 12, 1857.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS NORTH TO THE 21" X 14" X 2" LIMESTONE THEY SET FOR THE 1/4 CORNER TO SECTIONS 28, 29, 32 & 33-19-10
 - 2) 40.00 CHAINS SOUTH TO THE 20" X 12" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 32 & 33-19-10 ON THE SOUTH TOWNSHIP BOUNDARY

- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 80, A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 112 DATED JULY 28, 1903 FOR A COUNTY ROAD IN TOWNSHIP 19, RANGE 10, SHOWS ON HIS SURVEY PLAT THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 33-19-10, BUT HE DOES NOT MENTION THIS CORNER IN HIS FIELD NOTES. HIS FIELD NOTES ARE IN HIS BOOK 3 ON PAGE 188.

- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY FOR ROAD NUMBER 584 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 205 THROUGH 208 [PACKET 726 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY WILLIAM EVANS AND OTHERS FOR REMARKING A ROAD IN TOWNSHIP 19-10 THAT HE SURVEYED ON JULY 28, 1903, SHOWS ON HIS SURVEY PLAT THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 33-19-10, BUT HE DOES NOT MENTION THIS CORNER IN HIS FIELD NOTES.

- 4) JASON R. LOADER, P.S. 1462, OF KAW VALLEY ENGINEERING, IN A LAND SURVEY REFERENCE REPORT DATED NOVEMBER 24, 2015 FOR PROJECT NUMBER F14S0058, THE SURVEY OF TWO TRACTS IN THE SOUTHEAST 1/4 OF SECTION 29-19-10 FOR FARM AND HOME REAL ESTATE ON AUGUST 21, 2014, SURVEY F29002 IN THE SURVEY FILE FOR TOWNSHIP 19-10, SAID THAT **HE FOUND AN EXISTENT 1/2" REBAR AT 0.1' BELOW THE GRAVEL ROAD SURFACE** AT THE EAST 1/4 CORNER OF SECTION 32-19-10. IN HIS SURVEYOR REPORT HE SAID THAT IT MEASURES APPROXIMATELY TO THE CALCULATED SOUTHEAST CORNER OF SECTION 29 AND ALIGNING WITH A HEDGE ROW TO THE WEST. THE REBAR WAS LOCATED WITH A METAL LOCATOR, TIED OUT, THEN REMOVED FOR EXCAVATION TO SEARCH FOR THE ORIGINAL STONE MONUMENTATION. WITH ASSISTANCE FROM THE LYON COUNTY HIGHWAY DEPARTMENT, AND AREA 6' X 6' X 5' IN DEPTH, CENTERED OVER THE FOUND REBAR, WAS EXCAVATED. AFTER NO EVIDENCE OF A STONE MONUMENT WAS FOUND, THE AREA WAS FILLED IN AND THE REBAR WAS RESET AT ITS FOUND LOCATION AND **ACCEPTED** AS THE LOCATION FOR THE EAST 1/4 CORNER OF SECTION 32-19-10. HE SENT THE FOLLOWING **HORIZONTAL TIES:**
 - 1) 1.0' WEST TO THE CENTERLINE OF NORTH-SOUTH COUNTY ROAD "C"
 - 2) 35.25' NW TO A MAG NAIL AND WASHER IN THE NORTHEAST FACE OF AN 18" HEDGE TREE
 - 3) 27.45' ENE TO A 60 DA NAIL AND WASHER IN THE TOP OF A FENCE POST
 - 4) 44.20' WEST TO A STONE CORNER FENCE POSTHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,642.62' NORTH TO THE 1/2" X 24" REBAR WITH "KVE CLS 20" CAP HE SET FOR THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 29-19-10
 - 2) 3,957.39' NORTH TO THE 1/2" X 24" REBAR WITH "KVE CLS 20" CAP HE SET FOR THE SOUTHEAST CORNER OF TRACT "B"
 - 3) 4,307.39' NORTH TO THE 1/2" X 24" REBAR WITH "KVE CLS 20" CAP HE SET FOR THE P.O.B. OF TRACT "B" AND THE SOUTHEAST CORNER OF TRACT "A"

HIS INFORMATION IS CONTINUED ON PAGE 2

- 4) 4,617.39' NORTH TO THE 1/2" X 24" REBAR WITH "KVE CLS 20" CAP HE SET FOR THE P.O.B. OF TRACT "A"
- 5) 5,277.39' NORTH TO THE 1/2" X 24" REBAR WITH "KVE CLS 20" CAP HE SET FOR THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 29-19-10
- 6) 7,912.16' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY RED CAP HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 29-19-10

WEST QUARTER CORNER SECTION 33-19-10