

**NORTH 1/4 CORNER SECTION 34, TOWNSHIP 19 SOUTH, RANGE 10 EAST**

- 1) ON PAGE 203 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 14" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 27 & 34-19-10.  
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 40.04 CHAINS WEST TO THE 22" X 16" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 27, 28, 33 & 34-19-10
  - 2) 40.04 CHAINS EAST TO THE 24" X 14" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 26, 27, 34 & 35-19-10
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 118 OF THE 7<sup>TH</sup> TERM, A ROAD SURVEY RECORDED IN SURVEY BOOK C ON PAGE 40 DATED OCTOBER 20, 1874 FOR A COUNTY ROAD IN TOWNSHIP 19, RANGE 10, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 34-19-10 ON THIS ROAD SURVEY.
- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 80, A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 112 DATED JULY 28, 1903 FOR A COUNTY ROAD IN TOWNSHIP 19, RANGE 10, APPARENTLY DID **NOT** FIND THE STONE AT THE NORTH 1/4 CORNER OF SECTION 34-19-10 ON THIS ROAD SURVEY WHEN HE RAN THE SECTION LINES FROM THE STONE THAT HE SET FOR THE NORTHEAST CORNER OF SECTION 33-19-10 TO THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 34-19-10. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 188 IN THE "KRETSINGER COLLECTION".
- 4) REA BOOK 31 ON PAGE 17 SHOWS THAT **THEY DROVE AN IRON PIN** FOR THE SOUTH 1/4 CORNER OF SECTION 27-19-10 AT 2,645 FEET EAST OF THE SOUTHEAST CORNER OF SECTION 28-19-10 AND IN LINE WITH WIRE FENCES TO THE NORTH AND SOUTH. THEY SAID THAT THEY DUG FOR THE STONE AT THIS CORNER, BUT THEY DID **NOT** FIND IT. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY JUST "HEELED-IN" FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
  - 1) 18' NORTH TO A WITNESS PIN JUST EAST OF A TELEPHONE POLE AT THE END OF THE FENCE NORTH
- 5) IN A FIELD BOOK LABELED "RT. 1078 HEINZ ROAD" IN THE VAULT IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE FOR THE ALIGNMENT OF THE HEINZ ROAD, [ROAD 140] IN 1957, IT SHOWS A **REBAR** AT THE NORTH 1/4 CORNER OF SECTION 34 ON PAGE 31 AT STATION 185+04.75. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN MY BE THE REA PIN – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
  - 1) 34.8' NE TO A SPIKE IN A TELEPHONE POLE
  - 2) 28.95' SOUTH TO A SPIKE IN THE TOP OF A POST
- 6) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 19-10 SHOWS A **REA PIN** AT THE "N1/4 CORNER SECTION 34-19-10". **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY JUST "HEELED-IN" FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
  - 1) 18' NORTH TO A WITNESS [REA]
- 7) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 19-10 SHOWS AN **IRON PIN** AT THE "SW CORNER SE1/4 OF SECTION 27-19-10". **VERIFY AND CHECK FOR**

**THE STONE OF RECORD BEFORE USING AS THIS MAY BE THE REA PIN!!  
WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**

- 1) 56.00' NNE TO A SPIKE IN A CORNER FENCE POST
- 2) 51.60' SSE TO A SPIKE IN A CORNER FENCE POST

NORTH QUARTER CORNER SECTION 34-19-10