

**WEST 1/4 CORNER SECTION 34, TOWNSHIP 19 SOUTH, RANGE 10 EAST**

1) ON PAGE 202 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 18" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 33 & 34-19-10.

2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 80, A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 112 DATED JULY 28, 1903 FOR A COUNTY ROAD IN TOWNSHIP 19, RANGE 10, SAID THAT **HE FOUND THE STONE AT THE EAST 1/4 CORNER OF SECTION 33-19-10 ON LINE WITH THE FENCES AND 20 FEET WEST OF A STONE WALL.** HE USED THIS STONE, THE STONE THAT HE FOUND AT THE EAST 1/2/4 CORNER OF THE SOUTHEAST 1/4 OF SECTION 28-19-10, AND THE STONE THAT HE FOUND AT THE EAST 1/4 CORNER OF SECTION 28-19-10 TO SET A 16" X 12" X 4" STONE MARKED "R" ON THE WEST FACE FOR THE NORTHEAST CORNER OF SECTION 33-19-10 ON THIS ROAD SURVEY. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 188 IN THE "KRETSINGER COLLECTION".

HIS NOTES/DRAWING SHOWS THE FOLLOWING DISTANCES:

- 1) 40.04 CHAINS NORTH TO THE 16" X 12" X 4" STONE MARKED "R" ON THE WEST FACE HE SET FOR THE NORTHEAST CORNER OF SECTION 33-19-10, FOR THE ROAD THAT BEGAN AT THE SOUTHWEST CORNER OF SECTION 30-19-10 ON THE RANGE LINE AND THE LYON AND CHASE COUNTY LINE TO BEGIN THIS ROAD THAT EXTENDED EAST ON THE SECTION LINES FOR 4 MILES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 34-19-10 AT THE TERMINUS OF THIS ROAD SURVEY
- 2) 60.00 CHAINS NORTH TO THE STONE HE FOUND AT THE EAST 1/2/4 CORNER OF THE SE1/4 OF SECTION 28-19-10
- 3) 79.96 CHAINS NORTH TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 28-19-10

3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY FOR ROAD NUMBER 584 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 205 THROUGH 208 PETITION BY WILLIAM EVANS AND OTHERS FOR REMARKING A ROAD IN TOWNSHIP 19-10 [PACKET 726 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JULY 28, 1903, SAID THAT **HE FOUND THE STONE IN LINE WITH THE FENCES AND 20 FEET WEST OF A STONE WALL** AT THE EAST 1/4 CORNER OF SECTION 33-19-10 ON THIS ROAD SURVEY. HE USED THIS STONE, THE STONE THAT HE FOUND AT THE EAST 1/2/4 CORNER OF THE SOUTHEAST 1/4 OF SECTION 28-19-10, AND THE STONE THAT HE FOUND AT THE EAST 1/4 CORNER OF SECTION 28-19-10 TO SET A 16" X 12" X 4" STONE MARKED "R" ON THE WEST FACE FOR THE NORTHEAST CORNER OF SECTION 33-19-10.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 4) 40.04 CHAINS NORTH TO THE 16" X 12" X 4" STONE MARKED "R" ON THE WEST FACE HE SET FOR THE NORTHEAST CORNER OF SECTION 33-19-10, FOR THE ROAD THAT BEGAN AT THE SOUTHWEST CORNER OF SECTION 30-19-10 ON THE RANGE LINE AND THE LYON AND CHASE COUNTY LINE TO BEGIN THIS ROAD THAT EXTENDED EAST ON THE SECTION LINES FOR 4 MILES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 34-19-10 TO THE TERMINUS OF THIS ROAD SURVEY
- 5) 60.00 CHAINS NORTH TO THE STONE HE FOUND AT THE EAST 1/2/4 CORNER OF THE SE1/4 OF SECTION 28-19-10
- 6) 79.96 CHAINS NORTH TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 28-19-10

WEST QUARTER CORNER SECTION 34-19-10