

WEST 1/16TH CORNER OF THE NORTHEAST QUARTER OF SECTION 35, TOWNSHIP 19 SOUTH, RANGE 10 EAST

- 1) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN AN AGREEMENT SURVEY RECORDED IN SURVEY BOOK "D" ON PAGE 160 DATED JUNE 28, 1883 AT THE REQUEST OF WORKMAN, ET. AL. TO ESTABLISH THE 1/16TH CORNER ON THE CENTER OF THE NORTHEAST 1/4 OF SECTION 35-19-10, SAID THAT **HE FOUND THE STONE** AT THE 1/8TH CORNER ON THE WEST LINE OF THE NORTHEAST 1/4 OF SECTION 35 ON THIS AGREEMENT SURVEY.
HIS SURVEY NOTES SHOW THE FOLLOWING DISTANCES:
 - 1) 19.94 CHAINS EAST TO THE STONE HE SET FOR THE 1/16TH CORNER IN THE CENTER OF THE NE1/4 OF SECTION 35
 - 2) 39.88 CHAINS EAST TO THE STONE SET FOR THE 1/8TH CORNER ON THE EAST LINE OF THE NE1/4 OF SECTION 35

- 2) GREGORY ALAN MILES, L.S. 667, IN SURVEY F35001 IN THE SURVEY FILES FOR TOWNSHIP 19-10 FOR A PROPERTY SURVEY FOR 3 TRACTS IN THE NORTH HALF OF THE NORTHEAST QUARTER OF SECTION 35-19-10 FOR PROJECT NUMBER 83-150 DATED JUNE 1, 1983 SHOWS ON HIS SURVEY DRAWING THAT **HE SET A #4 REBAR WITH HIS "MILES LS 667" CAP** FOR THE SOUTHWEST CORNER OF THE NORTHWEST 1/4 OF THE NORTHEAST 1/4 OF SECTION 35. THIS CORNER IS ALSO THE SOUTHWEST CORNER OF TRACT 3.
HIS SURVEY DRAWING SHOWS THE FOLLOWING DISTANCES:
 - 1) 1,318.87' NORTH TO A #5 REBAR WITH A LYON COUNTY CAP HE FOUND THAT WAS SET BY THE COUNTY SURVEYOR AT THE NORTH 1/4 CORNER OF SECTION 35, BEING THE NORTHWEST CORNER OF TRACT NUMBER 3
 - 2) 1,319.52' EAST TO A #4 REBAR WITH HIS "MILES LS 667" CAP HE SET FOR THE SOUTHWEST CORNER OF THE NE1/4 OF THE NE1/4 OF SECTION 3, BEING THE SOUTHWEST CORNER OF TRACT NUMBER 1
 - 3) 2,639.03' EAST TO A #5 REBAR WITH A LYON COUNTY CAP HE FOUND THAT WAS SET BY THE COUNTY SURVEYOR AT THE SOUTHEAST CORNER OF THE NE1/4 OF THE NE1/4 OF SECTION 35. BEING THE SOUTHEAST CORNER OF TRACT NUMBER 1

WEST SIXTEENTH CORNER NORTHEAST QUARTER OF SECTION 35-19-10