

NORTH 1/4 CORNER SECTION 36, TOWNSHIP 19 SOUTH, RANGE 10 EAST

- 1) ON PAGE 189 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 11" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 25 & 36-19-10.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.16 CHAINS WEST TO THE 21" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 25, 26, 35 & 36-19-10
 - 2) 40.00 CHAINS EAST TO THE 26" X 17" X 2" SANDSTONE THEY SET FOR THE CORNER TO SECTIONS 25 & 36-19-10 ON THE EAST TOWNSHIP BOUNDARY

- 2) SAMUEL P. DAVIES, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 46, SURVEY 129 OF THE 7TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 45 DATED MAY 13, 1870 TO DIVIDE THE SOUTHEAST 1/4 OF SECTION 25-19-10 INTO 2 EQUAL PARTS BY A LINE PASSING NORTH & SOUTH THROUGH IT, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 25-19-10 ON THIS **PERMANENT SURVEY**.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,641' WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 25-19-10
 - 2) 1,325' EAST TO THE STONE POST HE SET FOR THE PERMANENT SOUTH 1/24 CORNER OF THE SE1/4 OF SECTION 25-19-10
 - 3) 2,650' EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 25-19-10 ON THE RANGE LINE

- 3) ROAD NUMBER 754 RECORDED IN ROAD RECORD BOOK 1 ON PAGE 10:
A CONTRACT DATED NOVEMBER 5, 1932 FOR A FIVE (5) FOOT STRIP PURCHASED BY THE PIKE TOWNSHIP BOARD FROM H. C. BEBERMYER OFF THE SOUTH SIDE OF THE SOUTHEAST 1/4 OF SECTION 25-19-10 BEGINNING AT A POINT TWENTY (20) FEET NORTH OF THE SOUTHEAST CORNER OF SECTION 25-19-10; THENCE WEST ON A LINE TWENTY (20) FEET FROM AND PARALLEL TO THE SOUTH LINE OF SAID SE1/4 A DISTANCE OF ONE-HALF (1/2) MILE; THENCE NORTH FIVE (5) FEET; THENCE EAST ON A LINE TWENTY-FIVE (25) FEET FROM AND PARALLEL TO THE SOUTH LINE OF SAID SE1/4 ONE-HALF (1/2) MILE; THENCE SOUTH 5 FEET TO THE PLACE OF BEGINNING, CONTAINING THREE-TENTHS (0.3) ACRES, MORE OR LESS.

- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 14, 2003, FOR PROJECT 03083-02, SAID THAT HE EXCAVATED FOR THE STONE AT THE NORTH 1/4 CORNER OF SECTION 36-19-10, BUT HE DID **NOT** FIND THE STONE. HE DEEMED THAT THE CORNER WAS **LOST** IN NORTH-SOUTH POSITION. HE SAID THAT THE EAST-WEST POSITION WAS NOT REESTABLISHED AT THIS TIME, SO HE DID **NOT** SET A MONUMENT FOR THE NORTH 1/4 CORNER OF SECTION 36-19-10.

- 5) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 22, 2007 FOR PROJECT NUMBER 07230-02, SURVEY F36003 IN THE SURVEY FILE FOR TOWNSHIP 19-10 FOR A SURVEY OF TWO TRACTS IN THE WEST HALF OF THE NORTHEAST QUARTER OF SECTION 36-19-10 FOR NELLIE OWENS, SAID THAT HE DEEMED THAT THE NORTH 1/4 CORNER OF SECTION 36-19-10 WAS **LOST**. **HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE NORTH 1/4 CORNER OF SECTION 36-19-10 FROM THE DAVIES SURVEY IN 1870 IN SURVEY BOOK "F" ON PAGE 45, BY PROPORTIONATE MEASURE. [**NOTE:** THE SURVEY BY SAMUEL P. DAVIES, DEPUTY COUNTY SURVEYOR, IS RECORDED IN SURVEY BOOK "B", NOT IN BOOK "F" – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]

HIS TIES ARE ON PAGE 2

- 1) 41.95' SW TO A 40 D NAIL & WASHER IN A POWER POLE
- 2) 49.40' SE TO THE WEST FACE OF A CHAIN-LINK FENCE CORNER POST
- 3) 37.70' NNE TO A 40 D NAIL & WASHER IN A HEDGE TREE
- 4) 37.5' SOUTH TO A LINE OF CHAIN-LINK FENCE TO THE EAST EXTENDED
- 5) 5.5' NORTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 140 EAST-WEST
- 6) 2.5' WEST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "F5" NORTH-SOUTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,643.23' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHWEST CORNER OF SECTION 36-19-10
- 2) 1,326.12' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHWEST CORNER OF THE E1/2 OF THE NE1/4 OF SECTION 36-19-10
- 3) 2,652.24' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP OVER THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 36-19-10 ON THE RANGE LINE
- 4) 2,633.94' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE CENTER CORNER OF SECTION 36-19-10
- 5) 5,283.90' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 36-19-10 ON THE TOWNSHIP LINE

- 6) AARON C. DAVIS, L.S. 1368, DEPUTY COUNTY SURVEYOR, IN SURVEY F36004 IN THE SURVEY FILE FOR TOWNSHIP 19-10 FOR A SURVEY OF THE NORTH HALF OF THE NORTHWEST QUARTER OF THE NORTHEAST QUARTER OF SECTION 36-19-10 FOR RICHARD MILLER FOR PROJECT NUMBER 07372-02 DATED NOVEMBER 2, 2007, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP** AT THE NORTH 1/4 CORNER OF SECTION 36-19-10. HIS TIES ARE MISSING FROM THE SURVEY TIE FILES.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,326.12' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHWEST CORNER OF THE N1/2 OF THE NE1/4 OF THE NE1/4 OF SECTION 36-19-10
- 2) 2,652.24' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP OVER THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 36-19-10 ON THE RANGE LINE
- 3) 1,316.97' SOUTH TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE SW1/4 OF THE NE1/4 OF SECTION 36-19-10
- 4) 2,633.94' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE CENTER CORNER OF SECTION 36-19-10

- 7) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 11, 2007 FOR PROJECT NUMBER 07426-02, SURVEY F36005 IN THE SURVEY FILE FOR TOWNSHIP 19-10 FOR 3 TRACTS IN THE WEST HALF OF THE NORTHEAST QUARTER OF SECTION 36-19-10 FOR NELLIE OWENS, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP** AT THE NORTH 1/4 CORNER OF SECTION 36-19-10 FROM HIS TIES OF OCTOBER 22, 2007.

- 1) 41.95' SW TO A 40 D NAIL & WASHER IN A POWER POLE
- 2) 49.40' SE TO THE WEST FACE OF A CHAIN-LINK FENCE CORNER POST
- 3) 37.70' NNE TO A 40 D NAIL & WASHER IN A HEDGE TREE
- 4) 37.5' SOUTH TO A LINE OF CHAIN-LINK FENCE TO THE EAST EXTENDED
- 5) 5.5' NORTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 140 EAST-WEST
- 6) 2.5' WEST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "F5" NORTH-SOUTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

HIS INFORMATION IS CONTINUED ON PAGE 3

- 1) 234.00' EAST TO THE NORTHEAST CORNER OF THE "HOUSE TRACT", AS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET AT 20' SOUTH
- 2) 1,326.12' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHEAST CORNER OF THE W1/2 OF THE NE1/4 OF SECTION 36-19-10
- 3) 1,312.25' SOUTH TO THE SOUTHWEST CORNER OF THE "HOUSE TRACT", AS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET AT 35' EAST IN A LINE OF FENCE TO THE NORTH AND SOUTH
- 4) 2,633.94' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE SOUTHWEST CORNER OF THE W1/2 OF THE NE1/4 OF SECTION 36-19-10

NORTH QUARTER CORNER SECTION 36-19-10