

**WEST 1/4 CORNER SECTION 36, TOWNSHIP 19 SOUTH, RANGE 10 EAST**

- 1) ON PAGE 189 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 19" X 12" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 35 & 36-19-10.
  
- 1) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN AN **AGREEMENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 160 DATED JUNE 28, 1883 AT THE REQUEST OF WORKMAN, ET. AL. TO ESTABLISH THE 1/16<sup>TH</sup> CORNER ON THE CENTER OF THE NORTHEAST 1/4 OF SECTION 35-19-10, SAID THAT **HE SET A STONE** FOR THE EAST 1/4 CORNER OF SECTION 35-19-10 ON LINE AND HALFWAY BETWEEN THE STONES HE FOUND AT THE NORTHEAST AND SOUTHEAST CORNERS OF SECTION 35-19-10 ON THIS **AGREEMENT SURVEY**.  
**HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:**
  - 1) 19.99 CHAINS NORTH TO THE STONE HE SET FOR THE EAST 1/8<sup>TH</sup> CORNER LINE OF THE NE1/4 OF SECTION 35-19-10
  - 2) 39.98 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 35-19-10
  - 3) 39.98 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 35-19-10 ON THE TOWNSHIP LINE
  
- 3) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED MAY 19, 1983, SAID THAT HE CONSIDERED THAT THE EAST 1/4 CORNER OF SECTION 35-19-10 WAS **LOST**. **HE SET A 5/8" REBAR WITH A PLASTIC LYON COUNTY CAP** FOR THE EAST 1/4 CORNER OF SECTION 35-19-10 ON TRUE LINE AND HALFWAY BETWEEN THE NORTHEAST CORNER AND THE SOUTHEAST CORNER OF SECTION 35-19-10 ON THE TOWNSHIP LINE, WHICH CONFORMS TO THE PHYSICAL EVIDENCE.
  - 1) 14.45' ENE TO THE CORNER OF THE SOUTH WINGWALL AT THE HUBGUARD
  - 2) 30.10' WNW TO THE CORNER OF THE SOUTH WINGWALL AT THE HUBGUARD
  - 3) 8.70' NORTH TO THE CENTERLINE OF A 6' RCB
  - 4) 4.00' WEST TO THE CENTERLINE TRAVELED WAY OF THE F.A.S. ROAD NORTH-SOUTH
  - 5) IN LINE WITH A FENCE TO THE EAST [EXTENDED]**HIS DRAWING ON HIS REFERENCE REPORT SHOWS THE FOLLOWING:**
  - 1) 2,649.98' SOUTH TO THE SOUTHEAST CORNER OF SECTION 35-19-10 ON THE TOWNSHIP LINE
  - 2) 1,324.99' NORTH TO THE EAST 1/16<sup>TH</sup> CORNER OF THE NE1/4 OF SECTION 35-19-10
  - 3) 2,649.98' NORTH TO THE NORTHEAST CORNER OF SECTION 35-19-10
  
- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 24, 2000, FOR PROJECT NUMBER 00480-14, SAID THAT **HE FOUND A BENT 1/2" REBAR** AT THE WEST 1/4 CORNER OF SECTION 36-19-10 FROM EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE DATED MAY 1983. **HE REPLACED THE BENT 1/2" REBAR WITH A 5/8" X 24" REBAR WITH A LYON COUNTY CAP.**
  - 1) 66.4' EAST TO A 40 D NAIL IN THE TOP OF A CORNER FENCE POST
  - 2) 47.4' NE TO A 40 D NAIL IN THE TOP OF A FENCE POST
  - 3) 8.3' NORTH TO THE CENTER OF THE BOX CULVERT
  - 4) IN LINE WITH A FENCE TO THE EAST
  
- 5) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 14, 2003, FOR PROJECT NUMBER 03083-02, SURVEY F36002 IN THE SURVEY FILE FOR TOWNSHIP 19-10 FOR THE SURVEY OF A 29.57 ACRE TRACT IN THE NORTHWEST QUARTER OF SECTION 36-19-10, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP** AT THE WEST 1/4

CORNER OF SECTION 36-19-10 FROM HIS EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE DATED OCTOBER 2000.

- 1) 66.75' EAST TO A 40 D NAIL IN THE TOP OF A CORNER FENCE POST
- 2) 47.4' NW TO A 40 D NAIL IN THE TOP OF A FENCE POST
- 3) 8.3' NORTH TO THE CENTER OF THE BOX CULVERT
- 4) IN LINE WITH A FENCE TO THE EAST
- 5) 71.00' NE TO A 40 D NAIL IN THE TOP OF A HEDGE FENCE POST
- 6) 3.0' EAST TO THE CENTERLINE TRAVELED WAY OF THE ROAD

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,354.81' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE 29.57 ACRE TRACT
- 2) 2,649.81' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 36-19-10

- 6) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 22, 2007 FOR PROJECT NUMBER 07230-02, SURVEY F36003 IN THE SURVEY FILE FOR TOWNSHIP 19-10 FOR A SURVEY OF TWO TRACTS IN THE WEST HALF OF THE NORTHEAST QUARTER OF SECTION 36-19-10 FOR NELLIE OWENS, SAID THAT **HE FOUND THE 5/8" X 24" REBAR WITH A LYON COUNTY CAP** AT THE WEST 1/4 CORNER OF SECTION 36-19-10 FROM HIS EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE DATED MARCH 2003.

- 1) 61.10' EAST TO A 40 D NAIL IN THE TOP OF A FENCE CORNER POST
- 2) 57.7' NW TO A 40 D NAIL IN THE TOP OF A FENCE POST
- 3) 8.5' NORTH TO THE CENTER OF A BOX CULVERT
- 4) IN LINE WITH FENCES TO THE EAST
- 5) 65.80' NE TO A 40 D NAIL IN THE TOP OF A HEDGE FENCE POST
- 6) 4.0' WEST TO THE CENTERLINE OF THE TRAVELED WAY OF THE ROAD

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,650.38' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHWEST CORNER OF SECTION 36-19-10
- 2) 2,649.42' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE SOUTHWEST CORNER OF SECTION 36-19-10 ON THE TOWNSHIP LINE
- 3) 2,638.72' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE CENTER CORNER OF SECTION 36-19-10
- 4) 3,960.30' EAST TO THE THEORETICAL POSITION FOR THE SOUTHWEST CORNER OF THE E1/2 OF THE NE1/4 OF SECTION 36-19-10
- 5) 5,281.88' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE EAST 1/4 CORNER OF SECTION 36-19-10 ON THE RANGE LINE

WEST QUARTER CORNER SECTION 36-19-10