

WEST 1/16TH CORNER OF THE NORTHWEST QUARTER OF SECTION 36, TOWNSHIP 19 SOUTH, RANGE 10 EAST

- 1) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN AN **AGREEMENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 160 DATED JUNE 28, 1883 AT THE REQUEST OF WORKMAN, ET. AL. TO ESTABLISH THE 1/16TH CORNER ON THE CENTER OF THE NORTHEAST 1/4 OF SECTION 35-19-10, SAID THAT **HE SET A STONE** FOR THE EAST 1/8TH CORNER OF THE NORTHEAST 1/4 OF SECTION 35-19-10 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE FOUND AT THE NORTHEAST CORNER AND THE STONE THAT HE SET FOR THE EAST 1/4 CORNER OF SECTION 35-19-10 ON THIS **AGREEMENT SURVEY**.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 19.99 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 35-19-10
 - 2) 19.99 CHAINS SOUTH TO THE STONE HE SET FOR THE EAST 1/4 CORNER OF SECTION 35-19-10
 - 3) 59.97 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 35-19-10 ON THE TOWNSHIP LINE
- 2) COMMISSIONER'S ROAD JOURNAL BOOK "B", PAGE 177
AN **AGREEMENT** SIGNED AUGUST 27, 1979 BETWEEN THE BOARD OF COUNTY COMMISSIONERS AND HENRY L. BAUGH WITH THE COUNTY PROVIDING A WELL PUMP TO SELL THE FOLLOWING TRACT OF LAND NEEDED TO WIDEN A COUNTY ROAD:
- 1) BEGINNING AT THE NORTHWEST CORNER OF SECTION 36-19-10; THENCE SOUTH 80 RODS; THENCE EAST 50 FEET; THENCE NORTH 620 FEET; THENCE EAST 15 FEET; THENCE NORTH 250 FEET; THENCE WEST 15 FEET; THENCE NORTH 450 FEET TO THE NORTH LINE OF SAID SECTION; THENCE WEST 50 FEET TO THE POINT OF BEGINNING, CONTAINING 0.75 ACRES MORE OR LESS, EXCEPT THAT PART NOW IN USE FOR HIGHWAY PURPOSES.

- 3) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED MAY 19, 1983, SAID THAT **HE SET A 1/2" X 24" REBAR WITH HIS "LS 752" CAP** FOR THE EAST 1/16TH CORNER OF THE NORTHEAST 1/4 OF SECTION 35-19-10 ON TRUE LINE AND HALF WAY BETWEEN THE NORTHEAST CORNER AND THE EAST 1/4 CORNER OF SECTION 35-19-10 AS PER A SURVEY BY RICE IN 1888.

- 1) 2.5' NORTH TO A LINE OF FENCE TO THE WEST [EXTENDED]
- 2) 4.0' NORTH TO A LINE OF FENCE TO THE EAST [EXTENDED]
- 3) IN THE CENTERLINE TRAVELED WAY OF THE F.A.S. ROAD

HIS DRAWING ON HIS REFERENCE REPORT SHOWS THE FOLLOWING:

- 1) 1,324.99' NORTH TO THE NORTHEAST CORNER OF SECTION 35-19-10
 - 2) 1,324.99' SOUTH TO THE EAST 1/4 CORNER OF SECTION 35-19-10
 - 3) 3,974.91' SOUTH TO THE SOUTHEAST CORNER OF SECTION 35-19-10 ON THE TOWN-SHIP LINE
- 4) GREGORY ALAN MILES, L.S. 667, IN SURVEY F35001 IN THE SURVEY FILES FOR TOWNSHIP 19-10 FOR A PROPERTY SURVEY FOR 3 TRACTS IN THE NORTH HALF OF THE NORTHEAST QUARTER OF SECTION 35-19-10 FOR PROJECT NUMBER 83-150 DATED JUNE 1, 1983 SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND A #5 REBAR WITH A PLASTIC CAP SET BY THE COUNTY SURVEYOR** AT THE SOUTHEAST CORNER OF THE NORTHEAST 1/4 OF THE NORTHEAST 1/4 OF SECTION 35-19-10. THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES. THIS CORNER IS ALSO THE SOUTHEAST CORNER OF TRACT 1.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

HIS INFORMATION IS CONTINUED ON PAGE 2

- 1) 1,319.51' WEST TO THE #4 REBAR WITH HIS "MILES LS 667" CAP HE SET FOR THE SOUTHWEST CORNER OF THE NE1/4 OF THE NE1/4 OF SECTION 35-19-10, BEING THE SOUTHWEST CORNER OF TRACT NUMBER 1
- 2) 2,639.03' WEST TO THE #4 REBAR WITH HIS "MILES LS 667" CAP HE SET FOR THE SOUTHWEST CORNER OF THE NW1/4 OF THE NE1/4 OF SECTION 35-19-10, BEING THE SOUTHWEST CORNER OF TRACT NUMBER 3
- 3) 662.50' NORTH TO THE #4 REBAR WITH HIS "MILES LS 667" CAP HE SET FOR THE NORTHEAST CORNER OF TRACT NUMBER 1
- 4) 1,325.00' NORTH TO THE #5 REBAR WITH A LYON COUNTY CAP HE FOUND THAT WAS SET BY THE COUNTY SURVEYOR AT THE NORTHEAST CORNER OF SECTION 35-19-10

WEST SIXTEENTH CORNER NORTHWEST QUARTER OF SECTION 36-19-10