

**NORTHWEST CORNER SECTION 01, TOWNSHIP 19 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 68 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 19" X 12" X 6"** FOR THE CORNER TO SECTIONS 1 & 2-19-11 ON THE TOWNSHIP LINE ON DECEMBER 9, 1856.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS EAST ON THE TOWNSHIP LINE TO THE 23" X 14" X 2-1/2" LIMESTONE THEY SET FOR THE NORTH 1/4 CORNER OF SECTION 1-19-11
  - 2) 80.00 CHAINS EAST ON THE TOWNSHIP LINE TO THE 36" X 12" X 6" LIMESTONE THEY SET FOR THE CORNER TO TOWNSHIPS 18 & 19 SOUTH, RANGES 11 & 12 EAST ON THE EAST TOWNSHIP BOUNDARY AT THE NORTHEAST CORNER OF SECTION 1-19-11
  - 3) 38.94 CHAINS SOUTH TO THE 23" X 14" X 2" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 1 & 2-19-11
  - 4) 78.94 CHAINS SOUTH TO THE 30" X 20" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 1, 2, 11 & 12-19-11
- 2) G. M. WALKER, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 32 RECORDED IN SURVEY BOOK "A" ON PAGE 66 DATED JANUARY 10, 1861 TO DIVIDE THE NORTHEAST 1/4 OF SECTION 2-19-11 INTO EAST AND WEST HALVES AND ESTABLISH THE NECESSARY BOUNDS AND CORNERS, SAID THAT **HE FOUND THE STONE POST** AT THE NORTHEAST CORNER OF SECTION 2-19-11 ON THE TOWNSHIP LINE ON THIS SURVEY.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 19.94 CHAINS WEST ON THE TOWNSHIP LINE TO THE STONE HE SET FOR THE N1/4/4 POST OF THE NE1/4 OF SECTION 2-19-11
  - 2) 39.88 CHAINS WEST ON THE TOWNSHIP LINE TO THE FOUND STONE NORTH 1/4 POST OF SECTION 2-19-11
- 3) G. M. WALKER, BRECKENRIDGE COUNTY DEPUTY SURVEYOR, IN SURVEY NUMBER 33 RECORDED IN SURVEY BOOK "A" ON PAGES 66 & 67 DATED JANUARY 12, 1861 TO ESTABLISH THE CENTER POST OF SECTION 35-18-11, ALSO TO DIVIDE THE NORTHWEST 1/4 INTO EAST AND WEST HALVES, ALSO TO DIVIDE THE SOUTHEAST 1/4 INTO EAST AND WEST HALVES, AND TO ESTABLISH THE BOUNDARIES OF A 40 ACRE LOT, BEING THE SOUTH PART OF THE EAST 1/2 OF THE SOUTHEAST 1/4 OF SECTION 34, SAID THAT **HE FOUND THE STONE POST** AT THE SOUTHEAST CORNER OF SECTION 35-18-11 ON THE TOWNSHIP LINE ON THIS SURVEY.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 19.94 CHAINS WEST ON THE TOWNSHIP LINE TO THE STONE HE FOUND AT THE S1/4/4 POST OF THE SE1/4 OF SECTION 35-18-11
  - 2) 20.07 CHAINS NORTH TO A STONE POST HE SET FOR THE NORTHEAST CORNER OF A 40 ACRE LOT IN THE SOUTH PART OF THE E1/2 OF THE SE1/4 OF SECTION 35-18-11
  - 3) 40.21 CHAINS NORTH TO THE FOUND STONE EAST 1/4 CORNER OF SECTION 35-18-11, "TAKEN FROM THE ROAD SURVEY AUGUST 24"
  - 4) 80.41 CHAINS NORTH TO THE STONE POST HE FOUND AT THE NORTHEAST CORNER OF SECTION 35-18-11, "TAKEN FROM THE ROAD SURVEY AUGUST 24"
- 4) G. M. WALKER, BRECKENRIDGE COUNTY DEPUTY SURVEYOR, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGE 32 [PACKET 918 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] FOR A ROAD IN FREMONT TOWNSHIP, BRECKENRIDGE COUNTY, PETITIONED BY THOMAS BRYANT AND OTHERS SURVEYED AUGUST 21, 1861 AND ESTABLISHED DECEMBER 3, 1861 ON THE COMMISSIONERS JOURNAL ON PAGE 163, SAID THAT **HE FOUND THE STONE** AT

THE SOUTHWEST CORNER OF SECTION 36-18-11 ON THE TOWNSHIP LINE, BEING ABOUT 35 FEET WEST OF THE LAWRENCE AND EMPORIA TERRITORIAL ROAD, TO COMMENCE THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.21 CHAINS NORTH TO THE STONE HE FOUND AT THE CORNER TO T. BRYANT'S SHOP
  - 2) 80.41 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 36-18-11
  - 3) 87.00 CHAINS NORTH TO ANGLE STAKE NUMBER 1 TO THE NORTHWESTERLY
- 5) JAMES MEANS, COUNTY SURVEYOR FROM 1865 TO 1867, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGE 57 [PACKET 394 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY P. B. PLUMB AND OTHERS FOR A ROAD FROM THE LAWRENCE AND EMPORIA ROAD EAST ON THE TOWNSHIP LINE TO INTERSECT THE ROAD FROM FOREST HILL TO WATERLOO THAT WAS SURVEYED ON JANUARY 25, 1866, AND ESTABLISHED IN THE COMMISSIONERS JOURNAL ON PAGE 122 ON FEBRUARY 12, 1866, APPARENTLY **FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 1-19-11 ON THE TOWNSHIP LINE ON THIS ROAD SURVEY. **[NOTE: HE HAD MISLABELED THE SECTION CORNERS ON HIS DRAWING – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]**

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE TOWNSHIP LINE TO THE STONE WHERE THE LAWRENCE AND EMPORIA ROAD CROSSES THE NORTH LINE OF TOWNSHIP 19 [RANGE 11] TO COMMENCE THIS ROAD SURVEY
  - 2) THIS ROAD EXTENDS EAST ON THE TOWNSHIP LINE WITH AN ANGLE TO THE SOUTHERLY AROUND BADGER CREEK IN THE NORTHEAST 1/4 OF SECTION 2-19-12 AND THE NORTHWEST 1/4 OF SECTION 1-19-12 AND RETURNS TO THE TOWNSHIP LINE AND CONTINUES EAST ON THE TOWNSHIP LINE TO THE ROAD FROM FOREST HILL TO WATERLOO AT THE TERMINUS OF THIS ROAD SURVEY
- 6) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 49 RECORDED IN SURVEY BOOK "A" ON PAGES 145 & 146 DATED MAY 12 & 13, 1868 FOR A SURVEY OF LAND OWNED BY BISHOP AND OTHERS, BEING SECTION 36-18-10, TO ESTABLISH THE CENTER CORNER AND DIVIDE THE SOUTHEAST QUARTER AND SOUTHWEST QUARTER INTO 40 ACRE LOTS, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 36-18-11 ON THE TOWNSHIP LINE ON THIS SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 319 RODS, 9 LINKS EAST ON THE TOWNSHIP LINE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 36-18-11 ON THE RANGE LINE
- 7) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 10, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 10 DATED FEBRUARY 10-12, 1870 TO ESTABLISH THE CORNER COMMON TO SECTIONS 25-26-35-36 IN TOWNSHIP 18-11, SAID THAT **HE FOUND THE STONE** AT THE CORNER COMMON TO SECTIONS 1, 2, 35 & 36 ON THE TOWNSHIP LINE BETWEEN TOWNSHIPS 18 & 19 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 2,659' NORTH TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 36-18-11
- 8) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN AN **INFORMAL SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 157 DATED MAY 16, 1883 AT THE REQUEST OF SPENCER AND DOYLE TO ESTABLISH THE 1/4 CORNER ON THE NORTH LINE OF SECTION 2-19-11, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 2-19-11 ON THE TOWNSHIP LINE ON THIS **INFORMAL SURVEY**.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 39.86-1/2 CHAINS WEST ON THE TOWNSHIP LINE TO THE STONE HE SET FOR THE NORTH 1/4 CORNER OF SECTION 2-19-11
  - 2) 79.73 CHAINS WEST ON THE TOWNSHIP LINE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 2-19-11
- 9) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 39, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 220 DATED MARCH 10-14, 1902 ORDERED BY CHRISTIAN THRASHER FOR S SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CENTER OF SECTION 4-19-11 AND ALSO THE CORNERS AND BOUNDARIES OF THE NORTH 1/2 OF THE NORTH 1/2 OF THE SOUTHWEST 1/4 OF SAID SECTION 4 AND RUN SUCH LINES AS ARE NECESSARY TO PROPERLY COMPLETE THE SURVEY. THE NORTH AND EAST LINES OF THE SOUTHWEST 1/4 OF SECTION 3-19-11 WILL ALSO BE LOCATED AND ESTABLISHED. **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 2-19-11 ON THE TOWNSHIP LINE ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 16, AND ADDITIONAL INFORMATION IS IN PACKET "M 123" IN MISCELLANEOUS DRAWER NUMBER 5 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 80.08 CHAINS WEST ON THE TOWNSHIP LINE ON TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 2-19-11
  - 2) 159.98 CHAINS WEST ON THE TOWNSHIP LINE TO THE STONE HE FOUND LOOSE IN THE GROUND AT THE NORTHWEST CORNER OF SECTION 3-19-11
  - 3) 200.12 CHAINS WEST ON THE TOWNSHIP LINE TO THE 3" X 12" X 14" STONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 4-19-11
  - 4) 240.15 CHAINS WEST ON THE TOWNSHIP LINE TO THE STONE HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 4-19-11
  - 5) 247.45 CHAINS WEST ON THE TOWNSHIP LINE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF THE WATERWORKS PROPERTY
  - 6) 280.22 CHAINS WEST ON THE TOWNSHIP LINE TO THE CORNER FENCE POST HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 5-19-11
  - 7) 320.12 CHAINS WEST ON THE TOWNSHIP LINE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 5-19-11
- 10) R. W. BALL, COUNTY ENGINEER, IN SURVEY SR #01001 IN THE LARGE SURVEY DRAWER FOR SECTIONS 1-8 IN TOWNSHIP 19-11, DATED APRIL & MAY 1951 FOR A PLAT OF SURVEY OF THE SOUTHWEST 1/4 OF SECTION 1-19-11, SHOWS A **POINT SET IN INTERSECTION OF ROAD EAST AND WEST AND ROAD NORTH AND SOUTH** AT THE NORTHWEST CORNER OF SECTION 1-19-11 ON THE TOWNSHIP LINE. HE DID NOT STATE IF HE FOUND OR SET A MONUMENT AT THIS CORNER ON THIS SURVEY.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,570.04' SOUTH "BY GOVERNMENT NOTES" TO A POINT IN THE WOOD LOT AT JONES AT THE WEST 1/4 CORNER OF SECTION 1-19-11 – NOTE DESCRIBED
- 2) 5,201.04' SOUTH "BY GOVERNMENT NOTES" TO THE CORNER STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 1-19-11
- 3) 2,640' EAST "BY GOVERNMENT NOTES" TO A POINT IN THE CENTERLINE OF THE ROAD AND 1' EAST OF A FENCE NORTH AT THE NORTH 1/4 CORNER OF SECTION 1-19-11 – NOT DESCRIBED
- 4) 5,280' EAST "BY GOVERNMENT NOTES" TO THE NORTHEAST CORNER OF SECTION 1-19-11 AT THE TOWNSHIP CORNER ON THE RANGE LINE – NOT DESCRIBED

CONTINUED ON PAGE 4

- 11) IN A *REPORT OF SURVEY* FOR SURVEY F01004 IN THE SURVEY FILE FOR TOWNSHIP 19-11 WITH NO NAME OR DATE, THE SURVEYOR SAID THAT "HE SET A POINT" FOR THE NORTHWEST CORNER OF SECTION 1-19-11 ON THE TOWNSHIP LINE ON THE PROLONGATION OF THE LINE FROM THE "SECTION CORNER IN PAVEMENT" AT THE SOUTHWEST CORNER OF SECTION 12-19-11 AND THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 1-19-11. THE SURVEY DOES NOT DESCRIBE THE MONUMENT THAT HE SET FOR THE "POINT".
- 12) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 18-11 SHOWS AN **IRON PIN** AT THE "SE CORNER 35-18-11" ON THE TOWNSHIP LINE.
  - 1) 98.3' SE TO A SPIKE IN A TELEPHONE POLE
  - 2) 101.95' TO A SPIKE IN A CATALPA TREE IN THE SCHOOL YARD
  - 3) 96.3' SE TO A SPIKE IN THE TOP OF A NEW CREOSOTED FENCE POST
- 13) IN A BROWN FIELD BOOK LABELED "MISC. 1950-1951" IN THE VAULT IN THE COUNTY ENGINEERS OFFICE FOR A SURVEY FOR JONES & EVANS IN SECTION 1-19-11 ON PAGES 31-33, IT SHOWS A "**MONUMENT**" AT THE NORTHWEST CORNER OF SECTION 1-19-11 ON THE TOWNSHIP LINE. THERE IS NO DESCRIPTION OF THE MONUMENT AT THIS CORNER.
  - 1) 43.0' NE BY EAST TO A NAIL IN A TELEPHONE POLE
  - 2) 51.1' NE TO A NAIL IN A POWER POLE
  - 3) 32.5' NW TO A NAIL IN A TELEPHONE POLE
- 14) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F01005 IN THE SURVEY FILE FOR SECTIONS 1-8 IN TOWNSHIP 19-11 SHOWING THE BOUNDARIES OF A 20.5 ACRE TRACT IN THE NORTHEAST CORNER OF THE WEST 1/2 OF THE NORTHWEST 1/4 OF SECTION 1-19-11 DATED APRIL 9 & 10, 1970, SHOWS ON HIS SURVEY DRAWING A "**MONUMENT**" AT THE NORTHWEST CORNER OF SECTION 1-19-11 ON THE TOWNSHIP LINE. THERE IS NO DESCRIPTION OF THE MONUMENT AND THERE ARE NO TIES ON THE SURVEY.
 

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

  - 1) 1,318' EAST ON THE TOWNSHIP LINE TO THE "MONUMENT" AT THE NORTHEAST CORNER OF THE W1/2 OF THE NW1/4 OF SECTION 1-19-11 – NOT DESCRIBED
- 15) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F01002 IN THE SURVEY FILE FOR SECTIONS 1-8 IN TOWNSHIP 19-11 FOR A 1.97 ACRE TRACT OF THE RINKER SCHOOL PROPERTY IN THE NORTHWEST 1/4 OF SECTION 1-19-11 DATED MAY 12, 1975, SHOWS ON HIS SURVEY DRAWING A "**MONUMENT**" AT THE NORTHWEST CORNER OF SECTION 1-19-11 ON THE TOWNSHIP LINE. THERE IS NO DESCRIPTION OF THE MONUMENT AND THERE ARE NO TIES ON THE SURVEY.
 

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

  - 1) 266' EAST ON THE TOWNSHIP LINE TO THE IRON PIN HE SET FOR THE NORTHEAST CORNER OF THE 1.97 ACRE TRACT
  - 2) 235' SOUTH TO THE IRON PIN HE SET FOR A CORNER OF THE 1.97 ACRE TRACT
- 16) STEVEN S. BROSEMER, L.S. 752, IN A SECTION CORNER REPORT DATED APRIL 30, 1985, FOR PROJECT NUMBER 85031, SURVEY F01003 IN THE SURVEY FILE FOR SECTIONS 1-8 IN TOWNSHIP 19-11 FOR THE SURVEY OF A 15 ACRE TRACT, MORE OR LESS, LOCATED IN THE NORTHEAST QUARTER OF SECTION 1-19-11, AND RECORDED IN VOLUME 415 ON PAGE 411 IN THE REGISTER OF DEEDS OFFICE ON APRIL 17, 1985, SAID THAT HE FOUND AND ACCEPTED A 1/2" REBAR AT 6" DEEP AT THE NORTHWEST CORNER OF SECTION 1-19-11 ON THE TOWNSHIP LINE.
  - 1) 4.0' EAST TO THE TRAVELED WAY OF THE ROAD TO THE NORTH
  - 2) 3.0' NORTH TO THE TRAVELED WAY OF THE ROAD TO THE WEST

HIS TIES ARE CONTINUED ON PAGE 5

- 3) IN THE TRAVELED WAY OF THE ROAD TO THE EAST
  - 4) 56.5' NNE TO THE EAST END OF A 36" CORRUGATED METAL PIPE CULVERT  
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
    - 1) 2,638.05' EAST ON THE TOWNSHIP LINE TO THE 4" X 10" STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 1-19-11, WITH 1/2" REBARS HE SET ON THE NORTH AND SOUTH SIDES AT THE CENTER OF THE STONE, AND A SPIKE HE SET OVER THE CENTER OF THE STONE
    - 2) 5,276.10' EAST ON THE TOWNSHIP LINE TO A 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF SECTION 1-19-11 AT THE TOWNSHIP CORNER ON THE RANGE LINE
    - 3) 7,763.2' EAST ON THE TOWNSHIP LINE TO THE STONE WITH A REBAR BENT OVER THE TOP OF THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 6-19-12
- 17) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED MAY 3, 1989, FOR JOB NUMBER 89041, SAID THAT **HE FOUND THE 1/2" REBAR** AT THE NORTHEAST CORNER OF SECTION 2-19-11 ON THE TOWNSHIP LINE FROM HIS TIES DATED APRIL 1985. **HE REPLACED THIS FOUND 1/2" REBAR WITH A 5/8" REBAR WITH A LYON COUNTY CAP.**
- 1) 53.1' NE TO A PK NAIL & WASHER IN THE WEST "RINKER" SIGN POST
  - 2) 56.6' NNE TO A PUNCH HOLE IN THE TOP OF A 24" X 42" METAL ARCH CULVERT
  - 3) 52.9' NNW TO A PUNCH HOLE IN THE TOP OF A 24" X 42" METAL ARCH CULVERT
  - 4) 3.0' NORTH TO THE CENTERLINE TRAVELED WAY OF THE ROAD EAST-WEST
  - 5) 7.0' EAST TO THE CENTERLINE TRAVELED WAY OF THE ROAD NORTH-SOUTH
- 18) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JANUARY 31, 1997, FOR JOB NUMBER 95024-02, THE GPS SURVEY OF EMPORIA AND LOCAL AREA, SAID THAT **SHE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP AT 9" DEEP IN THE ASPHALT TURNOUT** AT THE NORTHWEST CORNER OF SECTION 1-19-11 ON THE TOWNSHIP LINE. SHE SET CONCRETE NAILS 1.0' WEST AND 1.0' EAST FOR STRADDLES.
- 1) 56.6' NNE TO A PUNCH HOLE IN THE TOP OF A 24" X 42" METAL ARCH CULVERT
  - 2) 52.9' NNW TO A PUNCH HOLE IN THE TOP OF A 24" X 42" METAL ARCH CULVERT
  - 3) 91.50' NE TO THE SOUTHWEST CORNER OF AN ANGLE IRON POST FOR THE "RINKER" SIGN POST
  - 4) 3.0' NORTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 190 EAST—WEST
  - 5) 7.0' EAST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "M" TO THE NORTH
  - 6) STATE PLANE COORDINATES IN U.S. FEET—GROUND LEVEL  
NORTH = 1964280.345                      EAST = 1984715.466
- 19) WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 31, 2001, FOR PROJECT NUMBER 01-59, SETTING COUNTY MONUMENT BOXES OVER SECTION CORNERS IN COUNTY ASPHALT ROADS, **FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP AT 10" BELOW THE SURFACE IN THE ASPHALT TURNOUT** AT THE NORTHWEST CORNER OF SECTION 1-19-11 ON THE TOWNSHIP LINE FROM THE TIES OF RECORD FROM POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, DATED JANUARY 1997 AND STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, DATED 1985 AND 1989. **I SET A 5/8" X 9" REBAR WITH A LYON COUNTY CAP OVER THE FOUND 5/8" REBAR, AND I SET A LYON COUNTY MONUMENT BOX FLUSH WITH THE SURFACE OF THE ASPHALT ROAD APPROACH WEST OF BURLINGAME ROAD** FOR THE NORTHWEST CORNER OF SECTION 1-19-11 ON THE TOWNSHIP LINE.

- 1) 52.9' NNW TO A PUNCH HOLE FOUND IN THE TOP OF A 24" X 42" METAL ARCH CULVERT
  - 2) 124.3' NNW TO THE TOP CENTER OF A TELEPHONE PEDESTAL
  - 3) 91.5' NE TO THE SOUTHWEST CORNER OF AN ANGLE IRON POST FOR THE "RINKER CORNER" SIGN POST
  - 4) 3' NORTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 190 EAST—WEST
  - 5) 7' EAST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "M" TO THE NORTH
- 20) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED SEPTEMBER 21, 2005, FOR PROJECT NUMBER 05-306-02, SURVEY F02001 IN THE SURVEY FILE FOR SECTIONS 1-8 IN TOWNSHIP 19-11 FOR TH NORTH LINE OF A TRACT IN SECTION 2-19-11 FOR FARM & HOME/FLOTT/WHITE, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT WELL** AT THE NORTHEAST CORNER OF SECTION 2-19-11 ON THE TOWNSHIP LINE FROM HIS EXISTING TIES ON FILE IN THE COUNTY ENGINEER'S OFFICE FOR PROJECT 89041 [1989].
- 1) 91.5' NE TO THE SOUTHWEST CORNER OF A POST FOR THE "RINKER" SIGN
  - 2) 56.6' NNE TO A PUNCH HOLE TIN THE TOP OF A 24" METAL ARCH CULVERT
  - 3) 52.9' NNW TO A PUNCH HOLE IN THE TOP OF A 24" METAL ARCH CULVERT
  - 4) 3' NORTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 190 EAST-WEST
  - 5) 7' EAST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "M" TO THE NORTH
- 21) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JANUARY 23, 2008, FOR PROJECT NUMBER 07438-02, SURVEYS F35005 AND F35006 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR THE SURVEY OF A 15.76 ACRE TRACT IN THE NORTHEAST 1/4 OF SECTION 35-18-11 FOR FULLER, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT WELL** AT THE SOUTHEAST CORNER OF SECTION 35-18-11 ON THE TOWNSHIP LINE FROM HIS EXISTING TIES ON FILE IN THE COUNTY ENGINEER'S OFFICE DATED SEPTEMBER 2005.
- 1) 91.5' NE TO THE SOUTHWEST CORNER OF A POST FOR THE "RINKER" SIGN
  - 2) 56.6' NNE TO A PUNCH HOLE IN THE TOP OF A 24" METAL ARCH CULVERT
  - 3) 52.9' NNW TO A PUNCH HOLE IN THE TOP OF A 24" METAL ARCH CULVERT
  - 4) 3.0' NORTH TO THE TRAVELED WAY OF COUNTY ROAD 190 EAST-WEST
  - 5) 7.0' EAST TO THE TRAVELED WAY OF COUNTY ROAD "M" TO THE NORTH
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,654.56' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 35-18-11
  - 2) 3,104.70' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHEAST CORNER OF THE 15.76 ACRE TRACT
  - 3) 3,981.84' NORTH TO THE 1/2" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHEAST CORNER OF THE S1/2 OF THE NE1/4 OF SECTION 35-19-11, AND THE P.O.B. OF THE 15.76 ACRE TRACT
  - 4) 5,309.12' NORTH TO THE 5/8" REBAR HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 35-18-11
- 22) JAMES A. BRULL, L.S. 1475, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 3, 2013 FOR LYON COUNTY BRIDGE REPLACEMENT PROJECT 13-36, THE REPLACEMENT OF TIMBER CULVERT 947.1-516.0 WITH A 30 FOOT ALL STEEL BRIDGE, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT WELL** AT THE NORTHWEST CORNER OF SECTION 1-19-11 ON THE TOWNSHIP LINE FROM THE EXISTING

REFERENCE TIES BY STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, DATED JANUARY 2008 ON FILE AT THE COUNTY ENGINEERS OFFICE.

- 1) 90.55' NE TO THE SOUTHWEST CORNER OF A POST FOR THE "RINKER" SIGN
- 2) 57.7' NNE TO A PUNCH HOLE IN THE TOP/SIDE OF A 24" METAL ARCH CULVERT
- 3) 51.7' NNW TO A PUNCH HOLE IN THE TOP/SIDE OF A 24" METAL ARCH CULVERT
- 4) 3.0' NORTH TO THE TRAVELED WAY OF COUNTY ROAD 190 EAST-WEST
- 5) 6.0' EAST TO THE TRAVELED WAY OF COUNTY ROAD "M" TO THE NORTH

PROJECT PLANS SHOWS THE FOLLOWING INFORMATION:

- 1) THIS SECTION CORNER IS P.O.T. STATION 0+00.00
- 2) 300.04' EAST ON THE SECTION LINE TO THE 5/8" X 1.1' REBAR WITH A LYON COUNTY CAP HE SET AT P.O.T. STATION 3+00.04
- 3) 700.00' EAST ON THE SECTION LINE TO THE 5/8" X 1.1' REBAR WITH A LYON COUNTY CAP HE SET AT P.O.T. STATION 7+00.00
- 4) 1,319.09' EAST ON THE SECTION LINE TO THE 5/8" REBAR HE FOUND AT THE NORTH 1/16<sup>TH</sup> CORNER OF THE NW1/4 OF SECTION 1-19-11 AT P.O.T. STATION 13+19.09
- 5) 2,638.23' EAST ON THE SECTION LINE TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 1-91-11 AT P.O.T. STATION 26+38.23

NORTHWEST CORNER SECTION 01-19-11