

**WEST 1/4 CORNER SECTION 01, TOWNSHIP 19 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 358 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 23" X 14" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 1 & 2-19-11 ON MARCH 18, 1857.  
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 38.94 CHAINS NORTH TO THE 19" X 12" X 6" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 1 & 2-19-11 ON THE TOWNSHIP LINE
  - 2) 40.00 CHAINS SOUTH TO THE 30" X 20" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 1, 2, 11 & 12-19-11
  
- 2) G. M. WALKER, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 32 RECORDED IN SURVEY BOOK "A" ON PAGE 66 DATED JANUARY 10, 1861 TO DIVIDE THE NORTHEAST 1/4 OF SECTION 2-19-11 INTO EAST AND WEST HALVES AND ESTABLISH THE NECESSARY BOUNDS AND CORNERS, SAID THAT **HE FOUND THE STONE EAST 1/4 POST** OF SECTION 2-19-11 ON THIS SURVEY.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 19.94 CHAINS WEST TO THE STONE HE SET FOR THE S1/4/4 POST OF THE NE1/4 OF SECTION 2-19-11
  - 2) 39.88 CHAINS WEST TO THE CENTER POST OF SECTION 2-19-11
  
- 3) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 68 RECORDED IN SURVEY BOOK "A" ON PAGE 168 DATED AUGUST 25 & 26, 1868 FOR A SURVEY OF LAND CONTAINED IN SECTION 1-91-11 FOR LAND OWNED BY MRS. RINKER, TO ESTABLISH THE CENTER CORNER, AND SURVEY 10 ACRES, MORE OR LESS, ON THE NORTHERN BOUNDARY OF THE WEST 1/2 OF THE SOUTHWEST 1/4 OF SAID SECTION 1, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 1-19-11 ON THIS SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 322 RODS, 11 LINKS EAST TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 1-19-11 ON THE RANGE LINE
  
- 4) S. K. McCRARY, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 124, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 205 DATED MAY 15, 1905 FOR L. S. NEWTON FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF 60 ACRES OFF THE EAST SIDE AND 60 ACRES OFF THE WEST SIDE OF EH SOUTHEAST 1/4 OF SECTION 1-19-11 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE IN PLACE** AT THE WEST 1/4 CORNER OF SECTION 1-19-11 ON THIS **PERMANENT SURVEY**, FROM WHICH:
  - 1) A 12" WALNUT TREE BEARS EAST 41 LINKS DISTANCE AND SOUTH 5 LINKS
  - 2) A COFFEE BEAN TREE BEARS NORTHWEST 45 LINKS.

HIS FIELD NOTES ARE IN BOOK 2 ON PAGE 174 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 173" IN MISCELLANEOUS DRAWER NUMBER 1 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE. **NOTE:** SEE THE SURVEY AS HIS NOTES AND DRAWING DO NOT SHOW THE SAME CHAINING NUMBERS – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 19.99 CHAINS EAST TO THE STONE HE FOUND IN PLACE AT THE SOUTHWEST CORNER OF THE E1/2 OF THE NE1/4 OF SECTION 1-19-11, AT 1 LINK WEST OF A BURR OAK TREE [**NOTE:** THIS SHOULD BE NW1/4 – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]
  - 2) 39.98 CHAINS EAST TO THE STONE MARKED "1/4" HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 1-19-11, FROM WHICH A 10" OAK TREE BEARS 5 LINKS EST, AND A 5" OAK TREE BEARS 9 LINKS SOUTH AND 2 LINKS EAST

- 3) 54.98 CHAINS EAST TO THE STONE HE SET FOR THE PERMANENT NORTHEAST CORNER OF THE WEST 60 ACRES OF THE SE1/4 OF SECTION 1-19-11
  - 4) 59.97-3/4 CHAINS EAST TO THE STONE HE SET FOR THE PERMANENT SOUTHEAST CORNER OF THE W1/2 OF THE NE1/4 OF SECTION 1-19-11
  - 5) 64.97 CHAINS EAST TO THE STONE HE SET FOR THE PERMANENT NORTHWEST CORNER OF THE EAST 60 ACRES OF THE SE1/4 OF SECTION 1-19-11
  - 6) 79.96 CHAINS EAST TO THE STONE HE SET FOR THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 1-19-11 ON THE RANGE LINE, ON LINE WITH A HEDGE RUNNING EAST AND A WIRE FENCE RUNNING WEST
- 5) R. W. BALL, COUNTY ENGINEER, IN SURVEY SR #01001 IN THE LARGE SURVEY DRAWER FOR SECTIONS 1-8 IN TOWNSHIP 19-11, DATED APRIL & MAY 1951 FOR A PLAT OF SURVEY OF THE SOUTHWEST 1/4 OF SECTION 1-19-11, SHOWS A **POINT SET IN WOOD LOT ON JONES** FOR THE WEST 1/4 CORNER OF SECTION 1-19-11.  
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,570.04' "BY GOVERNMENT NOTES" TO A POINT HE SET IN THE INTERSECTION OF THE ROADS NORTH-SOUTH-EAST-WEST AT THE NORTHWEST CORNER OF SECTION 1-19-11 ON THE TOWNSHIP LINE
  - 2) 2,642.31' EAST TO A POINT 2' NORTH AND 2' EAST OF AN OLD FENCE CORNER AT THE CENTER CORNER OF SECTION 1-19-11
  - 3) 5,284.62' EAST TO THE POSITION FOR THE EAST 1/4 CORNER OF SECTION 1-19-11 ON THE RANGE LINE, AS DETERMINED BY THE GOVERNMENT NOTES
- 6)) IN A *REPORT OF SURVEY* FOR SURVEY F01004 IN THE SURVEY FILE FOR TOWNSHIP 19-11 WITH NO NAME OR DATE, THE SURVEYOR SAID THAT "HE SET A POINT" FOR THE WEST 1/4 CORNER OF SECTION 1-19-11, BUT DOES NOT DESCRIBE THE MONUMENT THAT HE SET AT THE "POINT".  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) 2,642' EAST TO A "POINT SET" FOR THE CENTER CORNER OF SECTION 1-19-11
- 7) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED SEPTEMBER 21, 2005, FOR PROJECT NUMBER 05-306-02, SURVEY F02001 IN THE SURVEY FILE FOR SECTIONS 1-8 IN TOWNSHIP 19-11 FOR TH NORTH LINE OF A TRACT IN SECTION 2-19-11 FOR FARM & HOME/FLOTT/WHITE, SAID THAT HE DID **NOT** FIND THE STONE AT THE EAST 1/4 CORNER OF SECTION 2-19-11 AS IT FALLS IN CULTIVATION. HE DETERMINED A **THEORETICAL POSITION** FOR THE EAST 1/4 CORNER OF SECTION 2-19-11, BUT HE DID **NOT** MONUMENT THIS POSITION ON THIS SURVEY.
- 1) 2,567.72' NORTH TO THE NORTHWEST CORNER OF SECTION 1-19-11 ON THE RANGE LINE [A 5/8" REBAR IN A WELL]
  - 2) 2,367.61' SOUTH TO THE SOUTHWEST CORNER OF SECTION 1-19-11 [A 1/2" REBAR OVER THE STONE]
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,629.84' WEST TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE SE1/4 OF SECTION 2-19-11
  - 2) 5,269.35' WEST TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE SW1/4 OF SECTION 2-19-11

WEST QUARTER CORNER SECTION 01-19-11