

**WEST 1/4 CORNER SECTION 02, TOWNSHIP 19 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 364 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT THE LOCATION FOR THE 1/4 CORNER BETWEEN SECTIONS 2 & 3-19-11 FALLS IN A CREEK AND **THEY SET A PERMANENT TRIANGULAR POST OF MULBERRY AT 145 LINKS NORTH OF THE 1/4 SECTION POINT BETWEEN SECTIONS 2 & 3**, FROM WHICH:
  - 1) AN ELM TREE 9" IN DIAMETER BEARS N. 81°30' W. AT 75 LINKS DISTANCE
  - 2) A BURR OAK TREE 30" IN DIAMETER BEARS S. 36°30' E. AT 30 LINKS DISTANCE

**THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION FROM THE TRUE 1/4 POINT:**

  - 1) 38.80 CHAINS NORTH TO THE 17" X 17" X 2-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 2 & 3-19-11 ON THE TOWNSHIP LINE
  - 2) 40.00 CHAINS SOUTH TO A 17" X 12" X 5" LIMESTONE SET FOR THE CORNER TO SECTIONS 2, 3, 10 & 11-19-11
  
- 2) KDOT SURVEYORS DETERMINED THAT THE WEST 1/4 CORNER OF SECTION 2-19-11 FALLS IN THE NEOSHO RIVER, AND WAS NOT SET BY THE GLO. THEY SAID THAT THEY COULD FIND NO RECORD OF PREVIOUS SURVEYS THAT ESTABLISHED THE WEST 1/4 CORNER OF SECTION 2-19-11.
  
- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED SEPTEMBER 21, 2005, FOR PROJECT NUMBER 05-306-02, SURVEY F02001 IN THE SURVEY FILE FOR SECTIONS 1-8 IN TOWNSHIP 19-11 FOR TH NORTH LINE OF A TRACT IN SECTION 2-19-11 FOR FARM & HOME/FLOTT/WHITE, SAID THAT HE DETERMINED THAT THE WEST 1/4 CORNER OF SECTION 2-19-11 FALLS IN THE NEOSHO RIVER. HE DETERMINED A **THEORETICAL POSITION** FOR THE WEST 1/4 CORNER OF SECTION 2-19-11 BASED ON ESTABLISHING THE CORNER ON TRUE LINE AND AT THE PRORATED DISTANCE BETWEEN THE NORTHWEST AND SOUTHWEST SECTION CORNERS OF SECTION 2-19-11.
  - 1) 2,650.18' SOUTH TO THE SOUTHWEST CORNER OF SECTION 2-19-11 [A 5/8" REBAR OVER THE STONE]
  - 2) 2,570.67' NORTH TO THE NORTHWEST CORNER OF SECTION 2-19-11 [A 1/2" REBAR OVER THE STONE]

**HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**

  - 1) 2,639.51' EAST TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE SE1/4 OF SECTION 1-19-11
  - 2) 5,269.35' EAST TO THE THEORETICAL POSITION FOR THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 1-19-11
  
- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MAY 24, 2011 FOR PROJECT NUMBER 09015-02, THE FINAL PLAT OF ESU ADDITION TO THE CITY OF EMPORIA IN SECTIONS 3, 10 & 11-19-11, SAID THAT HE DETERMINED A **CALCULATED POSITION** FOR THE EAST 1/4 CORNER OF SECTION 3-19-11 TO BE ON LINE BETWEEN THE SOUTHEAST AND NORTHEAST CORNERS OF SECTION 3-19-11, AND AT THE GLO PRORATION, AS THE TRUE POSITION FOR THE EAST 1/4 CORNER OF SECTION 3-19-11 FALLS IN THE NEOSHO RIVER.
  - 1) 2,570.75' NORTH TO THE LIMESTONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 3-19-11
  - 2) 2,650.26' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE SOUTHEAST CORNER OF SECTION 3-19-11

WEST QUARTER CORNER SECTION 02-19-11