

WEST 1/4 CORNER SECTION 03, TOWNSHIP 19 SOUTH, RANGE 11 EAST

- 1) ON PAGE 370 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A SANDSTONE 21" X 18" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 3 & 4-19-11 ON MARCH 25, 1857. THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.49 CHAINS NORTH TO THE 19" X 15" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 3 & 4-19-11 ON THE TOWNSHIP LINE
 - 2) 40.00 CHAINS SOUTH TO THE 21" X 18" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 3, 4, 9 & 10-19-11

- 2) G. M. WALKER, BRECKENRIDGE COUNTY SURVEYOR FROM 1857 TO 1860, IN SURVEY NUMBER 3 RECORDED IN SURVEY BOOK "A" ON PAGE 3 DATED JANUARY 1, 1858, A **PERMANENT SURVEY** TO ESTABLISH THE CENTER POST OF SECTION 3-19-11 AND TO RUN THE SOUTH LINE OF THE NORTHWEST 1/4 OF SAID SECTION 3, SAID THAT **HE FOUND THE WEST 1/4 STONE POST** OF SECTION 3-19-11 ON THIS **PERMANENT SURVEY**.

- 3) G. M. WALKER, BRECKENRIDGE COUNTY SURVEYOR FROM 1857 TO 1860, IN SURVEY NUMBER 23 RECORDED IN SURVEY BOOK "A" ON PAGE 26 AND DATED FEBRUARY 1859, SAID THAT **HE FOUND THE WEST 1/4 STONE POST** OF SECTION 3-19-11 ON THIS SURVEY.

- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 39, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 220 DATED MARCH 10-14, 1902 ORDERED BY CHRISTIAN THRASHER FOR A SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CENTER CORNER OF SECTION 4-19-11 AND ALSO THE CORNERS AND BOUNDARIES OF THE NORTH 1/2 OF THE NORTH 1/2 OF THE SOUTHWEST 1/4 OF SAID SECTION 4 AND RUN SUCH LINES AS ARE NECESSARY TO PROPERLY COMPLETE THE SURVEY. THE NORTH AND EAST LINES OF THE SOUTHWEST 1/4 OF SECTION 3-19-11 WILL ALSO BE LOCATED AND ESTABLISHED. **HE SET A 14" X 12" X 3" STONE** FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 3-19-11 ON THIS **PERMANENT SURVEY**. HE NOTED THAT THIS STONE IS 38 LINKS SOUTH OF A LINE EXTENDED FROM THE STONE THAT HE SET FOR THE PERMANENT WEST 1/4 CORNER AND THE STONE THAT HE SET FOR THE PERMANENT CENTER 1/4 CORNER OF SECTION 4-19-11. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 16, AND ADDITIONAL INFORMATION IS IN PACKET "M 123" IN MISCELLANEOUS DRAWER NUMBER 5 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE. HE MARKED THE FOLLOWING WITNESS TREES:
 - 1) 18" ELM S. 2° W. AT 92 LINKS
 - 2) 12" HACKBERRY S. 12°45' E. AT 80 LINKS
 - 3) THE STONE IS 38 LINKS SOUTH OF A LINE EXTENDED WESTHIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.80 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 3-19-11
 - 2) 39.30 CHAINS NORTH TO THE STONE FOUND LOOSE IN THE GROUND AT THE NORTHWEST CORNER OF SECTION 3-19-11 ON THE TOWNSHIP LINE

- 5) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 19-11 SHOWS A **PIN AT 10" DEEP** AT THE "W 1/4 CORNER SECTION 3-19-11".
 - 1) 59.9' SOUTH TO A SPIKE & WASHER IN A TRIPLE 30" ELM TREE
 - 2) 78.4' SE TO A SPIKE & WASHER IN A TRIPLE 60" ELM TREE
 - 3) 80.2' SW TO A SPIKE & WASHER IN A TRIPLE 50" ASH TREE

CONTINUE ON PAGE 2

- 6) E. C. GOLDSMITH, COUNTY ENGINEER FROM 1944 TO 1949, IN LARGE SURVEY SR #04002 IN THE SURVEY DRAWER FOR SECTIONS 1-8 IN TOWNSHIP 19-11 DATED AUGUST 10, 1947, SHOWS ON HIS SURVEY DRAWING AN **IRON PIN** AT THE EAST 1/4 CORNER OF SECTION 4-19-11, BUT THERE ARE NO TIES ON THE SURVEY.
- 7) KRETSINGER REFERENCE TIE BOOK 13 ON PAGE 100 SHOWS A **1/2" BAR AT 10" DEEP** AT THE "E1/4 CORNER SECTION 4-19-11" UNDER THE HEADING "KANSAS HIGHWAY COMMISSION SECTION LINE TIES FOR PROJECT 50S-56 F I608 (5)".
 - 1) 59.9' SOUTH TO A SPIKE & WASHER IN A TRIPLE 30" ELM TREE
 - 2) 78.4' SE TO A SPIKE & WASHER IN A TRIPLE 60" ELM TREE
 - 3) 80.2' SW TO A SPIKE & WASHER IN A 50" ASH TREE
- 8) 1963 TIES FROM KDOT FROM PLANS FOR I-35 BY-PASS PROJECT 35-56-I35-2 (1) (127)/50-56-F050-5 (5), ON PAGE 21; SHOWS A **1/2" REBAR AT 10" DEEP** AT THE WEST 1/4 CORNER OF SECTION 3-19-11.
 - 1) 102.9' SOUTH BASELINE TANGENT STATION 475 + 41.4
 - 2) 59.9' SOUTH TO A SPIKE & WASHER IN A 3 @ 30" ELM TREE
 - 3) 78.4' SE TO A SPIKE & WASHER IN A 60" ELM TREE
 - 4) 80.2' SW TO A SPIKE & WASHER IN A 50" ASH TREE

WEST QUARTER CORNER SECTION 03-19-11