

CENTER CORNER SECTION 04, TOWNSHIP 19 SOUTH, RANGE 11 EAST

- 1) W. T. PARKER, SURVEYOR, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 8 & 9 [PACKET 170 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] FOR THE "EMPORIA AND AMERICUS ROAD" SURVEYED SEPTEMBER 11, 1858, AND RECORDED IN THE COMMISSIONER'S JOURNAL ON PAGE 31 ON NOVEMBER 1, 1858, SAID THAT **HE FOUND** THE CENTER CORNER OF SECTION 4-19-11 ON THIS ROAD SURVEY. NO WIDTH IS RECORDED AND BY THE TERRITORIAL LAW IN EFFECT AT THE TIME THE ROAD WOULD BE FORTY FEET WIDE.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS SOUTHEASTERLY TO THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 3-19-11 TO START THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS NORTH TO THE CENTER CORNER OF SECTION 33-18-11 AT A TURN TO THE NORTHWESTERLY TO THE SOUTH LINE OF AMERICUS TO END THIS ROAD SURVEY
- 2) G. M. WALKER, BRECKENRIDGE COUNTY SURVEYOR FROM 1857 TO 1860, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 17 TO 19 FOR THE RESURVEY OF THE "EMPORIA TO AMERICUS ROAD" ORIGINALLY SURVEYED SEPTEMBER 10, 1858 AND ESTABLISHED NOVEMBER 1, 1858, RESURVEYED THE ROAD ON FEBRUARY 15 & 16, 1859 AND IT WAS ESTABLISHED ON FEBRUARY 28, 1859 [PACKET 526 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] ESTABLISHED NOVEMBER 1, 1858, SAID THAT **HE FOUND THE STONE CENTER POST** OF SECTION 4-18-11 ON THIS ROAD RESURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS NORTH TO THE STONE POST HE FOUND AT THE CENTER CORNER OF SECTION 33-18-11 AT A TURN TO THE NORTHWESTERLY
 - 2) THIS ROAD EXTENDS SOUTH ON THE 1/2 SECTION LINE TO THE STONE HE FOUND AT THE SOUTH 1/4 POST OF SECTION 4-19-11 TO COMMENCE THIS ROAD SURVEY
- 3) G. M. WALKER, BRECKENRIDGE COUNTY SURVEYOR FROM 1857 TO 1860, IN SURVEY NUMBER 25 OF THE 2ND TERM, RECORDED IN SURVEY BOOK "A" ON PAGE 27 DATED FEBRUARY 14, 1859, TO ESTABLISH THE CENTER POST OF SECTION 4-19-11, SAID THAT **HE SET A STONE CENTER POST** OF SECTION 4-19-11 ON LINE BETWEEN THE STONE NORTH 1/4 POST AND THE STONE SOUTH 1/4 POST OF SECTION 4 AT 40.00 CHAINS NORTH OF THE STONE SOUTH 1/4 POST OF SECTION 4-19-11 ON THIS SURVEY.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 20.00 CHAINS NORTH TO THE STAKE HE SET FOR THE SOUTHWEST CORNER OF THE N1/2 OF THE NE1/4 OF SECTION 4-19-11
 - 2) 38.94 CHAINS NORTH TO THE FOUND STONE NORTH 1/4 POST OF SECTION 4-19-11 ON THE TOWNSHIP LINE
 - 3) 40.00 CHAINS SOUTH TO THE FOUND STONE SOUTH 1/4 POST OF SEC. 4-19-11
- 4) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 54 RECORDED IN SURVEY BOOK "A" ON PAGE 153 DATED MAY 22, 1868 FOR A SURVEY OF ANN OWEN'S LAND, BEING ALL THAT PART OF THE SOUTHWEST 1/4 OF SECTION 33-18-11, AND ALSO THE EAST 1/2 OF THE NORTHWEST 1/4 OF SECTION 4-19-11, SAID THAT **HE SET A STONE** FOR THE CENTER CORNER OF SECTION 4-19-11 ON LINE WITH THE STONE THAT HE FOUND AT THE NORTH 1/4 CORNER AND THE STONE THAT HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 4-19-11 AT 160 RODS NORTH OF THE SOUTH 1/4 CORNER OF SECTION 4-19-11 ON THIS SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

HIS INFORMATION IS CONTINUED ON PAGE 2

- 1) 160 RODS SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 4-19-11
 - 2) 154 RODS, 4 LINKS NORTH TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 4-19-11 ON THE TOWNSHIP LINE
- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 66 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 266 TO 268 PETITIONED BY WILLIAM HUMPHREYS AND OTHERS FOR A COUNTY ROAD IN SECTION 4-19-11 [PACKET 337 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON MARCH 3, 1880, WAS ESTABLISHED AS A 60 FOOT WIDE ROAD, **EXCEPT** FOR THE FIRST HALF MILE WHICH IS 40 FEET IN WIDTH, ON APRIL 12, 1880, AND WAS RECORDED ON APRIL 21, 1880 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 4-19-11 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS 40 FOOT WIDE ROAD EXTENDS WEST ON THE 1/2 SECTION LINE FOR 2,640' TO THE NORTHWEST CORNER OF THE SW1/4 OF SECTION 4-19-11 TO COMMENCE THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS SOUTH FOR A 60 FOOT WIDE ROAD ON THE 1/2 SECTION LINE FOR 1,980 FEET TO THE CEMETERY GROUND; THEN TURNS EAST FOR 30 FEET; THEN SOUTH FOR 660 FEET TO THE SOUTHEAST CORNER OF SECTION 4-19-11 AT THE TERMINUS OF THIS ROAD SURVEY
- 6) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE LEFT SIDE PAGE 179 DATED MARCH 31, 1880, FOR A COUNTY ROAD IN TOWNSHIP 19-11, APPARENTLY **FOUND THE STONE** AT THE NORTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 4-19-11 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS WEST ON THE 1/2 SECTION LINE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF THE SW1/4 OF SECTION 4-19-11 TO COMMENCE THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS SOUTH ON THE 1/2 SECTION LINE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 4-19-11 TO END THIS ROAD SURVEY
- 7) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A ROAD SURVEY FOR ROAD NUMBER 304 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 166 TO 168 PETITIONED BY D. L. COOK AND OTHERS TO **VACATE** A COUNTY ROAD IN TOWNSHIP 19-11 [PACKET 531 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE] THAT HE SURVEYED ON FEBRUARY 24, 1885, WAS **VACATED** ON JULY 14, 1885 WITH THE PRINCIPAL PETITIONER TO PAY ALL COSTS AS NOTED BY JOHN L. BUTLER, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JANUARY 25, 1886 BY ROLAND LAKIN, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE CENTER CORNER OF SECTION 4-19-11 TO END THE ROAD **VACATED** ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS **VACATED** ROAD EXTENDS SOUTHEASTERLY TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 3-19-11 TO BEGIN THE ROAD **VACATED** ON THIS ROAD SURVEY
- 8) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 105, A ROAD SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 105 DATED JUNE 2, 1885 FOR J. P. SIEVER, PRINCIPLE PETITIONER FOR A ROAD IN SECTION 4-19-11, SAID THAT **HE FOUND THE STONE** AT THE CENTER CORNER OF SECTION 4-19-11 TO BEGIN THIS ROAD SURVEY.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS EAST ON THE 1/2 SECTION LINE FOR 1,320 FEET TO AN ANGLE STONE HE SET ON THIS ROAD SURVEY

- 9) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 39, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 220 DATED MARCH 10-14, 1902 ORDERED BY CHRISTIAN THRASHER FOR S SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CENTER OF SECTION 4-19-11 AND ALSO THE CORNERS AND BOUNDARIES OF THE NORTH 1/2 OF THE NORTH 1/2 OF THE SOUTHWEST 1/4 OF SAID SECTION 4 AND RUN SUCH LINES AS ARE NECESSARY TO PROPERLY COMPLETE THE SURVEY. THE NORTH AND EAST LINES OF THE SOUTHWEST 1/4 OF SECTION 3-19-11 WILL ALSO BE LOCATED AND ESTABLISHED. **HE SET AN 18" X 12" X 4" STONE** FOR THE PERMANENT CENTER 1/4 CORNER OF SECTION 4-19-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 16, AND ADDITIONAL INFORMATION IS IN PACKET "M 123" IN MISCELLANEOUS DRAWER NUMBER 5 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 10.04-1/2 CHAINS SOUTH TO THE 16" X 12" X 3" STONE HE SET FOR THE PERMANENT SOUTHEAST CORNER OF THE N1/2 OF THE N1/2 OF THE SW1/4 OF SECTION 4-19-11
- 2) 40.18 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 4-19-11
- 3) 20.10 CHAINS NORTH TO THE STONE HE FOUND AT THE 1/8TH CORNER ON THE WEST SIDE OF THE NE1/4 OF SECTION 4-19-11
- 4) 39.18 CHAINS NORTH TO THE 3" X 12" X 14" STONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 4-19-11 ON THE TOWNSHIP LINE
- 5) 10.02-1/4 CHAINS WEST TO THE 12" X 6" X 4" PERMANENT PROPERTY STONE HE SET ON THIS SURVEY
- 6) 20.06-1/2 CHAINS WEST TO THE 12" X 10" X 2" STONE HE SET FOR THE PERMANENT 1/8TH CORNER ON THE NORTH SIDE OF THE SW1/4 OF SEC. 4-19-11
- 7) 40.13 CHAINS WEST TO THE 6" X 9" X 15" STONE HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 4-19-11

- 10) COMMISSIONER'S ROAD JOURNAL BOOK "A", PAGE 113
ON JUNE 11, 1930 A PETITION SIGNED BY W. A. WILLIS AND OTHERS FOR THE **VACATION** OF A ROAD IN TOWNSHIP 19-11 WAS PRESENTED TO THE BOARD OF COUNTY COMMISSIONERS. THE ROAD WAS VIEWED ON AUGUST 8, 1930, AND THE FINAL ORDER WAS ISSUED ON AUGUST 8, 1930 THAT THE ROAD BE **VACATED** AS PETITIONED FOR:

- 1) BEGINNING AT A POINT 1,280 FEET NORTH OF THE CENTER OF SECTION 4-19-11, AND VACATE THE ROAD AS NOW LAID OUT BETWEEN THE NORTHWEST QUARTER AND THE NORTHEAST QUARTER OF SAID SECTION 4 FROM SAID POINT OF BEGINNING TO THE NORTH LINE OF SAID SECTION 4

- 11) O. D. HENRY, COUNTY SURVEYOR, IN A ROAD SURVEY FOR ROAD NUMBER 738 RECORDED IN ROAD RECORD BOOK "E" ON PAGE 97 PETITIONED BY W. A. WILLIS AND OTHERS FOR THE **VACATION** OF A ROAD IN TOWNSHIP 19-11 THAT WAS VIEWED BY THE COUNTY COMMISSIONERS AND THE COUNTY SURVEYOR ON AUGUST 8, 1930 AND THE VIEWERS RECOMMENDED THAT THE ROAD SHOULD BE **VACATED**. HIS SURVEY DRAWING SHOWED THAT THE ROAD VACATED WAS THE ROAD NORTH OF THE NEOSHO RIVER, AND WAS RECORDED ON APRIL 3, 1931 BY O. D. HENRY, COUNTY SURVEYOR.

THE FOLLOWING ROAD WAS VACATED:

BEGINNING AT A POINT 1,028 FEET NORTH OF THE CENTER OF SECTION 4-19-11 AND VACATE THE ROAD AS NOW LAID OUT BETWEEN THE NORTHWEST QUARTER

AND THE NORTHEAST QUARTER OF SAID SECTION 4 FROM SAID POINT OF BEGINNING TO THE NORTH LINE OF SAID SECTION 4-19-11

- 12) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 19-11 SHOWS A **STONE** AT THE "C1/4 CORNER SECTION 04-19-11".
 - 1) 31.7' NE TO AN IRON PIN
 - 2) 31.7' NW TO A SPIKE IN A POWER POLE
 - 3) 44.8' SW TO A REBAR AT THE EAST SIDE OF A POWER POLE
 - 4) 22.0' NE TO A SPIKE & WASHER IN A GUY POLE
 - 5) 46.4' SW TO A SPIKE & WASHER IN TELEPHONE POLE
 - 6) 32.8' NW TO A SPIKE & WASHER IN A TELEPHONE POLE

- 13) KRETSINGER REFERENCE TIE BOOK 13 ON PAGE 100 SHOWS A **STONE** AT THE CENTER CORNER OF SECTION 4-19-11 UNDER THE HEADING "KANSAS HIGHWAY COMMISSION SECTION LINE TIES FOR PROJECT 50S-56 F I608 (5)" UNDER "CENTER CORNER SECTION 04-19-11".
 - 1) 22.0' NE TO A SPIKE & WASHER IN A GUY POLE
 - 2) 46.4' SW TO A SPIKE & WASHER IN A TELEPHONE POLE
 - 3) 32.8' NW TO A SPIKE & WASHER IN TELEPHONE POLE

- 14) LARGE SURVEY SR #04005 IN THE SURVEY DRAWER FOR SECTIONS 1-8 IN TOWNSHIP 19-11 FOR THE J. E. ARNDT PROPERTY IN THE NORTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 4 WITH NO NAME OR DATE SHOWS ON THE SURVEY DRAWING THEY **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 4-19-11.

THE SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

 - 1) 1,323.46' WEST TO THE IRON PIN AT THE NORTH 1/16TH CORNER OF THE SW1/4 OF SECTION 4-19-11
 - 2) 2,646.93' WEST TO THE IRON PIN AT THE NORTHWEST CORNER OF THE SW1/4 OF SECTION 4-19-11
 - 3) 1,325.2' SOUTH TO THE IRON PIN AT THE EAST 1/16TH CORNER OF THE SW1/4 OF SECTION 4-19-11
 - 4) 2,640.5' SOUTH TO THE IRON PIN AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 4-19-11

- 15) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN LARGE SURVEY SR #04006 IN THE SURVEY DRAWER FOR SECTIONS 1-8 IN TOWNSHIP 19-11 FOR A PARTIAL SUBDIVISION OF THE SOUTHWEST 1/4 OF THE NORTHEAST 1/4 OF SECTION 4-19-11, BUT NOT DATED, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 4-19-11.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

 - 1) 1,325.20' SOUTH TO THE IRON PIN AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 4-19-11

- 16) E. C. GOLDSMITH, COUNTY ENGINEER FROM 1944 TO 1949, IN LARGE SURVEY SR #04002 IN THE SURVEY DRAWER FOR SECTIONS 1-8 IN TOWNSHIP 19-11, DATED AUGUST 10, 1947, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE** AT THE CENTER CORNER OF SECTION 4-19-11.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

 - 1) 2,651.88' SOUTH TO THE IRON PIN AT THE SOUTH 1/4 CORNER OF SEC. 4-19-11

- 17) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F04034 IN THE SURVEY FILE FOR SECTIONS 1-8 IN TOWNSHIP 19-11 SHOWING THE RESULTS OF A SURVEY OF THE WEST 330 FEET OF THE SOUTH 1/2 OF THE SOUTH 1/2 OF THE NORTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 4-19-11 DATED

NOVEMBER 2, 1959 SHOWS ON HIS SURVEY DRAWING A "MONUMENT" AT THE NORTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 4-19-11. THERE IS NO DESCRIPTION OF THE MONUMENT ON THE SURVEY.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,322.46' WEST TO THE "MONUMENT" AT THE NORTH 1/16TH CORNER OF THE SW1/4 OF SECTION 4-19-11 – NOT DESCRIBED
- 2) 2,646.92' WEST TO THE "MONUMENT" AT THE NORTHWEST CORNER OF THE SW1/4 OF SECTION 4-19-11 – NOT DESCRIBED
- 3) 1,325.2' SOUTH TO THE "MONUMENT" AT THE EAST 1/16TH CORNER OF THE SW1/4 OF SECTION 4-19-11 – NOT DESCRIBED
- 4) 2,650.4' SOUTH TO THE "MONUMENT" AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 4-19-11 – NOT DESCRIBED

- 18) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F04031 IN THE SURVEY FILE FOR SECTIONS 1-8 IN TOWNSHIP 19-11 FOR THE SURVEY OF A 1 ACRE TRACT IN THE NORTHEAST 1/4 OF SECTION 4-19-11 DATED SEPTEMBER 26, 1962, SHOWS ON HIS SURVEY DRAWING A "MONUMENT" AT THE CENTER CORNER OF SECTION 4-19-11. THERE IS NO DESCRIPTION OF THE MONUMENT ON THE SURVEY.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 545' NORTH TO THE "MONUMENT" HE SET FOR THE SOUTHWEST CORNER OF THE 1 ACRE TRACT – NOT DESCRIBED
- 2) 620' NORTH TO THE "MONUMENT" HE SET FOR THE NORTHWEST CORNER OF THE 1 ACRE TRACT – NOT DESCRIBED

- 19) 1963 TIES FROM KDOT FROM PLANS FOR I-35 BY-PASS PROJECT 35-56-I35-2 (1) (127)/50-56-F050-5 (5), PAGE 20, AND SHOWS A 4" X 12" LIMESTONE AT THE CENTER CORNER OF SECTION 4-19-11.

- 1) 100.1' SOUTH OF CENTERLINE STATION 450 + 92.8
- 2) 22.0' NE TO A SPIKE & WASHER A IN GUY POLE
- 3) 46.4' SW TO A SPIKE & WASHER IN A TELEPHONE POLE
- 4) 32.8' NW TO A SPIKE & WASHER IN A TELEPHONE POLE

- 20) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN LARGE SURVEY SR #04007 IN THE SURVEY DRAWER FOR SECTIONS 1-8 IN TOWNSHIP 19-11 DATED DECEMBER 29, 1964, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND A STONE** AT THE NORTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 4-19-11.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,325.2' SOUTH TO THE IRON PIN AT THE SOUTHEAST CORNER OF THE NE1/4 OF THE SE1/4 OF SECTION 4-19-11

- 21) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED APRIL 17, 1992, FOR JOB NUMBER 92180-03, FOR A SURVEY OF THE FOUR SEASONS COMPLEX, SAID THAT **HE FOUND A 5/8" REBAR IN A WATER VALVE BOX MARKED "SURVEY PIN"** AT THE CENTER CORNER OF SECTION 4-19-11.

- 1) 59.7' NW TO THE SOUTHEAST CORNER OF A WINGWALL
- 2) 60.0' NE TO THE SOUTHWEST CORNER OF A WINGWALL
- 3) 79.5' SSW TO THE TOP FIRE OF A HYDRANT
- 4) IN THE CENTERLINE TRAVELED WAY OF THE ROAD NORTH-SOUTH-WEST

- 22) POLLY A. JONES, L.S 1130, IN SURVEY F04041 IN THE SURVEY FILE FOR SECTIONS 1-8 IN TOWNSHIP 19-11 FOR THE SURVEY OF A 4.7 ACRE TRACT IN THE NORTHEAST 1/4 OF SECTION 4-19-11 FOR PROJECT NUMBER 94361-14 DATED DECEMBER 16, 1994, SHOWS ON HER SURVEY DRAWING THAT **SHE FOUND A 5/8" REBAR** AT THE

CENTER CORNER OF SECTION 4-19-11. HER TIES ARE MISSING FROM THE SURVEY TIE FILES.

HER SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 621.6' NORTH TO THE CONCRETE NAIL SHE SET FOR THE SOUTHWEST CORNER OF THE 4.7 ACRE TRACT
 - 2) 726.0' NORTH TO A CONCRETE NAIL SHE SET FOR THE P.O.B. OF THE 4.7 ACRE TRACT
 - 3) 2,569.12' NORTH TO THE THEORETICAL POSITION FOR THE NORTH 1/4 CORNER OF SECTION 4-19-11 ON THE TOWNSHIP LINE
- 23) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED AUGUST 5, 2011 FOR PROJECT NUMBER 11110-02, A SURVEY OF LOT 8 IN BLOCK 11 I COUNTRY CLUB HEIGHTS ADDITION TO THE CITY OF EMPORIA FOR TOM STEBBINS, SAID THAT **HE FOUND THE 5/8" REBAR IN A WATER VALVE BOX** AT THE CENTER CORNER OF SECTION 4-19-11 FROM HIS EXISTING REFERENCE TIES ON FILE AT THE COUNTY ENGINEER'S OFFICE. HE NOTED THAT HE FOUND THIS REBAR IN A WATER VALVE BOX MARKED "SURVEY PIN" IN 1992.
- 1) 34.45' NW TO THE SOUTHWEST CORNER OF AN INLET
 - 2) 32.3' NE TO THE SOUTHEAST CORNER OF AN INLET
 - 3) 52.75' NW TO A SPIKE & WASHER IN A UTILITY POLE
 - 4) 79.35' SSW TO THE TOP OF A FIRE HYDRANT
 - 5) IN THE CENTERLINE TRAVELED WAY OF THE ASPHALT ROAD NORTH-SOUTH [LINCOLN STREET]

CENTER QUARTER CORNER SECTION 04-19-11