

NORTH 1/4 CORNER SECTION 04, TOWNSHIP 19 SOUTH, RANGE 11 EAST

- 1) ON PAGE 67 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A POST** FOR THE NORTH 1/4 CORNER OF SECTION 4-19-11 ON THE TOWNSHIP LINE ON DECEMBER 9, 1856, FROM WHICH:
 - 1) A BURR OAK TREE 10" IN DIAMETER BEARS S. 45° W. AT 26 LINKS DISTANCE
 - 2) A HICKORY TREE 9" IN DIAMETER BEARS N. 36-1/4° W. AT 38 LINKS DISTANCE

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

 - 1) 40.00 CHAINS WEST ON THE TOWNSHIP LINE TO THE 21" X 13" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 4 & 5-19-11
 - 2) 40.00 CHAINS EAST ON THE TOWNSHIP LINE TO THE 19" X 15" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 3 & 4-9-11

- 2) G. M. WALKER, BRECKENRIDGE COUNTY SURVEYOR FROM 1857 TO 1860, IN SURVEY NUMBER 2 RECORDED IN SURVEY BOOK "A" ON PAGE 3, A **PERMANENT SURVEY** DATED DECEMBER 31, 1857 TO ESTABLISH THE CENTER POST OF SECTION 33-18-11 AND ALSO THE SOUTHWEST AND SOUTHEAST CORNERS OF THE NORTH 1/2 OF THE SOUTHEAST 1/4 OF SAID SECTION 33-18-11, SAID THAT **HE FOUND THE SOUTH 1/4 POST** OF SECTION 33-18-11 ON THE TOWNSHIP LINE ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

 - 1) 20.17 CHAINS NORTH TO THE STONE POST HE SET FOR THE PERMANENT SOUTHWEST CORNER OF THE N1/2 OF THE SE1/4 OF SECTION 33-18-11
 - 2) 40.34 CHAINS NORTH TO THE STONE POST HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 33-18-11
 - 3) 80.68 CHAINS NORTH TO THE FOUND NORTH STONE 1/4 POST OF SEC. 33-18-11

- 3) W. T. PARKER, SURVEYOR, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 8 & 9 [PACKET 170 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] FOR THE "EMPORIA AND AMERICUS ROAD" SURVEYED SEPTEMBER 11, 1858, AND RECORDED IN THE COMMISSIONER'S JOURNAL ON PAGE 31 ON NOVEMBER 1, 1858, APPARENTLY **FOUND** THE NORTH 1/4 CORNER OF SECTION 4-19-11 ON THE TOWNSHIP LINE ON THIS ROAD SURVEY. NO WIDTH IS RECORDED AND BY THE TERRITORIAL LAW IN EFFECT AT THE TIME THE ROAD WOULD BE FORTY FEET WIDE.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

 - 1) THIS ROAD EXTENDS SOUTH TO THE CENTER CORNER OF SECTION 4-19-11 AT A TURN TO THE SOUTHEASTERLY TO THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 3-19-11 TO START THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS NORTH TO THE CENTER CORNER OF SECTION 33-18-11 AT A TURN TO THE NORTHWESTERLY TO THE SOUTH LINE OF AMERICUS TO THE TERMINUS OF THIS ROAD SURVEY

- 4) G. M. WALKER, BRECKENRIDGE COUNTY SURVEYOR FROM 1857 TO 1860, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 17 TO 19 FOR THE RESURVEY OF THE "EMPORIA TO AMERICUS ROAD" ORIGINALLY SURVEYED SEPTEMBER 10, 1858 AND ESTABLISHED NOVEMBER 1, 1858, RESURVEYED THE ROAD ON FEBRUARY 15 & 16, 1859 AND IT WAS ESTABLISHED ON FEBRUARY 28, 1859 [PACKET 526 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] ESTABLISHED NOVEMBER 1, 1858, SAID THAT **HE FOUND THE POST** AT THE NORTH 1/4 OF SECTION 4-19-11 ON THE TOWNSHIP LINE ON THIS ROAD RESURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

 - 1) THIS ROAD EXTENDS NORTH TO THE STONE POST HE FOUND AT THE CENTER CORNER OF SECTION 33-18-11 AT A TURN TO THE NORTHWESTERLY

HIS INFORMATION IS CONTINUED ON PAGE 2

- 2) THIS ROAD EXTENDS SOUTH ON THE 1/2 SECTION LINE TO THE STONE HE FOUND AT THE SOUTH 1/4 POST OF SECTION 4-19-11 TO COMMENCE THIS ROAD SURVEY
- 5) G. M. WALKER, BRECKENRIDGE COUNTY SURVEYOR FROM 1857 TO 1860, IN SURVEY NUMBER 25 OF THE 2ND TERM, RECORDED IN SURVEY BOOK "A" ON PAGE 27 DATED FEBRUARY 14, 1859, TO ESTABLISH THE CENTER POST OF SECTION 4-19-11, SAID THAT **HE FOUND THE NORTH 1/4 POST** OF SECTION 4-19-11 ON THE TOWNSHIP LINE ON THIS SURVEY. HE MARKED THE FOLLOWING WITNESS TREES:
- 1) A 30" DIAMETER BURR OAK S. 12-1/2° W. 42 LINKS
 - 2) AN 8" DIAMETER BUR OAK S. 34° W. 27 LINKS
 - 3) A 10" DIAMETER HICKORY N. 49° W. 39 LINKS
- HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
- 1) 18.94 CHAINS SOUTH TO THE STAKE HE SET FOR THE SOUTHWEST CORNER OF THE N1/2 OF THE NE1/4 OF SECTION 4-19-11
 - 2) 38.94 CHAINS SOUTH TO THE STONE HE SET FOR THE CENTER POST OF SECTION 4-19-11
 - 3) 78.94 CHAINS SOUTH TO THE FOUND STONE SOUTH 1/4 POST OF SEC. 4-19-11
- 6) G. M. WALKER, BRECKENRIDGE COUNTY SURVEYOR FROM 1857 TO 1860, IN A ROAD SURVEY ON REVIEW FROM THE ORIGINAL SURVEY OF SEPTEMBER 10, 1858, AND ESTABLISHED NOVEMBER 1, 1858, RECORDED IN SURVEY BOOK "A" ON PAGES 26, 27 & 28 DATED FEBRUARY 15, 1859 FOR THE COUNTY ROAD FROM EMPORIA TO AMERICUS, SAID THAT **HE FOUND THE NORTH 1/4 POST** OF SECTION 4-19-11 ON THE TOWNSHIP LINE ON THIS ROAD SURVEY.
- HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
- 1) 78.94 CHAINS SOUTH TO THE FOUND STONE 1/4 POST OF SECTION 4-19-11
- 7) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 54 RECORDED IN SURVEY BOOK "A" ON PAGE 153 DATED MAY 22, 1868 FOR A SURVEY OF ANN OWEN'S LAND, BEING ALL THAT PART OF THE SOUTHWEST 1/4 OF SECTION 33-18-11, AND ALSO THE EAST 1/2 OF THE NORTHWEST 1/4 OF SECTION 4-19-11, SAID THAT **HE FOUND THE NORTH 1/4 CORNER** OF SECTION 4-19-11 ON THE TOWNSHIP LINE ON THIS SURVEY.
- HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) 80 RODS WEST ON THE TOWNSHIP LINE TO THE STONE HE SET FOR THE NORTH 1/2/4 CORNER OF THE NW1/4 OF SECTION 4-19-11
 - 2) 160 RODS WEST ON THE TOWNSHIP LINE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 4-19-11
 - 3) 154 RODS, 4 LINKS SOUTH TO THE STONE HE SET FOR THE CENTER CORNER OF SECTION 4-19-11
 - 4) 314 RODS, 4 LINKS SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 4-19-11
- 8) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 39, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 220 DATED MARCH 10-14, 1902 ORDERED BY CHRISTIAN THRASHER FOR S SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CENTER OF SECTION 4-19-11 AND ALSO THE CORNERS AND BOUNDARIES OF THE NORTH 1/2 OF THE NORTH 1/2 OF THE SOUTHWEST 1/4 OF SAID SECTION 4-19-11 AND RUN SUCH LINES AS ARE NECESSARY TO PROPERLY COMPLETE THE SURVEY. THE NORTH AND EAST LINES OF THE SOUTHWEST 1/4 OF SECTION 3-19-11 WILL ALSO BE LOCATED AND ESTABLISHED. **HE SET A 14" X 12" X 3" LIMESTONE** FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 4-19-11 ON THE TOWNSHIP LINE ON THIS **PERMANENT SURVEY**. HE LOCATED THIS CORNER BY THE DECAYED STUMPS OF THE OLD WITNESS TREES; THE OAK TREE AND HACKBERRY TREE

WERE FOUND. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 16, AND ADDITIONAL INFORMATION IS IN PACKET "M 123" IN MISCELLANEOUS DRAWER NUMBER 5 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE. HE BLAZED NEW WITNESS TREES AS FOLLOWS:

- 1) A 24" ELM IS S. 36° E. AT 59 LINKS DISTANCE
- 2) A 6" HACKBERRY IS S. 86° W. AT 37 LINKS
- 3) A DOUBLE HACKBERRY IS N. 11°30' W. AT 34 LINKS

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 40.03 CHAINS WEST ON THE TOWNSHIP LINE TO THE STONE HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 4-19-11
 - 2) 80.00 CHAINS WEST ON THE TOWNSHIP LINE TO A CORNER FENCE POST HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 5-19-11
 - 3) 120.00 CHAINS WEST ON THE TOWNSHIP LINE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 5-19-11
 - 4) 40.14 CHAINS EAST ON THE TOWNSHIP LINE TO THE STONE HE FOUND LOOSE IN THE GROUND AT THE NORTHWEST CORNER OF SECTION 3-19-11
 - 5) 120.04 CHAINS EAST ON THE TOWNSHIP LINE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 2-19-11
 - 6) 200.12 CHAINS EAST ON THE TOWNSHIP LINE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 2-19-11
 - 7) 19.08 CHAINS SOUTH TO THE STONE HE FOUND AT THE WEST 1/8TH CORNER OF THE NE1/4 OF SECTION 4-19-11 THAT WAS 2-1/2' WEST OF LINE
 - 8) 39.18 CHAINS SOUTH TO THE 4" X 12" X 18" STONE HE SET FOR THE PERMANENT SOUTHEAST CORNER OF THE N1/2 OF THE N1/2 OF THE SW1/4 OF SECTION 4-19-11
 - 9) 49.22-1/2 CHAINS SOUTH TO A 3" X 12" X 16" PERMANENT PROPERTY STONE HE SET ON THIS SURVEY
 - 10) 79.36 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 4-19-11
- 9) COMMISSIONER'S ROAD JOURNAL BOOK "A", PAGE 113
ON JUNE 11, 1930 A PETITION SIGNED BY W. A. WILLIS AND OTHERS FOR THE VACATION OF A ROAD IN TOWNSHIP 19-11 WAS PRESENTED TO THE BOARD OF COUNTY COMMISSIONERS. THE ROAD WAS VIEWED ON AUGUST 8, 1930, AND THE FINAL ORDER WAS ISSUED ON AUGUST 8, 1930 THAT THE ROAD BE VACATED AS PETITIONED FOR:
- 1) BEGINNING AT A POINT 1,280 FEET NORTH OF THE CENTER OF SECTION 4-19-11, AND VACATE THE ROAD AS NOW LAID OUT BETWEEN THE NORTHWEST QUARTER AND THE NORTHEAST QUARTER OF SAID SECTION 4 FROM SAID POINT OF BEGINNING TO THE NORTH LINE OF SAID SECTION 4
- 10) O. D. HENRY, COUNTY SURVEYOR, IN A ROAD SURVEY FOR ROAD NUMBER 738 RECORDED IN ROAD RECORD BOOK "E" ON PAGE 97 PETITIONED BY W. A. WILLIS AND OTHERS FOR THE VACATION OF A ROAD IN TOWNSHIP 19-11 THAT WAS VIEWED BY THE COUNTY COMMISSIONERS AND THE COUNTY SURVEYOR ON AUGUST 8, 1930 AND THE VIEWERS RECOMMENDED THAT THE ROAD SHOULD BE VACATED. HIS SURVEY DRAWING SHOWED THAT THE ROAD VACATED WAS THE ROAD NORTH OF THE NEOSHO RIVER, AND WAS RECORDED ON APRIL 3, 1931 BY O. D. HENRY, COUNTY SURVEYOR.
THE FOLLOWING ROAD WAS VACATED:
BEGINNING AT A POINT 1,028 FEET NORTH OF THE CENTER OF SECTION 4-19-11 AND VACATE THE ROAD AS NOW LAID OUT BETWEEN THE NORTHWEST QUARTER AND THE NORTHEAST QUARTER OF SAID SECTION 4 FROM SAID POINT OF BEGINNING TO THE NORTH LINE OF SAID SECTION 4-19-11

CONTINUED ON PAGE 4

- 11) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN SECTION CORNER REPORTS DATED DECEMBER 6, 1994 FOR JOB NUMBER 94361-14, FOR SURVEY F04041 IN THE SURVEY FILE FOR SECTIONS 1-8 IN TOWNSHIP 19-11 FOR A 4.7 ACRE TRACT IN THE NORTHEAST 1/4 OF SECTION 4-19-11, SAID THAT SHE DETERMINED THAT THE NORTH 1/4 CORNER OF SECTION 4-19-11 ON THE TOWNSHIP LINE WAS **LOST**. THE **TRUE POSITION** WAS DETERMINED TO BE ON TRUE LINE BETWEEN THE NORTHWEST AND NORTHEAST CORNERS OF SECTION 4-19-11 ON THE TOWNSHIP LINE AND AT THE PRORATED DISTANCE OF ALVA J. SMITH'S PERMANENT SURVEY, AND THAT THIS **TRUE POSITION** FALLS IN THE NEOSHO RIVER. **SHE SET A 1/2" X 24" REBAR WITH HER "LS 1130" CAP FOR A WITNESS CORNER AT 30.0' EAST OF THE TRUE POSITION ON THE EAST-WEST TOWNSHIP LINE.** THE FOLLOWING TIES ARE TO THE **WITNESS CORNER**:
- 1) 16.4' NNE TO A 1/2" REBAR SET FOR A REFERENCE
 - 2) 20.3' SSE TO A 1/2" REBAR SET FOR A REFERENCE
 - 3) 57.5' NORTH TO A LINE OF POWER POLES EAST-WEST
 - 4) 9.9' WEST TO A NAIL & SHINER IN A 4" HACKBERRY TREE
- HER SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION FROM THE TRUE POSITION FOR THE NORTH 1/4 CORNER:**
- 1) 2,639.01' WEST ON THE TOWNSHIP LINE TO THE 5/8" REBAR SHE FOUND AT THE NORTHWEST CORNER OF SECTION 4-19-11
 - 2) 30.00' EAST ON THE TOWNSHIP LINE TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE SET FOR A **WITNESS CORNER**
 - 3) 2,646.26' EAST ON THE TOWNSHIP LINE TO THE 1" REBAR SHE FOUND AT THE NORTHEAST CORNER OF SECTION 4-19-11
 - 4) 1,843.12' SOUTH TO THE CONCRETE NAIL SHE SET FOR THE P.O.B. OF THE 4.7 ACRE TRACT
 - 5) 1,947.52' SOUTH TO THE CONCRETE NAIL SHE SET FOR THE SOUTHWEST CORNER OF THE 4.7 ACRE TRACT
 - 6) 2,569.12' SOUTH TO THE 5/8" REBAR SHE FOUND AT THE CENTER CORNER OF SECTION 4-19-11

NORTH QUARTER CORNER 04-19-11