

**NORTH 1/16TH CORNER SOUTHWEST QUARTER OF SECTION 04, TOWNSHIP 19 SOUTH,
RANGE 11 EAST**

- 1) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 54 RECORDED IN SURVEY BOOK "A" ON PAGE 153 DATED MAY 22, 1868 FOR A SURVEY OF ANN OWEN'S LAND, BEING ALL THAT PART OF THE SOUTHWEST 1/4 OF SECTION 33-18-11, AND ALSO THE EAST 1/2 OF THE NORTHWEST 1/4 OF SECTION 4-19-11, SAID THAT **HE SET A STONE** FOR THE 1/2/4 CORNER ON THE SOUTH SIDE OF THE NORTHWEST 1/4 OF SECTION 4 EQUIDISTANT BETWEEN THE STONE HE FOUND AT THE WEST 1/4 CORNER AND THE STONE HE SET FOR THE CENTER OF SECTION 4 ON THIS SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING DISTANCES:

- 1) 80 RODS WEST TO THE STONE FOUND AT THE WEST 1/4 CORNER OF SECTION 4\
 - 2) 80 RODS EAST TO THE STONE SET FOR THE CENTER OF SECTION 4
- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 39, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 220 DATED MARCH 10-14, 1902 ORDERED BY CHRISTIAN THRASHER FOR S SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CENTER OF SECTION 4-19-11 AND ALSO THE CORNERS AND BOUNDARIES OF THE NORTH 1/2 OF THE NORTH 1/2 OF THE SOUTHWEST 1/4 OF SAID SECTION 4 AND RUN SUCH LINES AS ARE NECESSARY TO PROPERLY COMPLETE THE SURVEY. THE NORTH AND EAST LINES OF THE SOUTHWEST 1/4 OF SECTION 3-19-11 WILL ALSO BE LOCATED AND ESTABLISHED. **HE SET A 12" X 10" X 2" STONE** FOR THE PERMANENT 1/8TH CORNER ON THE NORTH SIDE OF THE SOUTHWEST 1/4 OF SECTION 4 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE SET FOR THE PERMANENT WEST 1/4 CORNER AND THE STONE THAT HE SET FOR THE PERMANENT CENTER 1/4 CORNER OF SECTION 4 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 16, AND ADDITIONAL INFORMATION IS IN PACKET "M 123" IN MISCELLANEOUS DRAWER NUMBER 5 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING DISTANCES:

- 1) 10.02-1/4 CHAINS EAST TO A 12" X 6" X 4" PROPERTY STONE HE SET ON THIS SURVEY
- 2) 20.06-1/2 CHAINS EAST TO THE 4" X 12" X 18" STONE HE SET FOR THE PERMANENT CENTER 1/4 CORNER OF SECTION 4
- 3) 20.06-1/2 CHAINS WEST TO THE 6" X 9" X 15" STONE HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 4

- 3) LARGE SURVEY SR #04005 IN THE LARGE SURVEY DRAWER FOR SECTIONS 1-8 IN TOWNSHIP 19-11 FOR THE J. E. ARNDT PROPERTY IN THE NORTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 4 WITH NO NAME OR DATE SHOWS ON THE SURVEY DRAWING AN **IRON PIN** AT THE 1/16TH CORNER ON THE NORTH SIDE OF THE SOUTHWEST 1/4 OF SECTION 4.

THE SURVEY DRAWING SHOWS THE FOLLOWING DISTANCES:

- 1) 1,323.47' WEST TO AN IRON PIN AT THE NORTHWEST CORNER OF THE SW1/4 OF SECTION 4
- 2) 1,323.46' EAST TO THE STONE THEY FOUND AT THE NORTHEAST CORNER OF THE SW1/4 OF SECTION 4
- 3) 1,325.58' SOUTH TO AN IRON PIN AT THE CENTER OF THE SW1/4 OF SECTION 4

- 4) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F04034 IN THE SURVEY FILE FOR SECTIONS 1-8 IN TOWNSHIP 19-11 SHOWING THE RESULTS OF A SURVEY OF THE WEST 330 FEET OF THE SOUTH 1/2 OF THE SOUTH 1/2 OF THE NORTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 4-19-11 DATED NOVEMBER 2, 1959 SHOWS ON HIS SURVEY DRAWING A "**MONUMENT**" AT THE

1/16TH CORNER ON THE NORTH SIDE OF THE SOUTHWEST 1/4 OF SECTION 4. THERE IS NO DESCRIPTION OF THE MONUMENT AND THERE ARE NO TIES ON THE SURVEY.

HIS DRAWING SHOWS THE FOLLOWING DISTANCES:

- 1) 1,322.46' WEST TO A "MONUMENT" AT THE NORTHWEST CORNER OF THE SW1/4 OF SECTION 4 – NOT DESCRIBED
- 2) 1,322.46' EAST TO A "MONUMENT" A THE NORTHEAST CORNER OF THE SW1/4 OF SECTION 4 – NOT DESCRIBED
- 3) 1,325.57' SOUTH TO THE THEORETICAL POSITION FOR THE CENTER OF THE SW1/4 OF SECTION 4
- 4) 2,651.13' SOUTH TO THE THEORETICAL POSITION FOR THE 1/16TH CORNER ON THE SOUTH SIDE OF THE SW1/4 OF SECTION 4

NORTH SIXTEENTH CORNER SOUTHWEST QUARTER SECTION 04-19-11