

NORTH 1/16TH CORNER OF THE NORTHEAST QUARTER OF SECTION 06, TOWNSHIP 19 SOUTH, RANGE 11 EAST

- 1) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 6, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 186 DATED MAY 14, 1900 ORDERED BY J. A. SPRAGUE TO SURVEY THE WEST 1/2 OF THE SOUTHEAST 1/4 OF SECTION 31-18-11, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF THE WEST 1/2 OF THE SOUTHEAST 1/4 OF SECTION 31-18-11 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING DISTANCES:
 - 1) 19.94 CHAINS EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 31-18-11
 - 2) 19.92 CHAINS WEST TO THE STONE HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 31-18-11
 - 3) 58.00 CHAINS WEST TO THE STONE HE SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 31-18-11 AT THE TOWNSHIP CORNER

- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED FEBRUARY 23, 1994, FOR PROJECT NUMBER 93522-02, SAID THAT HE EXCAVATED FOR THE STONE FOUND BY ALVA J. SMITH AT THE SOUTHEAST CORNER OF THE WEST 1/2 OF THE SOUTHEAST 1/4 OF SECTION 31-18-11, BUT HE DID **NOT** FIND IT. **HE SET A 1/2" X 24" REBAR WITH HIS "LS 752" CAP** FOR THE SOUTHEAST CORNER OF THE WEST 1/2 OF THE SOUTHEAST 1/4 OF SECTION 31-18-11 ON LINE BETWEEN THE STONES THAT FOUND AT THE SOUTH 1/4 CORNER AND THE SOUTHEAST CORNER OF SECTION 31-18-11, AND AT THE PRORATED DISTANCE HE FOUND ON THE PERMANENT SURVEY BY ALVA J. SMITH IN 1900 RECORDED IN SURVEY BOOK "E" ON PAGE 186; I.E., 19.92 CHAINS IN THE WEST 1/2 AND 19.94 CHAINS IN THE EAST 1/2.
 - 1) 1,315.89' WEST TO THE SOUTH 1/4 CORNER OF SECTION 31
 - 2) 1,317.22' EAST TO THE SOUTHEAST CORNER OF SECTION 31

- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F31007 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR A SURVEY OF THE SOUTH HALF OF THE NORTHEAST QUARTER OF THE SOUTHEAST QUARTER AND THE SOUTHEAST QUARTER OF THE SOUTHEAST QUARTER OF SECTION 31-18-11, EXCEPT THE SOUTH 46.5 FEET AND TWO OTHER TRACTS, FOR PROJECT NUMBER 95246-02 DATED DECEMBER 7, 1995 SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE 1/2" REBAR WITH HIS "LS 752" CAP** AT THE SOUTHWEST CORNER OF THE EAST 1/2 OF THE SOUTHEAST 1/4 OF SECTION 31-18-11.
HIS SURVEY DRAWING SHOWS THE FOLLOWING DISTANCES:
 - 1) 1,324.34' NORTH TO A #4 REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE S1/2 OF THE NE1/4 OF THE SE1/4 OF SECTION 31
 - 2) 1,986.51' NORTH TO A #4 REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE N1/2 OF THE NE1/4 OF THE SE1/4 OF SECTION 31
 - 3) 2,649.68' NORTH TO THE THEORETICAL POSITION FOR THE 1/16TH CORNER ON THE NORTH SIDE OF THE SE1/4 OF SECTION 31
 - 4) 1,317.02' EAST TO THE STONE & REBAR HE FOUND AT THE SOUTHEAST CORNER OF SECTION 31

- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED APRIL 7, 2009 FOR PROJECT NUMBER 09076-02, SURVEY F31015 IN THE SURVEY FILE FOR TOWNSHIP 18-11 FOR A TRACT IN THE WEST HALF OF THE SOUTHEAST QUARTER OF SECTION 31-18-11 FOR WILLIAMS, SAID THAT HE DETERMINED A **THEORETICAL POSITION** FOR THE SOUTHEAST CORNER OF THE WEST 1/2 OF THE SOUTHEAST 1/4 OF SECTION 31-18-11, BUT IT WAS **NOT** MONUMENTED ON THIS SURVEY.

HIS SURVEY DRAWING SHOWS THE FOLLOWING DISTANCES:

- 1) 400.00' WEST TO THE SOUTHWEST CORNER OF THE EXCEPTED TRACT AS WITNESSED BY A 1/2" REBAR WITH HIS "LS 752" CAP HE FOUND 46.5' NORTH
- 2) 1,316.12' WEST TO A 5/8" REBAR WITH AN ALUMINUM CAP IN A MONUMENT WELL HE FOUND AT THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 31
- 3) 1,098.00' NORTH TO A 1/2" REBAR WITH HIS "LS 752" CAP HE FOUND AT THE NORTHEAST CORNER OF THE EXCEPTED TRACT
- 4) 2,648.70' NORTH TO A 1/2" REBAR WITH HIS "LS 752" CAP HE FOUND AT THE NORTHEAST CORNER OF THE W1/2 OF THE SE1/4 OF SECTION 31

NORTH SIXTEENTH CORNER NORTHEAST QUARTER 06-19-11