

**CENTER CORNER SOUTHWEST QUARTER OF SECTION 08, TOWNSHIP 19 SOUTH,
RANGE 11 EAST**

- 1) E. C. GOLDSMITH, COUNTY ENGINEER FROM 1944 TO 1949, BY W. D. KRETSINGER, L.S. 363, IN AN **INFORMAL SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 155 TO LOCATE THE CORNERS AND BOUNDARIES OF THE NORTH 1/2 OF THE SOUTHEAST 1/4 OF THE SOUTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 8, SHOWS ON HIS SURVEY DRAWING THAT HE SET A **TEMPORARY POINT** FOR THE CENTER OF THE SOUTHWEST 1/4 CORNER OF SECTION 8 ON THIS **INFORMAL SURVEY**. HE NOTED TO REFER TO THE PREVIOUS CHAINING NOTES FOR THE LYON COUNTY FAIR GROUNDS RECORDED ON PAGE 141 OF PERMANENT SURVEY BOOK 1. THERE ARE NO TIES ON THE SURVEY.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,322.90' NORTH TO THE TEMPORARY POINT HE SET FOR THE 1/8TH CORNER ON THE EAST AND WEST 1/2 SECTION LINE
 - 2) 661.45' SOUTH TO THE 1/2" DIAMETER REBAR HE SET FOR THE NORTHEAST TRACT CORNER
 - 3) 992.17' SOUTH TO THE 1/2" DIAMETER REBAR HE SET FOR THE SOUTHEAST TRACT CORNER
 - 4) 1,322.9' SOUTH TO THE TEMPORARY POINT HE SET FOR THE SOUTHEAST CORNER OF THE SW1/4 OF THE SW1/4 OF SECTION 8
 - 5) 1,322.6' WEST TO THE TEMPORARY POINT HE SET FOR THE NORTHWEST CORNER OF THE SW1/4 OF THE SW1/4 OF SECTION 8
- 2) KDOT PLANS FOR 50-56-U050-5(9) FOR NEW HIGHWAY 50 ALIGNMENT DATED 1972, SHOWS A **60 D SPIKE** AT THE CENTER CORNER OF THE NORTHEAST 1/4 OF SECTION 8.
 - 1) 664.34' SOUTH OF BASELINE STATION 385+03.58
 - 2) 57.05' NE TO A SPIKE & WASHER IN A POWER POLE
 - 3) 38.03' NNE TO A SPIKE & WASHER IN A POWER POLE
 - 4) 91.54' SSE TO A SPIKE & WASHER IN A 40" ELM TREE
- 3) LLOYD J. DOBLER, L.S. 541, IN SURVEY F08001 IN THE SURVEY FILES FOR SECTION 1-8 IN TOWNSHIP 19-11 DATED APRIL 1978 FOR A SURVEY FOR ROBERT HILLARD, SHOWS ON HIS SURVEY DRAWING A "**MONUMENT**" AT THE NORTHWEST CORNER OF THE SOUTHEAST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 8. HE DOES NOT DESCRIBE THE MONUMENT AND THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES.
- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F08119 IN THE SURVEY FILE FOR SECTIONS 1-8 IN TOWNSHIP 19-11 FOR THE SURVEY OF THREE TRACTS IN THE NORTHWEST QUARTER OF THE SOUTHWEST QUARTER OF SECTION 8-19-11 FOR PROJECT NUMBER 00521-02 DATED FEBRUARY 23, 2001, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND A PLUS ("+") CUT IN CONCRETE** AT THE SOUTHEAST CORNER OF THE NORTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 8.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,323.27' NORTH TO THE 40 D NAIL IN THE CONCRETE SEAM WITH SCRIBE MARKS ON THE NORTH & SOUTH SIDES HE SET FOR THE NORTHEAST CORNER OF THE NW1/4 OF THE SW1/4 OF SECTION 8
- 5) CHARLES W. BROOKSHER, L.S. 1281, OF PROFESSIONAL ENGINEERING CONSULTANTS, IN A SECTION CORNER REPORT DATED SEPTEMBER 28, 2004, FOR PROJECT NUMBER 60X04550, SAID THAT **HE FOUND A CHISELED PLUS ("+") ON THE CONCRETE PAVEMENT** AT THE SOUTHEAST CORNER OF THE NORTHWEST

1/4 OF THE SOUTHWEST 1/4 OF SECTION 8 FROM RECORD TIES IN THE COUNTY ENGINEER'S OFFICE.

- 1) 57.05' NE TO A SPIKE & WASHER IN THE SOUTHEAST FACE OF A POWER POLE
- 2) 42.87' WEST TO A PK NAIL IN THE NORTH FACE OF A POWER POLE
- 3) 45.20' NNE TO A PK NAIL IN THE NORTHWEST FACE OF A POWER POLE
- 4) 53.92' SE TO THE TOP OPERATING NUT ON A FIRE HYDRANT

- 6) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED OCTOBER 19, 2004, FOR PROJECT NUMBER 04332-02, SURVEY F08124 IN THE SURVEY FILE FOR SECTIONS 1-8 IN TOWNSHIP 19-11 FOR THE WEST 265 FEET OF THE SOUTH HALF OF THE NORTH HALF OF THE NORTHEAST QUARTER OF THE SOUTHWEST QUARTER OF THE SOUTHWEST QUARTER OF SECTION 8-19-11, SAID THAT **FOUND A PLUS ("+") CUT IN CONCRETE** AT THE CENTER OF THE SOUTHWEST 1/4 OF SECTION 8 FROM HIS PREVIOUS SURVEY.

- 1) 46.20' NE TO A MAG NAIL IN A POWER POLE
- 2) 57.05' NE TO A 40 D NAIL & WASHER IN A POWER POLE
- 3) 54.05' SE TO THE TOP CENTER OF A FIRE HYDRANT
- 4) 42.9' WEST TO AN ALUMINUM SPIKE IN A POWER POLE
- 5) 0.45' WEST TO THE SEAM CUT NORTH-SOUTH [GRAHAM STREET]

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 661.22' WEST TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE NE1/4 OF THE SW1/4 OF THE SW1/4 OF SECTION 8
- 2) 1,322.44' WEST TO THE 5/8" REBAR FOUND AT THE NORTHWEST CORNER OF THE SW1/4 OF THE SW1/4 OF SECTION 8
- 3) 1,322.25' SOUTH TO THE COTTON GIN SPINDLE FROM A PREVIOUS SURVEY FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF THE SW1/4 OF SEC. 8

- 7) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F08125 IN THE SURVEY FILE FOR SECTIONS 1-8 IN TOWNSHIP 19-11 FOR PROJECT NUMBER 04447-02 DATED DECEMBER 6, 2004 FOR A SURVEY OF THE WEST 161.27 FEET OF A TRACT IN THE NORTHEAST QUARTER OF THE SOUTHWEST QUARTER OF THE SOUTHWEST QUARTER OF SECTION 8-19-11, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND A PLUS CUT** AT THE NORTHEAST CORNER OF THE NORTH 1/2 OF THE NORTH 1/2 OF THE NORTHEAST 1/4 OF THE SOUTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 8.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 499.95' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF THE SURVEY TRACT
- 2) 661.22' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF THE N1/2 OF THE N1/2 OF THE NE1/4 OF THE SW1/4 OF THE SW1/4 OF SECTION 8
- 3) 1,322.44' WEST TO THE 1/2" REBAR WITH HIS "LS 7852" CAP HE FOUND AT THE NORTHWEST CORNER OF THE SW1/4 OF THE SW1/4 OF SECTION 8

- 8) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED FEBRUARY 08, 2007, FOR PROJECT NUMBER 07001-02, SURVEY F08130 IN THE SURVEY FILE FOR SECTIONS 1-8 IN TOWNSHIP 19-11 FOR A TRACT IN THE SOUTHWEST QUARTER OF SECTION 8-19-11 FOR PAUL HANCOCK/ESTES, SAID THAT **HE FOUND THE PLUS ("+") CUT IN CONCRETE** AT THE CENTER OF THE SOUTHWEST 1/4 OF SECTION 8 FROM HIS PREVIOUS SURVEY.

- 1) 46.20' NE TO A MAG NAIL IN A POWER POLE
- 2) 57.05' NE TO A 40 D NAIL & WASHER IN A POWER POLE
- 3) 54.05' SE TO THE TOP CENTER OF A FIRE HYDRANT
- 4) 42.9' WEST TO AN ALUMINUM SPIKE IN A POWER POLE

HIS TIES ARE CONTINUED ON PAGE 3

5) 0.45' WEST TO THE SEAM CUT NORTH-SOUTH [GRAHAM STREET]

6) 0.20' NORTH TO THE SEAM CUT EAST-WEST [GRAHAM STREET]

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

1) 661.13' SOUTH TO THE THEORETICAL POSITION FOR THE SOUTHWEST CORNER OF THE N1/2 OF THE SE1/4 OF THE SW1/4 OF SECTION 8

2) 1,322.66' SOUTH TO THE MAG NAIL HE FOUND AT THE SOUTHWEST CORNER OF THE SE1/4 OF THE SW1/4 OF SECTION 8

3) IN THE INTERSECTION OF 9TH AVENUE AND GRAHAM STREET

CENTER CORNER SOUTHWEST QUARTER SECTION 08-19-11