

**NORTH 1/16TH CORNER NORTHWEST QUARTER OF SECTION 08, TOWNSHIP 19 SOUTH,
RANGE 11 EAST**

- 1) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN LARGE SURVEY SR #05005 IN THE SURVEY DRAWER FOR SECTIONS 1-8 IN TOWNSHIP 19-11 WITH NO DATE FOR A TOPOGRAPHIC SURVEY OF THE SE 1/4 OF THE SW 1/4 OF SECTION 5-19-11, SHOWS A “**MONUMENT**” AT THE SOUTHWEST CORNER OF THE SOUTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 5, BUT THERE IS NO DESCRIPTION OF THE MONUMENT AND THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES.

HIS SURVEY DRAWING SHOWS THE FOLLOWING DISTANCES:

- 1) 1,324.3'± EAST TO A MONUMENT AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 5
 - 2) 1,320'3"± NORTH TO A MONUMENT AT THE NORTHWEST CORNER OF THE SE1/4 SW1/4 OF SECTION 5
- 2) LARGE SURVEY SR #50006 IN THE SURVEY DRAWER FOR SECTIONS 1-8 IN TOWNSHIP 19-11 WITH NO NAME OR DATE SHOWS A “**MONUMENT**” AT THE SOUTHWEST CORNER OF THE SOUTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 5, BUT THERE IS NO DESCRIPTION OF THE MONUMENT AND THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES.
- HIS SURVEY DRAWING SHOWS THE FOLLOWING DISTANCES:
- 1) 1,320.3' NORTH TO A MONUMENT AT THE NORTHEAST CORNER OF THE SE1/4 SW1/4 OF SECTION 5
 - 2) 1,324.3' EAST TO A MONUMENT AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 5

- 3) LARGE SURVEY SR #05001 IN THE LARGE SURVEY DRAWER FOR SECTIONS 1-8 IN TOWNSHIP 19-11 WITH NO NAME OR DATE SHOWS AN **IRON PIN** AT THE 1/16TH CORNER ON THE NORTH SIDE OF THE NORTHWEST 1/4 OF SECTION 8, BUT THERE IS NO DESCRIPTION OF THE MONUMENT AND THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES.

THE SURVEY DRAWING SHOWS THE FOLLOWING DISTANCES:

- 1) 1,324.3' WEST TO A STONE & IRON PIN AT THE SOUTHWEST CORNER OF SEC. 5
 - 2) 1,323.4' EAST TO AN IRON PIN AT THE SOUTH 1/4 CORNER OF SECTION 5
 - 3) 3,972.9' EAST TO A STONE & IRON PIN AT THE SOUTHWEST CORNER OF SEC. 5
 - 4) 1,321.75' NORTH TO AN IRON PIN AT THE CENTER OF THE SW1/4 OF SECTION 5
 - 5) 2,643.50' NORTH TO AN IRON PIN AT THE 1/16TH CORNER
- 4) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED MARCH 26, 2002, FOR PROJECT NUMBER 01581-02, SURVEY F08121 IN THE SURVEY FILE FOR SECTIONS 1-8 IN TOWNSHIP 19-11 FOR THE SURVEY OF A TRACT OF LAND IN THE NORTHWEST QUARTER OF SECTION 8-19-11 IN THE CITY OF EMPORIA, SAID THAT **SHE FOUND A COTTON GIN SPINDLE IN THE ASPHALT PAVEMENT OF 18TH STREET FROM A PRIOR SURVEY** AT THE NORTH 1/16TH CORNER OF THE NORTHWEST 1/4 OF SECTION 8.
- 1) 37.25' NORTH TO A 1/2" REBAR WITH A “GEOTECH” CAP
 - 2) 65.75' NNW TO A CONCRETE NAIL & BOTTLE CAP IN A POWER POLE
 - 3) 30.0' SOUTH TO A 1/2" REBAR WITH HER CAP AT THE NORTHEAST CORNER OF THE F.H.T.C. TRACT AT THE RIGHT-OF-WAY
 - 4) 33.05' SSW TO A CONCRETE NAIL & BOTTLE CAP IN A POWER POLE
 - 5) 53.85' SE TO THE NEAR FACE OF A GAS PIPE LINE MARKER AT GROUND LEVEL
 - 6) IN THE CENTERLINE TRAVELED WAY OF 18TH AVENUE
- HER SURVEY DRAWING SHOWS THE FOLLOWING DISTANCE:
- 1) 1,325.94' WEST TO A 5/8" REBAR FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 8

- 5) CHARLES W. BROOKSHER, L.S. 1281, OF PROFESSIONAL ENGINEERING CONSULTANTS, IN A SECTION CORNER REPORT DATED SEPTEMBER 28, 2004, FOR PROJECT NUMBER 60X04550, SAID THAT **HE FOUND THE COTTON GIN SPINDLE** AT THE NORTHEAST CORNER OF THE NORTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 8 FROM TIES IN THE COUNTY ENGINEER'S OFFICE.
 - 1) IN THE CENTERLINE 18TH STREET ASPHALT PAVEMENT
 - 2) 37.25' NORTH TO A 1/2" BAR
 - 3) 22.83' SOUTH TO A 1/2" BAR DRILLED INTO THE CONCRETE SIDEWALK
 - 4) 30.00' SOUTH TO A 1/2" BAR
 - 5) 65.75' NNW TO A NAIL & BOTTLE CAP IN THE SOUTH FACE OF A POWER POLE
 - 6) 33.05' SW TO A NAIL & BOTTLE CAP IN THE NORTHEAST FACE OF A POWER POLE

- 6) GARY L. HAY, L.S. 1212, OF H.N.T.B., IN A SECTION CORNER REPORT DATED AUGUST 26, 2005, FOR PROJECT NUMBER 41922, EMPORIA INDUSTRIAL ROAD, SAID THAT **HE FOUND THE COTTON GIN SPINDLE** AT THE NORTH 1/16TH CORNER OF THE NORTHWEST 1/4 OF SECTION 8 FROM PREVIOUS LAND SURVEY REFERENCE REPORTS BY POLLY A. JONES [3/26/02] AND CHARLES W. BROOKSHER [9/28/04]. KDOT PROJECT 35-56 KA-0133-01.
 - 1) IN THE CENTERLINE TRAVELED WAY OF 8TH STREET
 - 2) 30.00' SOUTH TO A 1/2" BAR FOUND
 - 3) 65.65' NORTH-NORTHWEST TO A NAIL & BOTTLECAP IN THE SOUTH FACE OF A POWER POLE
 - 4) 33.05' SOUTHWEST TO A NAIL & BOTTLECAP IN THE NORTHWEST FACE OF A POWER POLE
 - 5) 50.75' NORTH-NORTHWEST TO THE SOUTH FACE OF A CHAIN LINK FENCE CORNER POST
 - 6) 574.35' WEST OF CENTERLINE STATION 163+90.62 [SW ANGLE = 38°59'55"]
 - 7) KANSAS STATE PLANE COORDINATES: CAF = 0.999920215
 NORTH = 1958609.660000 EAST = 1965055.557000

NORTH SIXTEENTH CORNER NORTHWEST QUARTER SECTION 08-19-11