

**NORTH 1/16<sup>TH</sup> CORNER SOUTHEAST QUARTER OF SECTION 08, TOWNSHIP 19 SOUTH, RANGE 11 EAST**

- 1) E. C. GOLDSMITH, COUNTY ENGINEER FROM 1944 TO 1949, BY LESLIE M. GOULD, L.S. 142, DEPUTY COUNTY SURVEYOR, IN AN **INFORMAL SURVEY** TO LOCATE THE PROPERTY CORNERS OF THE LYON COUNTY FAIR GROUND IN THE WEST 1/2 OF THE SOUTHEAST 1/4 OF SECTION 8-19-11 RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 141 WITH NO DATE, SAID THAT **HE SET A 1/2" SQUARE IRON PIN** FOR THE NORTHEAST CORNER OF THE WEST 1/2 OF THE SOUTHEAST 1/4 OF SECTION 8-19-11 ON LINE AND HALFWAY BETWEEN THE CENTER CORNER AND THE EAST 1/4 CORNER OF SECTION 8-19-11 ON THIS **INFORMAL SURVEY**.  
**HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**
  - 1) 1,323.7' EAST TO THE 1/2" SQUARE IRON PIN HE SET FOR THE EAST 1/4 CORNER OF SECTION 8-19-11
  - 2) 1,323.7' WEST TO THE 1/2" SQUARE IRON PIN HE SET FOR THE CENTER CORNER OF SECTION 8-19-11
  - 3) 3,971.1' WEST TO THE 1/2" DIAMETER IRON PIN HE FOUND AT THE WEST 1/4 CORNER OF SECTION 8-19-11
  - 4) 30.0' SOUTH TO THE 1/2" DIAMETER IRON PIN HE SET FOR THE NORTHEAST PROPERTY CORNER
  - 5) 1,323.33' SOUTH TO THE 1/2" DIAMETER IRON PIN HE SET FOR THE CENTER CORNER OF THE SE1/4 OF SECTION 8-19-11 AND A PROPERTY CORNER
  - 6) 2,646.65' SOUTH TO A TEMPORARY POINT HE SET FOR THE 1/16<sup>TH</sup> CORNER ON THE SOUTH SIDE OF THE SE1/4 OF SECTION 8-19-11
  
- 2) LESLIE M. GOULD, L.S 142, ASSISTANT COUNTY ENGINEER AND COUNTY SURVEYOR FROM 1953 TO 1978, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 13 DATED DECEMBER, 1955 TO SURVEY TRACTS IN THE NORTHEAST 1/4 OF SECTION 8, SHOWS ON HIS DRAWING **AN IRON PIN** FOR THE SOUTH 1/16<sup>TH</sup> CORNER OF THE NORTHEAST 1/4 OF SECTION 8-19-11 HALFWAY BETWEEN THE CENTER CORNER AND THE EAST 1/4 CORNER OF SECTION 8-19-11 ON THIS **PERMANENT SURVEY**.  
**HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**
  - 1) 661.44' WEST TO AN IRON PIN SET
  - 2) 1,322.88' WEST TO AN IRON PIN AT THE CENTER CORNER OF SECTION 8-19-11 WITNESSED AS FOLLOWS: 33.9' NORTH TO A STEEL GATE POST; 26.5' SSW TO A SPIKE IN A POWER POLE; 28.4' NORTH TO A SPIKE IN A GUY POLE; 27.1' SE TO A STEEL GATE POST
  - 3) 3,968.63' WEST TO AN IRON PIN AT THE WEST 1/4 CORNER OF SECTION 8-19-11 WITNESSED AS FOLLOWS 21.9' WSW TO A SPIKE & WASHER IN THE TOP OF A GUARD POST; 26.9' NW TO A SPIKE & WASHER IN A GUARD POST; 45.9' NE TO A NAIL & WASHER IN A GUY POLE; AND 29.7' SE TO A NAIL & WASHER IN A POWER POLE
  - 4) 661.44' EAST TO AN IRON PIN SET
  - 5) 1,322.88' EAST TO AN IRON PIN AT THE EAST 1/4 CORNER OF SECTION 8-19-11 WITNESSED AS FOLLOWS: 40.8' NE TO A SPIKE IN A POWER POLE; 32.45' SE TO A SPIKE IN A POWER POLE; AND 33.1' SW TO A SPIKE IN A POWER POLE
  - 6) 661.53' NORTH TO AN IRON PIN SET
  - 7) 1,323.06' NORTH TO AN IRON PIN AT THE CENTER CORNER OF THE NE1/4 OF SECTION 8-19-11
  
- 3) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 19-11 SHOWS AN **IRON PIN** AT THE NORTH 1/16<sup>TH</sup> CORNER OF THE SOUTHEAST 1/4 OF SECTION 8-19-11.
  - 1) 40.5' NE TO A LIGHT POLE
  - 2) 44.7' SE TO A LIGHT POLE

CONTINUED ON PAGE 2

- 4) KRETSINGER REFERENCE TIE BOOK 13 ON PAGE 84 AT THE TOP OF THE PAGE SHOWS AN **IRON PIN** AT THE “NW CORNER E1/2 SE1/4 OF SECTION 08-19-11”.
  - 1) 40.5’ NE TO THE NEAR FACE OF A LIGHT POLE
  - 2) 44.7’ SE TO THE NEAR FACE OF A LIGHT POLE
  
- 5) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED AUGUST 9, 2010, FOR PROJECT NUMBER 10214-02, THE BOUNDARY SURVEY OF THE FAIRGROUNDS FOR THE BOARD OF COUNTY COMMISSIONERS, SURVEY F08133 IN THE SURVEY FILE FOR SECTIONS 1-8 IN TOWNSHIP 19-11 AND THE TOPOGRAPHIC SURVEY IS RECORDED AS LARGE SURVEY SR#80070 IN THE SURVEY DRAWER FOR TOWNSHIP 19-11, SAID THAT HE DETERMINED A **THEORETICAL POSITION** FOR THE NORTHEAST CORNER OF THE NORTHWEST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 8-19-11. THE POSITION WAS **NOT** MONUMENTED ON THIS SURVEY.  
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 1,322.40’ WEST TO THE 2” ALUMINUM CAPPED REBAR IN A MONUMENT WELL HE FOUND AT THE NORTHWEST CORNER OF THE SE1/4 OF SECTION 8-19-11
  - 2) 1,322.40’ EAST TO THE 5/8” CAPPED REBAR IN A MONUMENT WELL HE FOUND AT THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 8-19-11
  - 3) 1,327.80’ SOUTH TO THE 3/4" REBAR HE FOUND AT THE SOUTHEAST CORNER OF THE NW1/4 OF THE SE1/4 OF SECTION 8-19-11

NORTH SIXTEENTH CORNER SOUTHEAST QUARTER SECTION 08-19-11