

**CENTER CORNER NORTHWEST QUARTER OF SECTION 09, TOWNSHIP 19 SOUTH,
RANGE 11 EAST**

- 1) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 4, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 184 DATED MAY 1, 1900 ORDERED BY W. W. JONES, J. W. McCULLOCH, AND FRED STUCKEY TO ESTABLISH THE WEST BOUNDARY OF THE NORTHWEST 1/4 OF THE NORTHEAST 1/4 OF THE NORTHWEST 1/4 OF SECTION 9-19-11, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF THE NORTHEAST 1/4 OF THE NORTHWEST 1/4 OF SECTION 9-19-11 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING DISTANCES:
 - 1) 20.09 CHAINS WEST TO THE STONE HE FOUND AT THE 1/8TH CORNER ON THE WEST SIDE OF THE NW1/4 OF SECTION 10
 - 2) 10.02 CHAINS NORTH TO THE 18" X 12" X 4" STONE DRESSED ON ONE SIDE HE SET FOR THE PERMANENT SOUTHWEST CORNER OF THE NW1/4 OF THE NE1/4 OF THE NW1/4 OF SECTION 10
 - 3) 20.03 CHAINS NORTH TO THE 18" X 12" X 4" STONE DRESSED ON ONE SIDE HE SET FOR THE PERMANENT NORTHWEST CORNER OF THE NE1/4 OF THE NW1/4 OF SECTION 10

- 2) E. C. GOLDSMITH, COUNTY ENGINEER FROM 1944 TO 1949, BY W. D. KRETSINGER, L.S. 363, IN AN **INFORMAL SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 157 FOR A SURVEY THE EAST 1/2 OF THE SOUTHEAST 1/4 OF THE NORTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 9-19-11 FOR THE EMPORIA MEMORIAL POST NO. 7957 OF THE VETERANS OF FOREIGN WARS, SAID THAT HE DETERMINED A **TEMPORARY POINT** FOR THE CENTER OF THE NORTHWEST 1/4 OF SECTION 9-19-11 ON THIS **INFORMAL SURVEY**. A PENCIL NOTE INDICATES THAT THE SURVEY WAS COMPLETED ON JULY 28, 1947. THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,326.50' WEST TO AN IRON PIN HE FOUND AT THE SOUTHWEST CORNER OF THE NW1/4 OF THE NW1/4 OF SECTION 9
 - 2) 1,326.50' EAST TO THE 1/8TH CORNER ON THE EAST SIDE OF THE NW1/4 OF SEC. 9
 - 3) 30.0' NORTH TO AN IRON PIN HE SET FOR THE SOUTHEAST TRACT CORNER ON THE NORTH RIGHT-OF-WAY LINE OF 15TH AVENUE
 - 4) 660.0' NORTH TO AN IRON PIN HE SET FOR THE NORTHEAST TRACT CORNER
 - 5) 1,321.6' NORTH TO THE TEMPORARY POINT FOR THE 1/8TH CORNER ON THE NORTH SIDE OF THE NW1/4 OF SECTION 9

- 3) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN LARGE SURVEY SR #9031 IN THE SURVEY DRAWER FOR SECTIONS 9 & 10 IN TOWNSHIP 19-11, DATED FEBRUARY 16, 1960, SHOWS ON HIS SURVEY DRAWING A "**MONUMENT**" AT THE SOUTHWEST CORNER OF THE NORTHEAST 1/4 OF THE NORTHWEST 1/4 OF SECTION 9-19-11. HE DOES NOT IDENTIFY THE MONUMENT AND THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES.

- 4) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 54 DATED SEPTEMBER 11 & 12, 1969, TO LOCATE THE BOUNDARIES OF A TRACT IN THE NORTHWEST 1/4 OF SECTION 9, SHOWS ON HIS DRAWING THAT **HE FOUND** THE SOUTHEAST CORNER OF THE NORTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 9-19-11 ON THIS **PERMANENT SURVEY**. THE SURVEY WAS RECORDED ON BOOK 2 OF PLATS ON PAGE 54A IN THE REGISTER OF DEEDS OFFICE ON OCTOBER 13, 1969. HE DOES NOT IDENTIFY THE MONUMENT AND THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,326.6' WEST TO THE SOUTHWEST CORNER OF THE NW1/4 OF THE NW1/4 OF SECTION 9

- 5) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN SURVEY F09189 IN THE SURVEY FILE FOR SECTION 9 IN TOWNSHIP 19-11 FOR A 1.433 ACRE TRACT IN THE NORTHWEST QUARTER OF THE NORTHWEST QUARTER OF SECTION 9-19-11 DATED SEPTEMBER 23, 2002 FOR PROJECT NUMBER 02086-02, SHOWS ON HER SURVEY DRAWING THAT **SHE SET A CONCRETE NAIL & WASHER IN THE PAVEMENT** FOR THE SOUTHEAST CORNER OF THE NORTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 9-19-11.
HER SURVEY DRAWING SHOWS THE FOLLOWING DISTANCES:
 - 1) 1,326.30' EAST TO THE CROSS CUT IN THE CONCRETE PAVEMENT AT THE SOUTHEAST CORNER OF THE NE1/4 OF THE NW1/4 OF SECTION 9
 - 2) 331.65' WEST TO THE CONCRETE NAIL & WASHER SHE SET IN PAVEMENT FOR THE SOUTHEAST CORNER OF THE W1/2 OF THE SE1/4 OF THE NW1/4 OF THE NW1/4 OF SECTION 9
 - 3) 865.65' WEST TO THE CONCRETE NAIL & WASHER SHE SET FOR THE SOUTHEAST CORNER OF THE 1.433 ACRE TRACT
 - 4) 1,096.60' WEST TO THE CONCRETE NAIL & WASHER SHE SET IN PAVEMENT FOR THE SOUTHWEST CORNER OF THE 1.433 ACRE TRACT
 - 5) 1,326.30' WEST TO THE CONCRETE NAIL & WASHER SHE SET IN THE CONCRETE PAVEMENT AT THE SOUTHWEST CORNER OF THE NW1/4 OF THE NW1/4 OF SECTION 9 AT THE INTERSECTION OF 15TH AVENUE AND PRAIRIE STREET

CENTER CORNER NORTHWEST QUARTER SECTION 09-19-11