

NORTH 1/4 CORNER SECTION 09, TOWNSHIP 19 SOUTH, RANGE 11 EAST

- 1) ON PAGE 375 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 25" X 24" X 1-1/2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 4 & 9-19-11 .
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.21 CHAINS WEST TO THE 40" X 22" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 4, 5, 8 & 9-19-11
 - 2) 40.21 CHAINS EAST TO THE 21" X 18" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 3, 4, 9 & 10-19-11

- 2) G. M. WALKER, BRECKENRIDGE COUNTY SURVEYOR FROM 1857 TO 1860, IN SURVEY NUMBER 9 RECORDED IN SURVEY BOOK "A" ON PAGE 6 DATED APRIL 17, 1858, A **PERMANENT SURVEY** TO ESTABLISH THE CENTER POST OF SECTION 9-19-11, SAID THAT **HE FOUND THE NORTH 1/4 STONE POST** OF SECTION 9-19-11 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 40.13-1/2 CHAINS SOUTH TO THE POST STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 9-19-11
 - 2) 80.27 CHAINS SOUTH TO THE FOUND SOUTH 1/4 POST STONE OF SEC. 9-19-11

- 3) G. M. WALKER, BRECKENRIDGE COUNTY SURVEYOR FROM 1857 TO 1860, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "A" ON PAGES 11 & 12 DATED DECEMBER 1 & 2, 1858, FOR THE COUNTY ROAD FROM EMPORIA VIA STUBBS FORD OF THE NEOSHO RIVER TO AMERICUS, SAID THAT **HE FOUND THE NORTH 1/4 STONE POST** OF SECTION 9-19-11 ON THIS ROAD SURVEY.

- 4) G. W. WALKER, BRECKENRIDGE COUNTY SURVEYOR, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 13 THROUGH 15 FOR THE "EMPORIA AND AMERICUS ROAD" SURVEYED DECEMBER 1 & 2, 1858, AND RECORDED IN THE COMMISSIONER'S JOURNAL ON PAGE 34 ON DECEMBER 6, 1858, SAID THAT **HE FOUND THE NORTH STONE 1/4 POST** OF SECTION 9-19-11 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS SOUTHEASTERLY TO THE WEST 1/4 STONE POST OF SECTION 10-19-11, BEING THE NORTHWEST CORNER OF EMPORIA
 - 2) THIS ROAD EXTENDS WEST 25.50 CHAINS TO AN ANGLE STAKE HE SET ON THIS ROAD SURVEY

- 5) G. M. WALKER, BRECKENRIDGE COUNTY SURVEYOR FROM 1857 TO 1860, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 17 TO 19 FOR THE RESURVEY OF THE "EMPORIA TO AMERICUS ROAD" ORIGINALLY SURVEYED SEPTEMBER 10, 1858 AND ESTABLISHED NOVEMBER 1, 1858, RESURVEYED THE ROAD ON FEBRUARY 15 & 16, 1859 AND IT WAS ESTABLISHED ON FEBRUARY 28, 1859 [PACKET 526 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] ESTABLISHED NOVEMBER 1, 1858, SAID THAT **HE FOUND THE SOUTH 1/4 STONE POST** OF SECTION 4-18-11 TO COMMENCE THIS ROAD RESURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS NORTH TO THE STONE POST HE FOUND AT THE CENTER CORNER OF SECTION 33-18-11 AT A TURN TO THE NORTHWESTERLY

- 6) G. M. WALKER, BRECKENRIDGE COUNTY SURVEYOR FROM 1857 TO 1860, IN SURVEY NUMBER 25 OF THE 2ND TERM, RECORDED IN SURVEY BOOK "A" ON PAGE 27 DATED FEBRUARY 14, 1859, TO ESTABLISH THE CENTER POST OF SECTION 4-19-11, SAID THAT **HE FOUND THE SOUTH 1/4 STONE POST** OF SECTION 4-19-11 ON THIS SURVEY.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS NORTH TO THE STONE HE SET FOR THE CENTER CORNER POST OF SECTION 4-19-11
- 2) 60.00 CHAINS NORTH TO THE STONE POST HE SET FOR THE SOUTHWEST CORNER OF THE S1/2 OF THE NE1/4 OF THE NW1/4 OF SECTION 4-19-11
- 3) 78.94 CHAINS NORTH TO THE FOUND NORTH 1/4 STONE POST OF SECTION 4-19-11 ON THE TOWNSHIP LINE

- 7) G. M. WALKER, BRECKENRIDGE COUNTY SURVEYOR FROM 1857 TO 1860, IN A ROAD SURVEY ON REVIEW FROM THE ORIGINAL SURVEY OF SEPTEMBER 10, 1858, AND ESTABLISHED NOVEMBER 1, 1858, RECORDED IN SURVEY BOOK "A" ON PAGES 26, 27 & 28 DATED FEBRUARY 15, 1859 FOR THE COUNTY ROAD FROM EMPORIA TO AMERICUS, SAID THAT **HE FOUND THE SOUTH 1/4 STONE POST** OF SECTION 4-19-11 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 79.84 CHAINS NORTH TO THE FOUND NORTH 1/4 STONE POST OF SECTION 4-19-11 ON THE TOWNSHIP LINE

- 8) H. S. SLEEPER, BRECKENRIDGE COUNTY SURVEYOR FROM 1859 TO 1862, IN SURVEY NUMBER 15 RECORDED IN SURVEY BOOK "A" ON PAGE 55 DATED JULY 13, 1861, TO SURVEY 20-1/4 ACRES FROM THE SOUTHWEST 1/4 OF SECTION 4-19-11, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 4-19-11 TO COMMENCE THIS SURVEY.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 81 RODS WEST TO THE SOUTHWEST CORNER OF THE 20-1/4 ACRE TRACT
- 2) 40 RODS NORTH TO THE NORTHEAST CORNER OF THE 20-14 ACRE TRACT

- 9) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 54 RECORDED IN SURVEY BOOK "A" ON PAGE 153 DATED MAY 22, 1868 FOR A SURVEY OF ANN OWEN'S LAND, BEING ALL THAT PART OF THE SOUTHWEST 1/4 OF SECTION 33-18-11, AND ALSO THE EAST 1/2 OF THE NORTHWEST 1/4 OF SECTION 4-19-11, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 4-19-11 ON THIS SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 160 RODS NORTH TO THE STONE HE SET FOR THE CENTER CORNER OF SECTION 4-19-11
- 2) 154 RODS, 4 LINKS NORTH TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 4-19-11 ON THE TOWNSHIP LINE

- 10) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 87 RECORDED IN SURVEY BOOK "A" ON PAGE 182 DATED FEBRUARY 11, 1869 FOR A ROAD PETITIONS BY T. B. PLUMB AND OTHERS FOR A ROAD IN TOWNSHIP 19, RANGE 11, SAID THAT HE BEGAN THIS ROAD SURVEY AT THE EMPORIA AND AMERICUS ROAD AT A **STONE SET IN THE GROUND**, BEING THE 1/4 CORNER ON THE NORTHERN BOUNDARY OF SECTION 9-19-11, SAID ROAD TO BE LAID OUT ON THE EAST SIDE OF THE CENTERLINE AND 60 FEET IN WIDTH.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 319 RODS, 10 LINKS SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 9-19-11

- 11) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 119 & 120 [PACKET 257 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY P. B. PLUMB AND OTHERS SURVEYED FEBRUARY 11, 1869, ESTABLISHED AS 60 FEET WIDE ON MARCH 1, 1869, AND FILED FOR RECORD ON MARCH 1, 1869 BY J. L. WILLIAMS,

COUNTY CLERK, SAID THAT HE COMMENCED THIS ROAD SURVEY AT A POINT IN THE EMPORIA AND AMERICUS ROAD AT A **STONE SET IN THE GROUND**, BEING THE 1/4 CORNER ON THE NORTH BOUNDARY OF SECTION 9-19-11. HE NOTED THAT THIS ROAD IS LAID ON THE EAST LINE ON THE CENTER LINE OF SECTION 9-19-11.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS SOUTH ON THE CENTER LINE OF SECTION 9-19-11 FOR 319 RODS AND 10 LINKS TO THE TERMINUS OF THIS ROAD SURVEY AT A STONE SET IN THE GROUND, BEING THE 1/4 CORNER ON THE SOUTHERN BOUNDARY OF SECTION 9-19-11
- 12) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 188 TO 190 [PACKET 27 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY J. M. STEELE AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 19-11 THAT WAS SURVEYED ON APRIL 22, 1871 AND WAS ORDERED ESTABLISHED IN PART AS A 60 FOOT WIDE ROAD AND IN PART VACATED AND RECORDED – REFERENCE BEING HAD TO ORDERS MADE BY THE COUNTY COMMISSION ON THE 4TH OF SEPTEMBER AND ALSO ON THE 10TH OF SEPTEMBER 1871 AS NOTED BY DAVID S. GILMORE, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 8-19-11, ON THIS ROAD SURVEY. SEE THE RECORD FOR THE PORTION OF THE ROAD ALLOWED AND THE PORTION OF THE ROAD VACATED.
- 13) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE LEFT PAGE 153 DATED FEBRUARY 15, 1878, APPARENTLY **FOUND THE STONE** AT THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF SECTION 4-19-11 TO END THIS ROAD SURVEY.
- 14) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 66 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 266 TO 268 PETITIONED BY WILLIAM HUMPHREYS AND OTHERS FOR A COUNTY ROAD IN SECTION 4-19-11 [PACKET 337 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON MARCH 3, 1880, WAS ESTABLISHED AS A 60 FOOT WIDE ROAD, EXCEPT FOR THE FIRST HALF MILE WHICH IS 40 FEET IN WIDTH, ON APRIL 12, 1880, AND WAS RECORDED ON APRIL 21, 1880 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 4-19-11 AT THE TERMINUS OF THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS 60 FOOT WIDE ROAD EXTENDS NORTH FOR 660 FEET; THEN TURNS WEST FOR 30 FEET TO THE CEMETERY GROUNDS; THEN EXTENDS NORTH ON THE 1/2 SECTION LINE FOR 1,980 FEET TO THE NORTHEAST CORNER OF THE SW1/4 OF SECTION 4-19-11; THEN TURNS WEST ON THE 1/2 SECTION LINE FOR A 40 FOOT WIDE ROAD TO THE NORTHWEST CORNER OF THE SW1/4 OF SECTION 4-19-11 TO COMMENCE THIS ROAD SURVEY
- 15) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE LEFT SIDE PAGE 179 DATED MARCH 31, 1880, FOR A COUNTY ROAD IN TOWNSHIP 19-11, APPARENTLY **FOUND THE STONE** AT THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 4-19-11 TO END THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS NORTH ON THE 1/2 SECTION LINE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF THE SW1/4 OF SECTION 4-19-11
- 16) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 4, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 184 DATED MAY 1, 1900 ORDERED BY W. W. JONES, J. W. McCULLOCH, AND FRED

STUCKEY TO ESTABLISH THE WEST BOUNDARY OF THE NORTHWEST 1/4 OF THE NORTHEAST 1/4 OF THE NORTHWEST 1/4 OF SECTION 9-19-11, SAID THAT **HE SET AN 18" X 10" X 5" STONE "DRESSED ON ONE SIDE"** FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 9-19-11 ON THIS **PERMANENT SURVEY**.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 20.11 CHAINS WEST TO THE 18" X 12" X 4" STONE DRESSED ON ONE SIDE HE SET FOR THE PERMANENT NORTHWEST CORNER OF THE NE1/4 OF THE NW1/4 OF SECTION 9-19-11
- 2) 40.21 CHAINS WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 9-19-11
- 3) 10.05 CHAINS EAST TO THE STONE HE FOUND MARKED "JAY"
- 4) 40.21 CHAINS EAST TO THE THEORETICAL LOCATION FOR THE NORTHEAST CORNER OF SECTION 9-19-11, AT A POINT 9 LINKS SOUTH AND 4 INKS WEST OF A FENCE POST – NO STONE
- 5) 80.01 CHAINS EAST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 10-19-11
- 6) 40.08 CHAINS SOUTH TO THE STONE HE FOUND AT THE CENTER CORNER OF SECTION 9-19-11

- 17) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 39, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 220 DATED MARCH 10-14, 1902 ORDERED BY CHRISTIAN THRASHER FOR S SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CENTER OF SECTION 4-19-11 AND ALSO THE CORNERS AND BOUNDARIES OF THE NORTH 1/2 OF THE NORTH 1/2 OF THE SOUTHWEST 1/4 OF SAID SECTION 4 AND RUN SUCH LINES AS ARE NECESSARY TO PROPERLY COMPLETE THE SURVEY. THE NORTH AND EAST LINES OF THE SOUTHWEST 1/4 OF SECTION 3-19-11 WILL ALSO BE LOCATED AND ESTABLISHED. **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 4-19-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 16, AND ADDITIONAL INFORMATION IS IN PACKET "M 123" IN MISCELLANEOUS DRAWER NUMBER 5 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 30.13-1/2 CHAINS NORTH TO THE 3" X 12" X 16" STONE HE SET FOR THE PERMANENT SOUTHWEST CORNER OF THE N1/2 OF THE N1/2 OF THE SW1/4 OF SECTION 4-19-11
- 2) 40.18 CHAINS NORTH TO THE 4" X 12" X 18" STONE HE SET FOR THE PERMANENT CENTER 1/4 CORNER OF SECTION 4-19-11
- 3) 60.28 CHAINS NORTH TO THE STONE HE FOUND AT THE 1/8TH CORNER ON THE WEST SIDE OF THE NE1/4 OF SECTION 4-19-11
- 4) 79.36 CHAINS NORTH TO THE 3" X 12" X 14" STONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 4-19-11

- 18) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 40, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 221 DATED MARCH 15, 1902 ORDERED BY I. O. O. F. LODGE NUMBER 15 TO SURVEY 11 ACRES OFF OF THE SOUTH SIDE OF THE NORTH 1/2 OF THE SOUTHEAST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 4-19-11, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 4-19-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 22, AND ADDITIONAL INFORMATION IS IN PACKET "M 123" IN MISCELLANEOUS DRAWER NUMBER 5 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 10.04 CHAINS NORTH TO THE 1" X 24" IRON BAR HE SET ON THIS SURVEY, AT 15 LINKS EAST AND 7 LINKS SOUTH OF THE CENTER OF A STONE WALL

HIS INFORMATION IS CONTINUED ON PAGE 5

- 2) 15.56 CHAINS NORTH TO THE 1" X 24" IRON BAR HE SET ON THIS SURVEY
 - 3) 30.10 CHAINS NORTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE N1/2 OF THE NE1/4 OF THE SE1/4 OF SECTION 4-19-11
- 19) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY FOR ROAD NUMBER 667 RECORDED IN ROAD RECORD BOOK "E" ON PAGE 24 PETITIONED BY F. C. NEWMAN AND OTHERS FOR A ROAD IN TOWNSHIP 19-11 [PACKET 779 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT WAS VIEWED BY THE COUNTY COMMISSIONERS AND THE COUNTY SURVEYOR ON DECEMBER 14, 1911 AND WAS GRANTED ON JANUARY 5, 1912 AS NOTED BY J. A. CLEMMER, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, ATTESTED BY O. K. MILLER, COUNTY CLERK, AND RECORDED ON JANUARY 15, 1912 BY MATTHEW BROWN, COUNTY SURVEYOR BY J. MAX YINGLING, DEPUTY, SAID THAT **HE FOUND THE STONE SET FIRMLY IN THE GROUND** AT THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF SECTION 4-19-11 TO BEGIN THIS ROAD SURVEY.
- HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS EAST FOR A 1/2 MILE TO THE STONE SET FIRMLY IN THE GROUND AT THE SOUTHWEST CORNER OF THE SOUTHWEST 1/4 OF SECTION 3-19-11; THEN CONTINUES EAST FOR 2,098 FEET TO THE ROAD RUNNING IN A PRACTICALLY NORTH AND SOUTH DIRECTION THROUGH SAID QUARTER SECTION KNOWN AS THE MERCHANT STREET ROAD AND TERMINATING THERE
 - 2) SAID ROAD TO BE 40 FEET WIDE, ALL ON THE NORTH SIDE OF THE ABOVE LINE AS DESCRIBED
- 21) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 89 FOR THE RECORD OF A PUBLIC ROAD VIEWED AND ALLOWED BY THE COUNTY COMMISSIONERS AND RECORDED IN VOLUME "E" ON PAGE 24 OF THE ROAD RECORDS, SAID THAT **HE FOUND THE STONE SET FIRMLY IN THE GROUND** AT THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF SECTION 4-19-11 TO BEGIN THIS ROAD SURVEY.
- HIS FIELD NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS EAST FOR A 1/2 MILE TO THE STONE SET FIRMLY IN THE GROUND AT THE SOUTHWEST CORNER OF THE SOUTHWEST 1/4 OF SECTION 3-19-11; THEN CONTINUES EAST ON THE SOUTH LINE OF THE SECTION FOR 2,098 FEET TO THE ROAD RUNNING IN A PRACTICALLY NORTH AND SOUTH DIRECTION THROUGH SAID QUARTER SECTION KNOWN AS THE MERCHANT STREET ROAD AND TERMINATING THERE
 - 2) SAID ROAD TO BE 40 FEET WIDE ALL ON THE NORTH SIDE OF THE ABOVE LINE AS DESCRIBED
 - 3) THE CHAIRMAN OF THE ROAD COMMISSIONERS WAS NOTIFIED ON JANUARY 13, 1912
 - 4) THE SURVEY WAS ENTERED ON THE 16TH DAY OF JANUARY, 1912 BY MATTHEW BROWN, COUNTY SURVEYOR, BY J. MAX YINGLING, DEPUTY
- 21) COMMISSIONER'S ROAD JOURNAL BOOK "A", PAGE 4
ON NOVEMBER 6, 1911 A PETITION SIGNED BY F. C. NEWMAN AND OTHERS FOR THE LOCATION OF A ROAD IN TOWNSHIP 19-11 WAS PRESENTED TO THE BOARD OF COUNTY COMMISSIONERS. THE ROAD WAS VIEWED ON DECEMBER 14, 1911, AND THE FINAL ORDER FOR THE LOCATION OF THE FOLLOWING ROAD WAS ISSUED ON JANUARY 15, 1912.
- 1) BEGINNING AT THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF SECTION 4-19-11; FROM THENCE DUE EAST ALONG THE SOUTH LINE OF SAID QUARTER SECTION AND CONTINUING ALONG DUE EAST ON THE SOUTH LINE OF THE

SOUTHWEST 1/4 OF SECTION 3-19-11 TO THE PUBLIC HIGHWAY RUNNING APPROXIMATELY NORTH AND SOUTH THROUGH SAID LAS NAMED QUARTER SECTION KNOWN AS THE MERCHANT STREET ROAD AND TERMINATING THERE

- 2) SAID ROAD TO BE 40 FEET WIDE, ALL ON THE NORTH SIDE OF THE ABOVE DESCRIBED LINE

- 22) W. S. RUGGLES, COUNTY ENGINEER FROM 1915 TO 1928, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 93 BY NOTICE FROM PHILLIP LOTTA, E. H. ACE, AND F. C. NEWCOMER, SAID THAT **HE FOUND THE STONE IN PLACE** AT THE NORTH 1/4 CORNER OF SECTION 9-19-11 ON THIS **PERMANENT SURVEY**. THE FIELD SURVEY WAS COMPLETED NOVEMBER 19, 1919 AND RECORDED NOVEMBER 11, 1919.

- 23) E. C. GOLDSMITH, COUNTY ENGINEER FROM 1944 TO 1949, BY W. D. KRETSINGER, L.S. 363, IN AN **INFORMAL SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 156 TO ESTABLISH THE RIGHT-OF-WAY LINES OF THE PROPOSED GRAND STREET BETWEEN 12TH AND 15TH AVENUES IN THE NORTHWEST 1/4 OF SECTION 9-19-11 IN THE CITY OF EMPORIA, SAID THAT **HE FOUND AN IRON PIN** AT THE NORTH 1/4 CORNER OF SECTION 9-19-11 ON THIS **INFORMAL SURVEY**. THERE ARE NO TIES ON THE SURVEY.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,321.6' SOUTH TO THE IRON PIN HE SET FOR THE 1/8TH CORNER ON THE EAST SIDE OF THE NW1/4 OF SECTION 9-19-11 AT LINCOLN STREET AND 15TH AVENUE
 - 2) 2,643.2' SOUTH TO THE IRON PIN HE FOUND AT THE CENTER CORNER OF SECTION 9-19-11 AT LINCOLN STREET AND 12TH AVENUE

- 24) E. C. GOLDSMITH, COUNTY ENGINEER FROM 1944 TO 1949, BY W. D. KRETSINGER, L.S. 363, IN AN **INFORMAL SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 157 TO SURVEY THE EAST 1/2 OF THE SOUTHEAST 1/4 OF THE NORTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 9 FOR THE EMPORIA MEMORIAL POST NO. 7957 OF THE VETERANS OF FOREIGN WARS, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND** THE NORTH 1/4 CORNER OF SECTION 9-19-11 ON THIS **INFORMAL SURVEY**. A PENCIL NOTE INDICATES THAT THE SURVEY WAS COMPLETED ON JULY 28, 1947. THERE ARE NO TIES ON THE SURVEY.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,326.93' WEST TO THE IRON PIN HE SET FOR THE NORTH 1/8TH CORNER OF THE NW1/4 OF SECTION 9-19-11
 - 2) 2,653.86' WEST TO THE IRON PIN HE FOUND AT THE NORTHWEST CORNER OF SECTION 9-19-11

- 25) LARGE SURVEY SR #04005 IN THE SURVEY DRAWER FOR SECTIONS 1-8 IN TOWNSHIP 19-11 FOR THE J. E. ARNDT PROPERTY IN THE NORTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 4-19-11 WITH NO NAME OR DATE SHOWS ON THE SURVEY DRAWING AN **IRON PIN** AT THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 4-19-11. THERE ARE NO TIES ON THE SURVEY.

- 26) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 19-11 SHOWS AN **IRON PIN** AT THE "S1/4 CORNER SECTION 04-19-11".
 - 1) 50' EAST TO A SPIKE & WASHER IN A GUY POLE
 - 2) 5.5' WEST TO A SPIKE & WASHER IN A POWER POLE
 - 3) 42' NORTH TO A SPIKE & WASHER IN A GUY POLE

CONTINUED ON PAGE 7

- 27) E. C. GOLDSMITH, COUNTY ENGINEER FROM 1944 TO 1949, IN LARGE SURVEY SR #04002 IN THE SURVEY DRAWER FOR SECTIONS 1-8 IN TOWNSHIP 19-11 DATED AUGUST 10, 1947, SHOWS ON HIS SURVEY DRAWING AN **IRON PIN** AT THE SOUTH 1/4 CORNER OF SECTION 4-19-11. THERE ARE NO TIES ON THE SURVEY.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,651.88' NORTH TO THE STONE HE FOUND AT THE CENTER CORNER OF SECTION 4-19-11
- 28) KRETSINGER REFERENCE TIE BOOK 13 ON PAGE 100 SHOWS A **PIN** AT THE "S1/4 CORNER SECTION 4-19-11" UNDER THE HEADING "KANSAS HIGHWAY COMMISSION SECTION LINE TIES FOR PROJECT 50S-56 F I608 (5)".
- 1) 50.0' EAST TO A SPIKE & WASHER IN A GUY POLE
 - 2) 5.5' WEST TO A SPIKE & WASHER IN A POWER POLE
 - 3) 42.0' NORTH TO A SPIKE & WASHER IN A GUY POLE
- 29) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 19-11 SHOWS AN **IRON PIN** AT THE "N1/4 CORNER SECTION 9-19-11".
- 1) 49.5' EAST TO A SPIKE IN A GUY POLE
 - 2) 11.2' WEST TO A STEEL FENCE
- 30) IN A FIELD BOOK LABELED "TOPOGRAPHY N 1/4 SECTION 9-19-11" IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE, IT SHOWS A **5/8" REBAR** AT THE NORTH 1/4 CORNER OF SECTION 9-19-11 FROM THE TOPOGRAPHY NOTES OF THE TED W. LORD PROPERTY. THERE IS NO DATE ON THE SURVEY NOTES.
- 1) 49.5' EAST TO A SPIKE IN A GUY POLE
 - 2) 11.2' WEST TO A CEMETERY FENCE BEARING NORTH-SOUTH
 - 3) 41.5' NORTH TO A TELEPHONE POLE
 - 4) 4.0' WEST TO A TELEPHONE POLE
- 31) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F04034 IN THE SURVEY FILE FOR SECTIONS 1-8 IN TOWNSHIP 19-11 SHOWING THE RESULTS OF A SURVEY OF THE WEST 330 FEET OF THE SOUTH 1/2 OF THE SOUTH 1/2 OF THE NORTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 4-19-11 DATED NOVEMBER 2, 1959 SHOWS ON HIS SURVEY DRAWING A "**MONUMENT**" AT THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 4-19-11. THERE IS NO DESCRIPTION OF THE MONUMENT AND THERE ARE NO TIES ON THE SURVEY.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,326.57' WEST TO THE THEORETICAL POSITION FOR THE SOUTH 1/16TH CORNER OF THE SW1/4 OF SECTION 4-19-11
 - 2) 2,653.13' WEST TO THE "MONUMENT" AT THE SOUTHWEST CORNER OF SECTION 4-19-11 – NOT DESCRIBED
 - 3) 1,325.2' NORTH TO THE "MONUMENT" AT THE EAST 1/16TH CORNER OF THE SW1/4 OF SECTION 4-19-11 – NOT DESCRIBED
 - 4) 2,650.4' NORTH TO THE "MONUMENT" AT THE NORTHEAST CORNER OF THE SW1/4 OF SECTION 4-19-11 – NOT DESCRIBED
- 32) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN LARGE SURVEY SR #09018 IN THE SURVEY DRAWER FOR SECTIONS 9 & 10 IN TOWNSHIP 19-11, DATED MAY 25, 1961, SHOWS A "**MONUMENT**" AT THE NORTHWEST CORNER OF THE NORTHEAST 1/4 OF SECTION 9-19-11. HE DOES NOT DESCRIBE THE MONUMENT AND THERE ARE NO TIES ON THE SURVEY.
- 33) KDOT PLANS FOR I-35 BY-PASS FROM 1963: PROJECT 35-56-I35-2 (1) (127)/50-56-F050-5 (5), PAGE 20, SHOWS A **5/8" REBAR** AT THE NORTH 1/4 CORNER OF SECTION 9-19-11. TIES ARE ON PAGE 8

- 1) 2,649.2' SOUTH OF THE CENTER CORNER OF SECTION 4-19-11
 - 2) 50.0' EAST TO A SPIKE & WASHER IN A GUY POLE
 - 3) 5.5' WEST TO A SPIKE & WASHER IN A POWER POLE
 - 4) 42.0' NORTH TO A SPIKE & WASHER IN A POWER POLE
- 34) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 11, 1992, SAID THAT **HE FOUND A 3/4" IRON PIN** AT THE NORTH 1/4 CORNER OF SECTION 9-19-11.
- 1) 33.7' SW TO THE NORTHEAST CORNER OF "FREMONT ROGERS" TOMBSTONE
 - 2) 29.7' EAST TO THE CENTER SEAM OF *LINCOLN STREET*
 - 3) 4.65' WEST TO THE CENTER OF A POWER POLE
- 35) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 17, 1992 AND DECEMBER 18, 1992, FOR JOB NUMBER 92180-03, A SURVEY OF THE FOUR SEASONS COMPLEX, SAID THAT **HE FOUND THE 5/8" REBAR** AT THE SOUTH 1/4 CORNER OF SECTION 4-19-11 FROM HIS EXISTING REFERENCE TIES ON FILE AT THE COUNTY ENGINEER'S OFFICE DATED FEBRUARY 1992.
- 1) 34.0' SW TO THE NORTHEAST CORNER OF "FREMONT ROGERS" TOMBSTONE
 - 2) 56.4' NNW TO THE SOUTHEAST CORNER OF "URIAH TIGERS" TOMBSTONE
 - 3) 4.55' WEST TO A NAIL & BOTTLE CAP IN A POWER POLE
 - 4) 30.0' EAST TO THE CENTERLINE TRAVELED WAY OF *LINCOLN STREET*
- 36) STEVEN S. BROSEMER, P.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MAY 12, 2015 FOR PROJECT NUMBER 15104-02, THE SURVEY OF LOTS 24, 25 & 26 IN THE CONTINUATION OF BERKELEY HILLS, AN ADDITION TO THE CITY OF EMPORIA, FOR CHRIS STANLEY, SAID THAT **HE FOUND THE RECORD 5/8" IRON PIN** AT THE NORTH 1/4 CORNER OF SECTION 9-19-11 FROM HIS EXISTING REFERENCE TIES ON FILE AT THE COUNTY SURVEYORS OFFICE FROM HIS PROJECT NUMBER 92180 IN 1992.
- 1) 5.8' WSW TO A CONCRETE NAIL & BOTTLECAP IN THE SOUTH SIDE OF A POWER POLE
 - 2) 34.0' SW TO THE NORTHEAST CORNER OF "FREMONT ROGERS" TOMBSTONE
 - 3) 56.4' NNW TO THE SOUTHEAST CORNER OF "URIAH TIGERS" TOMBSTONE
 - 4) 30.0' EAST TO THE TRAVELED WAY OF *LINCOLN STREET*

NORTH QUARTER CORNER SECTION 09-19-11