

**NORTH 1/16TH CORNER NORTHWEST QUARTER OF SECTION 09, TOWNSHIP 19 SOUTH,
RANGE 11 EAST**

- 1) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 4, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 184 DATED MAY 1, 1900 ORDERED BY W. W. JONES, J. W. McCULLOCH, AND FRED STUCKEY TO ESTABLISH THE WEST BOUNDARY OF THE NORTHWEST 1/4 OF THE NORTHEAST 1/4 OF THE NORTHWEST 1/4 OF SECTION 9-19-11, SAID THAT **HE SET AN 18" X 12" X 4" STONE "DRESSED ON ONE SIDE"** FOR THE PERMANENT NORTHWEST CORNER OF THE NORTHEAST 1/4 OF THE NORTHWEST 1/4 OF SECTION 9-19-11 ON THIS **LEGAL SURVEY**.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 20.10 CHAINS WEST TO THE STONE HE FOUND AT THE CORNER COMMON TO SECTIONS 4, 5, 8 & 9
 - 2) 20.11 CHAINS EAST TO THE 18" X 10" X 5" STONE DRESSED ON ONE SIDE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SEC. 9
 - 3) 30.15 CHAINS EAST TO A STONE HE FOUND MARKED "JAY"
 - 4) 60.32 CHAINS EAST TO THE THEORETICAL LOCATION FOR THE NORTHEAST CORNER OF SECTION 9 AT A POINT 9 LINKS SOUTH AND 4 LINKS WEST OF A FENCE POST – NO STONE FOUND
 - 5) 100.12 CHAINS EAST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 10
 - 6) 10.01 CHAINS SOUTH TO THE 18" X 12" X 4" STONE DRESSED ON ONE SIDE HE SET FOR THE PERMANENT SOUTHWEST CORNER OF THE NW1/4 OF THE NE1/4 OF THE NW1/4 OF SECTION 10
 - 7) 20.03 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF THE NE1/4 OF THE NW1/4 OF SECTION 10
- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 40, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 221 DATED MARCH 15, 1902 ORDERED BY I. O. O. F. LODGE NUMBER 15 TO SURVEY 11 ACRES OFF OF THE SOUTH SIDE OF THE NORTH 1/2 OF THE SOUTHEAST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 4-19-11, SAID THAT **HE FOUND THE STONE** AT THE 1/8TH CORNER ON THE SOUTH LINE OF THE SOUTHWEST 1/4 OF SECTION 4-19-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 22, AND ADDITIONAL INFORMATION IS IN PACKET "M 123" IN MISCELLANEOUS DRAWER NUMBER 5 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 10.03-1/4 CHAINS NORTH TO THE 1" X 24" IRON PIN HE SET ON THIS SURVEY
 - 2) 15.55 CHAINS NORTH TO THE 1" X 24" IRON PIN HE SET ON THIS SURVEY
 - 3) 30.10 CHAINS NORTH TO A TREE AT THE SOUTHWEST CORNER OF THE N1/2 OF THE NE1/4 OF THE SW1/4 OF SECTION 4
- 3) E. C. GOLDSMITH, COUNTY ENGINEER FROM 1944 TO 1949, BY W. D. KRETSINGER, L.S. 363, IN AN **INFORMAL SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 157 FOR A SURVEY THE EAST 1/2 OF THE SOUTHEAST 1/4 OF THE NORTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 9-19-11 FOR THE EMPORIA MEMORIAL POST NO. 7957 OF THE VETERANS OF FOREIGN WARS, SAID THAT HE DETERMINED A **TEMPORARY POINT** FOR THE 1/8TH CORNER ON THE NORTH SIDE OF THE NORTHWEST 1/4 OF SECTION 9-19-11 ON THIS **INFORMAL SURVEY**. A PENCIL NOTE INDICATES THAT THE SURVEY WAS COMPLETED ON JULY 28, 1947, BUT THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

HIS INFORMATION IS CONTINUED ON PAGE 2

- 1) 1,326.93' WEST TO THE IRON PIN HE FOUND AT THE NORTHWEST CORNER OF SECTION 9
 - 2) 1,326.93' EAST TO THE NORTH 1/4 CORNER OF SECTION 9
 - 3) 660.8' SOUTH TO THE IRON PIN HE SET FOR THE NORTHEAST TRACT CORNER
 - 4) 1,291.6' SOUTH TO THE IRON PIN HE SET FOR THE SOUTHEAST TRACT CORNER ON THE NORTH RIGHT-OF-WAY LINE OF 15TH AVENUE
 - 5) 1,321.6' SOUTH TO A TEMPORARY POINT HE SET FOR THE CENTER OF THE NW1/4 OF SECTION 9
- 4) LARGE SURVEY SR #04005 IN THE SURVEY DRAWER FOR SECTIONS 1-8 IN TOWNSHIP 19-11 FOR THE J. E. ARNDT PROPERTY IN THE NORTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 4 WITH NO NAME OR DATE SHOWS AN **IRON PIN** AT THE 1/16TH CORNER ON THE SOUTH SIDE OF THE SW1/4 OF SECTION 4-19-11. THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES.
THE SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,326.57' WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 4
 - 2) 1,326.57' EAST TO THE IRON PIN AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 4
- 5) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F04034 IN THE SURVEY FILE FOR SECTIONS 1-8 IN TOWNSHIP 19-11 SHOWING THE RESULTS OF A SURVEY OF THE WEST 330 FEET OF THE SOUTH 1/2 OF THE SOUTH 1/2 OF THE NORTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 4-19-11 DATED NOVEMBER 2, 1959 SHOWS ON HIS SURVEY DRAWING SHOWS THAT HE DETERMINED A **THEORETICAL POSITION** FOR THE 1/16TH CORNER ON THE SOUTH SIDE OF THE SOUTHWEST 1/4 OF SECTION 4-19-11 TO BE ON TRUE LINE AND HALFWAY BETWEEN THE SOUTHWEST CORNER AND THE SOUTH 1/4 CORNER OF SECTION 4, BUT IT WAS **NOT** MONUMENTED ON THIS SURVEY.
HIS SURVEY DRAWING SHOWS THE FOLLOWING DISTANCES:
- 1) 1,326.56' WEST TO THE "MONUMENT" AT THE SOUTHWEST CORNER OF SECTION 4 – NOT DESCRIBED
 - 2) 1,326.57' EAST TO THE "MONUMENT" AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 4 – NOT DESCRIBED
 - 3) 1,324.56' NORTH TO THE THEORETICAL POSITION FOR THE CENTER OF THE SW1/4 OF SECTION 4
 - 4) 2,651.13' NORTH TO THE "MONUMENT" AT THE 1/16TH CORNER ON THE NORTH SIDE OF THE SW1/4 OF SECTION 4 – NOT DESCRIBED

NORTH SIXTEENTH CORNER NORTHWEST QUARTER SECTION 09-19-11