

**WEST 1/16<sup>TH</sup> CORNER NORTHEAST QUARTER OF SECTION 09, TOWNSHIP 19 SOUTH, RANGE 11 EAST**

- 1) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE LEFT PAGE 204 DATED JULY 26, 1881, FOR A COUNTY ROAD IN TOWNSHIP 19-11, APPARENTLY **FOUND THE STONE** AT THE NORTHWEST CORNER OF THE SOUTH 1/2 OF THE NORTHEAST 1/4 OF SECTION 9-19-11 TO END THIS ROAD SURVEY.
  
- 2) E. C. GOLDSMITH, COUNTY ENGINEER FROM 1944 TO 1949, BY W. D. KRETSINGER, L.S. 363, IN AN **INFORMAL SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 156 TO ESTABLISH THE RIGHT-OF-WAY LINES OF THE PROPOSED GRAND STREET BETWEEN 12<sup>TH</sup> AND 15<sup>TH</sup> AVENUES IN THE NORTHWEST 1/4 OF SECTION 9-19-11 IN THE CITY OF EMPORIA, SAID THAT **HE DROVE A 3/8" IRON PIN** AT THE 1/8<sup>TH</sup> CORNER ON THE EAST SIDE OF THE NORTHEAST 1/4 OF SECTION 9-19-11 AT THE INTERSECTION OF 15<sup>TH</sup> AVENUE AND LINCOLN STREET ON THIS **INFORMAL SURVEY**. HE SET THIS CORNER ON LINE AND HALFWAY BETWEEN THE IRON PIN FOUND AT THE NORTH 1/4 CORNER AND THE IRON PIN THAT HE FOUND AT THE CENTER CORNER OF SECTION 9. THERE ARE NO TIES ON THE SURVEY.  
**HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**
  - 1) 1,321.6' SOUTH TO THE IRON PIN HE FOUND AT THE CENTER CORNER OF SECTION 9 IN LINCOLN STREET AND 12<sup>TH</sup> AVENUE
  - 2) 1,321.5' NORTH TO THE IRON PIN HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 9
  - 3) 2,653.0' WEST TO AN IRON PIN HE SET FOR THE 1/8<sup>TH</sup> CORNER ON THE WEST SIDE OF THE NW1/4 OF SECTION 9
  
- 3) E. C. GOLDSMITH, COUNTY ENGINEER FROM 1944 TO 1949, BY W. D. KRETSINGER, L.S. 363, IN AN **INFORMAL SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 157 FOR A SURVEY THE EAST 1/2 OF THE SOUTHEAST 1/4 OF THE NORTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 9-19-11 FOR THE EMPORIA MEMORIAL POST NO. 7957 OF THE VETERANS OF FOREIGN WARS SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE 1/8<sup>TH</sup> CORNER** ON THE EAST SIDE OF THE NORTHWEST 1/4 OF SECTION 9-19-11 ON THIS **INFORMAL SURVEY**. HE DOES NOT IDENTIFY THE MONUMENT AND THERE ARE NO TIES ON THE SURVEY. A PENCIL NOTE INDICATES THAT THE SURVEY WAS COMPLETED ON JULY 28, 1947.  
**HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**
  - 1) 1,326.50' WEST TO THE TEMPORARY POINT HE SET FOR THE CENTER OF THE NW1/4 OF SECTION 9
  - 2) 2,653.0' WEST TO THE IRON PIN HE FOUND AT THE SOUTHWEST CORNER OF THE NW1/4 OF THE NW1/4 OF SECTION 9
  
- 4) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY SR #9031 IN THE LARGE SURVEY DRAWER FOR SECTIONS 9 & 10 IN TOWNSHIP 19-11, DATED FEBRUARY 16, 1960, SHOWS ON HIS SURVEY DRAWING A **"MONUMENT"** AT THE SOUTHEAST CORNER OF THE NORTHEAST 1/4 OF THE NORTHWEST 1/4 OF SECTION 9-19-11. HE DOES NOT IDENTIFY THE MONUMENT AND THERE ARE NO TIES ON THE SURVEY.
  
- 5) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN LARGE SURVEY SR #9018 IN THE LARGE SURVEY DRAWER FOR SECTIONS 9 & 10 IN TOWNSHIP 19-11, DATED MAY 25, 1961, SHOWS ON HIS SURVEY DRAWING A **"MONUMENT"** AT THE SOUTHWEST CORNER OF THE NORTH 1/2 OF THE NORTHEAST 1/4 OF SECTION 9-19-11. HE DOES NOT IDENTIFY THE MONUMENT AND THERE ARE NO TIES ON THE SURVEY.

CONTINUED ON PAGE 2

- 6) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F09087 IN THE SURVEY FILE FOR SECTION 9 IN TOWNSHIP 19-11 FOR A SURVEY OF A TRACT IN THE SOUTHEAST 1/4 OF THE NORTHEAST 1/4 OF THE NORTHEAST 1/4 OF SECTION 9-19-11 DATED OCTOBER 2, 1973, SHOWS ON HIS SURVEY DRAWING A "MONUMENT" AT THE SOUTHWEST CORNER OF THE NORTHWEST 1/4 OF THE NORTHEAST 1/4 OF SECTION 9-19-11 AT THE INTERSECTION OF 15<sup>TH</sup> AVENUE AND LINCOLN STREET. HE DOES NOT IDENTIFY THE MONUMENT AND THERE ARE NO TIES ON THE SURVEY.
- 7) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED SEPTEMBER 24, 2002, FOR PROJECT NUMBER 02086-02, SURVEY F09189 IN THE SURVEY FILE FOR SECTION 9 IN TOWNSHIP 19-11 FOR A 1.433 ACRE TRACT IN THE NORTHWEST QUARTER OF THE NORTHWEST QUARTER OF SECTION 9-19-11, SAID THAT **SHE FOUND A PLUS CUT IN THE PAVEMENT AT THE INTERSECTION OF 15<sup>TH</sup> AVENUE AND LINCOLN STREET** AT THE EAST 1/16<sup>TH</sup> CORNER OF THE NORTHWEST 1/4 OF SECTION 9-19-11 FROM A PREVIOUS SURVEY BY STEVEN S. BROSEMER, L.S. 752, [PROJECT 91316]. SHE SAID THAT BROSEMER SET THIS CORNER FOR SAID SURVEY.
- 1) 36.20' SE TO A CONCRETE NAIL & WASHER IN A POWER POLE
  - 2) 66.35' SW TO A CONCRETE NAIL & WASHER IN A POWER POLE
  - 3) 30.50' NORTH TO A PIPE IN A CONCRETE BASE FOR A FLAG POLE
  - 4) 20.40' WEST TO THE CENTER SEAM FOR LINCOLN STREET TO THE SOUTH
  - 5) 1.60' EAST TO THE CENTER SEAM FOR LINCOLN STREET TO THE NORTH
  - 6) 30.30' SOUTH TO THE CENTER SEAM OF 15<sup>TH</sup> AVENUE EAST AND WEST
- HER SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,326.60' WEST TO THE CONCRETE NAIL & WASHER SHE SET IN PAVEMENT FOR THE SOUTHEAST CORNER OF THE NW1/4 OF THE NW1/4 OF SECTION 9
  - 2) 1,658.25' WEST TO THE CONCRETE NAIL & WASHER SHE SET IN PAVEMENT FOR THE SOUTHEAST CORNER OF THE W1/2 OF THE SE1/4 OF THE NW1/4 OF THE NW1/4 OF SECTION 9
  - 3) 2,192.25' WEST TO THE CONCRETE NAIL & WASHER SHE SET IN PAVEMENT FOR THE SOUTHEAST CORNER OF THE 1.433 ACRE TRACT
  - 4) 2,423.20' WEST TO THE CONCRETE NAIL & WASHER SHE SET IN PAVEMENT FOR THE SOUTHWEST CORNER OF THE 1.433 ACRE TRACT
  - 5) 2,653.20' WEST TO THE CONCRETE NAIL & WASHER SHE SET IN PAVEMENT FOR THE SOUTHWEST CORNER OF THE NW1/4 OF THE NW1/4 OF SECTION 9 AT THE INTERSECTION OF 15<sup>TH</sup> AVENUE AND PRAIRIE STREET

WEST SIXTEENTH CORNER NORTHEAST QUARTER SECTION 09-19-11