

NORTHWEST CORNER SECTION 10, TOWNSHIP 19 SOUTH, RANGE 11 EAST

- 1) ON PAGE 369 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 21" X 18" X 2"** FOR THE CORNER TO SECTIONS 3, 4, 9 & 10-19-11.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS NORTH TO THE 21" X 18" X 2" SANDSTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 3 & 4-19-11
 - 2) 79.49 CHAINS NORTH TO THE 19" X 15" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 3 & 4-19-11
 - 3) 39.80 CHAINS EAST TO THE 28" X 14" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTION 3 & 10-19-11
 - 4) 79.60 CHAINS EAST TO THE 17" X 12" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 2, 3, 10 & 11-19-11

- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 118 RECORDED IN SURVEY BOOK "A" ON PAGE 206 DATED MAY 22, 1869 TO SURVEY 5 ACRES OF LAND IN THE NORTH 1/2 OF THE NORTHEAST 1/4 OF SECTION 9-19-11, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 9-19-11 ON THIS SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 159 RODS, 10 LINKS SOUTH TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 9-19-11

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 44, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 43 DATED JUNE 14, 1870 TO ESTABLISH THE CORNER TO SECTIONS 2, 3, 10 & 11-19-11, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 10-19-11 ON THIS **PERMANENT SURVEY**.

- 4) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 97, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 97 DATED APRIL 28, 1885 ORDERED BY D. L. COOK TO ESTABLISH THE NORTH 1/4 CORNER OF SECTION 10-19-11, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 10-19-11 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,624' EAST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 10-19-11
 - 2) 5,248' EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 10-19-11

- 5) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 105, A ROAD SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 105 DATED JUNE 2, 1885 FOR J. P. SIEVER, PRINCIPLE PETITIONER FOR A ROAD IN SECTION 4-19-11, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 4-19-11 TO END THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINE FOR 1,290' TO A ROAD STONE HE SET FOR AN ANGLE IN THE ROAD TO THE NORTHWEST

- 6) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 4, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 184 DATED MAY 1, 1900 ORDERED BY W. W. JONES, J. W. McCULLOCH, AND FRED STUCKEY TO ESTABLISH THE WEST BOUNDARY OF THE NORTHWEST 1/4 OF THE NORTHEAST 1/4 OF THE NORTHWEST 1/4 OF SECTION 9-19-11, SAID THAT HE SEARCHED FOR THE STONE AT THE NORTHEAST CORNER OF SECTION 9-19-11, BUT

HE DID **NOT** FIND THE STONE. HE DID **NOT** RESET THE NORTHEAST CORNER OF SECTION 9-19-11 ON THIS **PERMANENT SURVEY**. HE MARKED A **TEMPORARY POINT** 9 LINKS SOUTH AND 4 LINKS WEST OF A FENCE POST AFTER RUNNING THE SECTION LINES FROM THE STONE THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 9-19-11 EAST TO THE STONE THAT HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 10-19-11.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 39.80 CHAINS EAST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 10-19-11
 - 2) 20.16 CHAINS WEST TO THE STONE HE FOUND MARKED "JAY"
 - 3) 40.21 CHAINS WEST TO THE 18" X 10" X 5" STONE DRESSED ON ONE SIDE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 9-19-11
 - 4) 60.32 CHAINS WEST TO THE 18" X 12" X 4" STONE DRESSED ON ONE SIDE HE SET FOR THE PERMANENT NORTHWEST CORNER OF THE NE1/4 OF THE NW1/4 OF SECTION 9-19-11
 - 5) 80.42 CHAINS WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 9-19-11
- 7) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 39, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 220 DATED MARCH 10-14, 1902 ORDERED BY CHRISTIAN THRASHER FOR A SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CENTER OF SECTION 4-19-11 AND ALSO THE CORNERS AND BOUNDARIES OF THE NORTH 1/2 OF THE NORTH 1/2 OF THE SOUTHWEST 1/4 OF SAID SECTION 4 AND RUN SUCH LINES AS ARE NECESSARY TO PROPERLY COMPLETE THE SURVEY. THE NORTH AND EAST LINES OF THE SOUTHWEST 1/4 OF SECTION 3-19-11 WILL ALSO BE LOCATED AND ESTABLISHED. **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 3-19-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 16, AND ADDITIONAL INFORMATION IS IN PACKET "M 123" IN MISCELLANEOUS DRAWER NUMBER 5 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 39.80 CHAINS NORTH TO THE 14" X 12" X 3" STONE HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 3-19-11
 - 2) 79.10 CHAINS NORTH TO THE STONE HE FOUND LOOSE IN THE GROUND AT THE NORTHWEST CORNER OF SECTION 3-19-11
- 8) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 153 DATED MAY 19, 1903 ORDERED BY HERMAN WHITE, ET. AL. FOR A SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THAT PORTION OF NORMAL ADDITION TO THE CITY OF EMPORIA LYING NORTH OF WALNUT STREET, AND ALSO THE CORNERS AND BOUNDARIES OF LOTS NUMBER 30 & 31 IN SAID ADDITION, SAID THAT **HE FOUND AN IRON SUPPOSED TO BE** THE NORTHWEST CORNER OF SECTION 10-19-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 158, AND ADDITIONAL INFORMATION IS IN PACKET "M 128" IN MISCELLANEOUS DRAWER NUMBER 7 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 1,324' SOUTH TO THE STONE HE FOUND AT THE 1/2/4 CORNER ON THE WEST SIDE OF THE NW1/4 OF SECTION 10-19-11
- 2) 2,648' SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF THE NW1/4 OF SECTION 10-19-11
- 3) 1,147' EAST TO THE IRON PIN HE FOUND AT THE NORTHWEST CORNER OF NORMAL ADDITION

HIS INFORMATION IS CONTINUED ON PAGE 3

- 4) 2,075' EAST TO THE STAKE AND IRON PIN HE FOUND AT THE NORTHEAST CORNER OF NORMAL ADDITION
 - 5) 2,626' EAST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 10-19-11
- 9) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 174 AND DATED MAY 1904, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 10-19-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK 2 ON PAGE 48 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 15" IN MISCELLANEOUS DRAWER NUMBER 1 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.
- 10) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY FOR ROAD NUMBER 667 RECORDED IN ROAD RECORD BOOK "E" ON PAGE 24 PETITIONED BY F. C. NEWMAN AND OTHERS FOR A ROAD IN TOWNSHIP 19-11 [PACKET 779 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT WAS VIEWED BY THE COUNTY COMMISSIONERS AND THE COUNTY SURVEYOR ON DECEMBER 14, 1911 AND WAS GRANTED ON JANUARY 5, 1912 AS NOTED BY J. A. CLEMMER, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, ATTESTED BY O. K. MILLER, COUNTY CLERK, AND RECORDED ON JANUARY 15, 1912 BY MATTHEW BROWN, COUNTY SURVEYOR BY J. MAX YINGLING, DEPUTY, SAID THAT **HE FOUND THE STONE SET FIRMLY IN THE GROUND** AT THE SOUTHWEST CORNER OF THE SOUTHWEST 1/4 OF SECTION 3-19-11 ON THIS ROAD SURVEY.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS WEST FOR A 1/2 MILE TO THE STONE SET FIRMLY IN THE GROUND AT THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF SECTION 4-19-11 TO BEGIN THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS EAST FOR 2,098 FEET TO THE ROAD RUNNING IN A PRACTICALLY NORTH AND SOUTH DIRECTION THROUGH SAID QUARTER SECTION KNOWN AS THE MERCHANT STREET ROAD AND TERMINATING THERE
 - 3) SAID ROAD TO BE 40 FEET WIDE, ALL ON THE NORTH SIDE OF THE ABOVE LINE AS DESCRIBED
- 11) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 89 FOR THE RECORD OF A PUBLIC ROAD VIEWED AND ALLOWED BY THE COUNTY COMMISSIONERS AND RECORDED IN VOLUME "E" ON PAGE 24 OF THE ROAD RECORDS, SAID THAT **HE FOUND THE STONE SET FIRMLY IN THE GROUND** AT THE SOUTHWEST CORNER OF THE SOUTHWEST 1/4 OF SECTION 3-19-11 ON THIS ROAD SURVEY.
HIS FIELD NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS WEST FOR A 1/2 MILE TO THE STONE SET FIRMLY IN THE GROUND AT THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF SECTION 4-19-11 TO BEGIN THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS EAST FOR 2,098 FEET TO THE ROAD RUNNING IN A PRACTICALLY NORTH AND SOUTH DIRECTION THROUGH SAID QUARTER SECTION KNOWN AS THE MERCHANT STREET ROAD, AND TERMINATING THERE
 - 3) SAID ROAD TO BE 40 FEET WIDE ALL ON THE NORTH SIDE OF THE ABOVE LINE AS DESCRIBED
 - 4) THE CHAIRMAN OF THE ROAD COMMISSIONERS WAS NOTIFIED ON JANUARY 13, 1912

CONTINUED ON PAGE 4

- 5) THE SURVEY WAS ENTERED ON THE 16TH DAY OF JANUARY, 1912 BY MATTHEW BROWN, COUNTY SURVEYOR, BY J. MAX YINGLING, DEPUTY
- 12) COMMISSIONER'S ROAD JOURNAL BOOK "A", PAGE 4
ON NOVEMBER 6, 1911 A PETITION SIGNED BY F. C. NEWMAN AND OTHERS FOR THE LOCATION OF A ROAD IN TOWNSHIP 19-11 WAS PRESENTED TO THE BOARD OF COUNTY COMMISSIONERS. THE ROAD WAS VIEWED ON DECEMBER 14, 1911, AND THE FINAL ORDER FOR THE LOCATION OF THE FOLLOWING ROAD WAS ISSUED ON JANUARY 15, 1912.
- 1) BEGINNING AT THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF SECTION 4-19-11; FROM THENCE DUE EAST ALONG THE SOUTH LINE OF SAID QUARTER SECTION AND CONTINUING ALONG DUE EAST ON THE SOUTH LINE OF THE SOUTHWEST 1/4 OF SECTION 3-19-11 TO THE PUBLIC HIGHWAY RUNNING APPROXIMATELY NORTH AND SOUTH THROUGH SAID LAS NAMED QUARTER SECTION KNOWN AS THE MERCHANT STREET ROAD AND TERMINATING THERE
 - 2) SAID ROAD TO BE 40 FEET WIDE, ALL ON THE NORTH SIDE OF THE ABOVE DESCRIBED LINE
- 13) O. D. HENRY, COUNTY ENGINEER FROM 1929 TO 1944, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 100 UPON RECEIPT OF A NOTICE FOR AN OFFICIAL SURVEY OF CERTAIN PARTS OF THE LAND OWNED BY THE STATE OF KANSAS AND OCCUPIED BY THE KANSAS STATE TEACHER'S COLLEGE, BEING IN THE NORTH 1/2 OF SECTION 10-19-11, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 10-19-11 ON THIS **PERMANENT SURVEY**. HE BEGAN THE SURVEY ON NOVEMBER 7, 1931 AND SIGNED THE SURVEY ON DECEMBER 1, 1931. THERE ARE NO TIES ON THE SURVEY.
- 14) IN A FIELD BOOK LABELED "TOPOGRAPHY N 1/4 SECTION 9-19-11" IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE IT SHOWS A "**MARK ON TOP OF STONE WALL**" AT THE SOUTHWEST CORNER OF SECTION 3-19-11 FROM THE TOPOGRAPHY NOTES OF THE TED W. LORD PROPERTY. THERE WAS NO DATE ON THE NOTES.
- 1) 19.0' NORTH TO A SPLICED T. P. [TELEPHONE POLE]
 - 2) 19.7' SW TO THE NORTHEAST CORNER OF A CONCRETE SEWER BOX
 - 3) 5/8" REBARS FOR WITNESSES 2.7' NORTH AND 3.0' EAST OF THE MARK
 - 4) 5/8" REBAR SET 20.0' NORTH OF THE MARK
- 15) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 19-11 SHOWS AN "**X MARK ON A STONE WALL**" AT THE "SW CORNER SECTION 3-19-11"
- 1) 2.7' NORTH TO A 5/8" DIAMETER REBAR
 - 2) 3.0' EAST TO A 5/8" DIAMETER REBAR
- 16) E. C. GOLDSMITH, COUNTY ENGINEER FROM 1944 TO 1949, IN LARGE SURVEY SR #04002 IN THE LARGE SURVEY DRAWER FOR SECTIONS 1-8 IN TOWNSHIP 19-11 DATED AUGUST 10, 1947, SHOWS ON HIS SURVEY DRAWING AN "**X ON STONE WALL**" AT THE SOUTHEAST CORNER OF SECTION 4-19-11. THERE ARE NO TIES ON THE SURVEY.
- 17) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN LARGE SURVEY SR #9018 IN THE LARGE SURVEY DRAWER FOR SECTIONS 9 & 10 IN TOWNSHIP 19-11, DATED MAY 25, 1961, SHOWS ON HIS SURVEY DRAWING A "**MONUMENT**" AT THE NORTHEAST CORNER OF SECTION 9-19-11. HE DOES NOT IDENTIFY THE MONUMENT AND THERE ARE NO TIES ON THE SURVEY.

CONTINUED ON PAGE 5

- 18) KDOT PLANS FOR I-35 BY-PASS FROM 1963: PROJECT 35-56-I35-2 (1) (127)/50-56-F050-5 (5), PAGE 21, SHOWS A **PLUS (“+”) CUT IN A STONE WALL** AT THE NORTHWEST CORNER OF SECTION 10-19-11.
- 1) 2,633.8’ SOUTH OF EAST 1/4 CORNER OF SECTION 04-19-11
 - 2) 5/8” REBARS 3.0’ EAST AND 7.0’ NORTH
 - 3) 15.65’ WNW TO THE SOUTHEAST CORNER OF A 9’ X 9’ CONCRETE PUMP PIT
 - 4) 19.30’ NW TO THE NORTHEAST CORNER OF A 9’ X 9’ CONCRETE PUMP PIT
- 19) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY SR #10026 IN THE LARGE SURVEY DRAWER FOR SECTIONS 9 & 10 IN TOWNSHIP 19-11 DATED NOVEMBER 6, 1964, SHOWS ON HIS SURVEY DRAWING A **PLUS (“+”) MARK IN A STONE WALL** AT THE NORTHWEST CORNER OF SECTION 10-19-11. THERE ARE NO TIES ON THE SURVEY.
- 20) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JANUARY 31, 1997, FOR JOB NUMBER 95024-02, THE GPS SURVEY OF EMPORIA AND LOCAL AREAS, SAID THAT **SHE FOUND A 1/2” REBAR** AT THE NORTHWEST CORNER OF SECTION 10-19-11.
- 1) STATE PLANE COORDINATES IN U.S. FEET – GROUND LEVEL
NORTH = 1958821.952 EAST = 1974329.415
 - 3) 23.9’ SE TO THE NORTH END OF A RETAINING WALL
 - 3) 12.1’ SSW TO A NAIL & SHINER IN AN 8” DIAMETER PEAR TREE
 - 4) 2.0’ NORTH TO A NAIL & SHINER IN A POWER POLE
 - 5) 21.0’ NORTH TO THE CENTERLINE TRAVELED WAY OF 18TH STREET EAST-WEST
 - 6) 12.5’ EAST TO THE CENTERLINE TRAVELED WAY OF THE STREET SOUTH
- 21) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN SURVEY F10147 IN THE SURVEY FILE FOR SECTION 10 IN TOWNSHIP 19-11 FOR A SURVEY OF TRACTS IN THE NORTHWEST QUARTER OF SECTION 19-19-11 FOR PROJECT NUMBER 00059-02 DATED MARCH 22, 2000, AND SURVEY F10148 DATED APRIL 15, 2000, SHOWS ON HER SURVEY DRAWINGS THAT **SHE FOUND THE 1/2” REBAR** AT THE NORTHWEST CORNER OF THE NORTHWEST 1/4 OF SECTION 10-19-11. HER TIES ARE MISSING FROM THE SURVEY TIE FILES.
- HER SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,644.08’ SOUTH TO THE 5/8” REBAR INSIDE A 3/4" PIPE SHE FOUND IN A VALVE BOX AT THE SOUTHWEST CORNER OF THE NW1/4 OF SECTION 10-19-11, IN THE INTERSECTION OF *WEST STREET AND 12TH AVENUE*
- 22) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 15, 2000, FOR JOB NUMBER 00222-02, SURVEY F09188 IN THE SURVEY FILE FOR SECTIONS 9 IN TOWNSHIP 19-11 FOR A TRACT IN THE NORTHEAST QUARTER OF SECTION 9-19-11, SAID THAT **HE FOUND THE 1/2” REBAR** AT THE NORTHEAST CORNER OF SECTION 9-19-11 FROM EXISTING TIES ON FILE IN THE COUNTY ENGINEER’S OFFICE BY POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, DATED JANUARY 1997.
- 1) 2.0’ NORTH TO A NAIL & SHINER IN A POWER POLE
 - 2) 12.4’ SSW TO A NAIL & SHINER IN A BRADFORD PEAR TREE
 - 3) 3.9’ SE TO THE NORTH END OF A RETAINING WALL
 - 4) 21.0’ NORTH TO THE CENTERLINE TRAVELED WAY OF 18TH STREET EAST-WEST
 - 5) 12.5’ EAST TO THE CENTERLINE TRAVELED WAY OF THE STREET TO THE SOUTH
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,364.02’ SOUTH TO THE NORTHEAST CORNER OF THE SURVEYED TRACT, AS WITNESSED BY THE 1/2" REBAR WITH HIS “LS 752” CAP HE SET AT 30.00’ WEST
- HIS INFORMATION IS CONTINUED ON PAGE 6

- 2) 2,464.02' SOUTH TO THE SOUTHEAST CORNER OF THE SURVEYED TRACT, AS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET AT 30.00' WEST
 - 3) 2,644.02' SOUTH TO THE 1/2" REBAR IN A 1" PIPE IN A WELL HE FOUND AT THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 9-19-11 FROM A PREVIOUS SURVEY
- 23) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MAY 24, 2011 FOR PROJECT NUMBER 09015-02, THE *FINAL PLAT OF ESU ADDITION* TO THE CITY OF EMPORIA IN SECTIONS 3, 10 & 11-19-11, SAID THAT **HE FOUND THE 1/2" REBAR** AT THE NORTHWEST CORNER OF SECTION 10-19-11 FROM HIS EXISTING REFERENCE TIES ON FILE AT THE COUNTY SURVEYOR'S OFFICE DATED DECEMBER 2000.
- 1) 2.00' NORTH TO A NAIL & SHINER IN A POWER POLE
 - 2) 21.0' NORTH OT THE CENTERLINE TRAVELED WAY FOR *18TH AVENUE* TO THE EAST AND WEST
 - 3) 12.5' EAST TO THE CENTERLINE TRAVELED WAY FOR THE STREET TO THE SOUTH
 - 4) 17.80' WNW TO THE SOUTHWEST CORNER OF A CONCRETE SLAB AROUND A SANITARY SEWER MANHOLE
 - 5) 33.30' ENE TO THE SOUTHEAST CORNER OF A CONCRETE SLAB AROUND A SANITARY SEWER MANHOLE

NORTHWEST CORNER SECTION 10-19-11