

WEST 1/4 CORNER SECTION 10, TOWNSHIP 19 SOUTH, RANGE 11 EAST

- 1) ON PAGE 369 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 14" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 9 & 10-19-11.
- 2) G. M. WALKER, BRECKENRIDGE COUNTY SURVEYOR FROM 1857 TO 1860, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "A" ON PAGES 11 & 12 DATED DECEMBER 1 & 2, 1858, FOR THE COUNTY ROAD FROM EMPORIA VIA STUBBS FORD OF THE NEOSHO RIVER TO AMERICUS, SAID THAT **HE FOUND THE WEST 1/4 STONE POST** OF SECTION 10-19-11, BEING THE NORTHWEST CORNER OF EMPORIA, TO COMMENCE THIS ROAD SURVEY.
- 3) G. W. WALKER, BRECKENRIDGE COUNTY SURVEYOR, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 13 THROUGH 15 FOR THE "EMPORIA AND AMERICUS ROAD" SURVEYED DECEMBER 1 & 2, 1858, AND RECORDED IN THE COMMISSIONER'S JOURNAL ON PAGE 34 ON DECEMBER 6, 1858, SAID THAT **HE FOUND THE WEST STONE 1/4 POST** OF SECTION 10-19-11, BEING THE NORTHWEST CORNER OF EMPORIA TOWNSITE, ON THIS ROAD SURVEY. NO WIDTH IS RECORDED AND BY THE TERRITORIAL LAW IN EFFECT AT THE TIME THE ROAD WOULD BE FORTY FEET WIDE.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS SOUTHEASTERLY BY STREETS TO THE SOUTH 1/4 STONE POST OF SECTION 10-19-11 AT THE CROSSING OF *COMMERCIAL STREET* AND *SIXTH AVENUE* IN EMPORIA TO START THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS NORTHWESTERLY TO THE NORTH STONE 1/4 POST OF SECTION 9-19-11 AT A TURN TO THE WEST
- 4) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 118 RECORDED IN SURVEY BOOK "A" ON PAGE 206 DATED MAY 22, 1869 TO SURVEY 5 ACRES OF LAND IN THE NORTH 1/2 OF THE NORTHEAST 1/4 OF SECTION 9-19-11, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 9-19-11 ON THIS SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 159 RODS, 10 LINKS NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 9-19-11
- 5) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 29, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 29 DATED APRIL 25, 1870 TO ESTABLISH THE CORNERS OF THE NORTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 9-19-11, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 9-19-11 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,328' WEST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/2/4 CORNER OF THE SE1/4 OF SECTION 9-19-11
 - 2) 2,656' WEST TO THE FOUND CENTER POST OF SECTION 9-19-11
 - 3) 1,323' SOUTH TO THE STONE HE SET FOR THE PERMANENT EAST 1/2/4 CORNER OF THE SE1/4 OF SECTION 9-19-11
 - 4) 2,646' SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 9-19-11
- 6) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 188 TO 190 [PACKET 27 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY J. M. STEELE AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 19-11 THAT WAS

SURVEYED ON APRIL 22, 1871 AND WAS ORDERED ESTABLISHED IN PART AS A 60 FOOT WIDE ROAD AND IN PART VACATED AND RECORDED – REFERENCE BEING HAD TO ORDERS MADE BY THE COUNTY COMMISSION ON THE 4TH OF SEPTEMBER AND ALSO ON THE 10TH OF SEPTEMBER 1871 AS NOTED BY DAVID S. GILMORE, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 10-19-11, “BEING THE NORTHWEST CORNER OF EMPORIA TOWNSITE”, TO BEGIN THIS ROAD SURVEY. SEE THE RECORD FOR THE PORTION OF THE ROAD ALLOWED AND THE PORTION OF THE ROAD VACATED.

- 7) MATHEW BROWN, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY FOR ROAD NUMBER 318 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 222 TO 224 PETITIONED BY J. D. HOLDEN AND OTHERS FOR A ROAD IN TOWNSHIP 19-11 “COMMENCING AT THE CENTER CORNER OF SECTION 9-19-11 AND RUNNING EAST 1/2 MILE TO THE WEST LINE OF SECTION 10 IN SAME TOWNSHIP AND RANGE” [PACKET 570 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON NOVEMBER 25, 1886, SAID THAT **HE RECOGNIZED THE STONE** AT THE EAST 1/4 CORNER OF SECTION 9-19-11 AS THE TERMINUS OF THIS ROAD SURVEY. ON APRIL 13, 1886, THE BOARD OF COUNTY COMMISSIONERS APPROVED THE 80 FOOT WIDE ROAD FROM THE PLACE OF BEGINNING TO THE NORTHWEST CORNER OF LOT 4 OF MRS. LEWIS ADDITION TO THE CITY OF EMPORIA – THE BALANCE OF THE PETITION WAS REJECTED – AS NOTED BY T. E. McMILLAN, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND WAS RECORDED ON MAY 1, 1886 BY ROLAND LAKIN, COUNTY CLERK.
- 8) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN A ROAD SURVEY FOR ROAD NUMBER 451 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 69 THROUGH 72 PETITION BY R. S. LAWRENCE AND OTHERS FOR A ROAD IN TOWNSHIP 19-11 [PACKET 691 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON MAY 26, 1899, SAID THAT HE BEGAN THIS ROAD SURVEY AT A STONE MARKED “R” LOCATED **670 FEET WEST OF THE 1/4 SECTION CORNER** ON THE EAST LINE OF SECTION 9-19-11, THENCE EAST FOR 670 FEET TO SAID 1/4 SECTION CORNER, THENCE SOUTH ON THE EAST LINE OF SAID SECTION 200 FEET TO THE TERMINUS OF SAID ROAD. ON JULY 7, 1899 THE COMMISSION REVISION WAS BEGINNING AT A STONE MARKED “R” LOCATED 670 FEET WEST OF THE QUARTER SECTION CORNER ON THE EAST LINE OF SECTION 9-19-11, THENCE EAST 340 FEET, THENCE NORTH 30 FEET, THENCE WEST 340 FEET, THENCE SOUTH 30 FEET TO THE POINT OF BEGINNING, AS NOTED BY W. H. MAYES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, ATTESTED BY H. E. PEACH, COUNTY CLERK, AND RECORDED ON JANUARY 5, 1890 BY MATTHEW BROWN, COUNTY SURVEYOR.
- 9) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK “F” ON PAGE 153 DATED MAY 19, 1903 ORDERED BY HERMAN WHITE, ET. AL. FOR A SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THAT PORTION OF NORMAL ADDITION TO THE CITY OF EMPORIA LYING NORTH OF WALNUT STREET, AND ALSO THE CORNERS AND BOUNDARIES OF LOTS NUMBER 30 & 31 IN SAID ADDITION, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF THE NORTHEAST 1/4 OF SECTION 10-19-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 158, AND ADDITIONAL INFORMATION IS IN PACKET “M 128” IN MISCELLANEOUS DRAWER NUMBER 7 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
1) 1,324’ NORTH TO THE STONE HE FOUND AT THE WEST 1/2/4 CORNER OF THE N1/4 OF SECTION 10-19-11

HIS INFORMATION IS CONTINUED ON PAGE 3

- 2) 2,648' NORTH TO THE IRON HE FOUND THAT WAS SUPPOSED TO BE THE NORTHWEST CORNER OF SECTION 10-19-11
- 10) S. K. McCRARY, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 123, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 204 DATED APRIL 28, 1905 FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF LOTS 9, 10, 11 & 12 IN MRS. LEWIS ADDITION TO THE CITY OF EMPORIA ORDERED BY W. A. WILLIS, AGENT FOR THE OWNERS OF THE ABOVE PROPERTY, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF THE SOUTHEAST 1/4 OF SECTION 9-19-11 IN THE INTERSECTION OF 12TH AVENUE AND WEST STREET ON THIS **PERMANENT SURVEY**. THERE IS ADDITIONAL INFORMATION IN PACKET 100 IN MISCELLANEOUS DRAWER NUMBER 5 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 690.08' WEST TO THE STONE HE SET
 - 2) 1,325.4' WEST TO THE STONE HE SET FOR THE PERMANENT NORTHWEST CORNER OF MRS. LEWIS ADDITION
 - 3) 2,656.4' WEST TO THE STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 9-19-11
- 11) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 152, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 234 DATED SEPTEMBER 9, 1906 BY THE ORDER OF J. C. HOWARD, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF THE SOUTHWEST 1/4 OF SECTION 10-19-11 TO BEGIN THIS **PERMANENT SURVEY**. THERE IS ADDITIONAL INFORMATION IN PACKET "M 86" IN MISCELLANEOUS DRAWER NUMBER 4 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.
- 12) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK 1 ON PAGE 67, AT THE REQUEST OF MRS. D. B. TAYLOR, THROUGH HER DAUGHTER KATE TAYLOR, TO LOCATE THE CORNERS AND BOUNDARIES OF LOT 14 IN BURNETT'S ADDITION TO THE CITY OF EMPORIA, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF THE NORTHWEST 1/4 OF SECTION 10-19-11 ON THIS **PERMANENT SURVEY**. THE SURVEY WAS MADE MAY 23 & 25, 1910 AND WAS ENTERED ON AUGUST 12, 1910.
- 13) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, BY HOWARD E. BROWN, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY FOR ROAD NUMBER 684 RECORDED IN ROAD RECORD BOOK "E" ON PAGE 41 PETITIONED BY G. F. BLANKENSHIP AND OTHERS FOR A ROAD IN TOWNSHIP 19-11 [PACKET 931 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT WAS VIEWED BY THE COUNTY COMMISSIONERS AND THE DEPUTY COUNTY SURVEYOR ON SEPTEMBER 15, 1914, SAID THAT "ALL FOUR CORNERS TO THE SOUTHEAST QUARTER OF SECTION 9-19-11 WERE IN AT THE TIME THIS SURVEY WAS MADE, AND THE EAST LINE OF THE WEST 1/2 OF SAID QUARTER WAS MIDWAY BETWEEN THESE **STONES**, INDICATING THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 9-19-11 ON THIS ROAD SURVEY. THIS CORNER WAS NOT PART OF THE ROAD.
- 14) W. G. RUGGLES, COUNTY ENGINEER FROM 1915 TO 1928, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 173 DATED MARCH 30, 1918 ORDERED BY R. G. ROBERTS TO ESTABLISH THE LINE BETWEEN HIS PROPERTY AND THAT OF C. E. RAYMOND IN THE NORTHEAST 1/4 OF SECTION 9-19-11, SAID THAT **HE FOUND A GAS PIPE IN THE PAVEMENT** AT THE SOUTHEAST CORNER OF THE NORTHEAST 1/4 OF SECTION 9-19-11 IN THE INTERSECTION OF 12TH AVENUE AND WEST STREET ON THIS **PERMANENT SURVEY**.

- 15) O. D. HENRY, COUNTY ENGINEER FROM 1929 TO 1944, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 100 UPON RECEIPT OF A NOTICE FOR AN OFFICIAL SURVEY OF CERTAIN PARTS OF THE LAND OWNED BY THE STATE OF KANSAS AND OCCUPIED BY THE KANSAS STATE TEACHER'S COLLEGE, BEING IN THE NORTH 1/2 OF SECTION 10-19-11, SAID THAT **HE FOUND** THE WEST 1/4 CORNER OF SECTION 10-19-11 ON THIS **PERMANENT SURVEY**. HE DID NOT DESCRIBE THE MONUMENT, BUT HIS LEGEND INDICATES THAT IT WAS THE **"GOVERNMENT MONUMENT: STONE OR IRON ROD REPLACING STONE"**. HE BEGAN THE SURVEY ON NOVEMBER 7, 1931 AND SIGNED THE SURVEY ON DECEMBER 1, 1931. THERE ARE NO TIES ON THE SURVEY.
- 16) E. C. GOLDSMITH, COUNTY ENGINEER FROM 1944 TO 1949, BY W. D. KRETSINGER, L.S. 363, IN AN **INFORMAL SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 156 TO ESTABLISH THE RIGHT-OF-WAY LINES OF THE PROPOSED GRAND STREET BETWEEN 12TH AND 15TH AVENUES IN THE NORTHWEST 1/4 OF SECTION 9-19-11 IN THE CITY OF EMPORIA, SAID THAT **HE FOUND AN IRON PIN** AT THE EAST 1/4 CORNER OF SECTION 9-19-11 AT THE INTERSECTION OF 12TH AVENUE AND WEST STREET ON THIS **INFORMAL SURVEY**. THERE ARE NO TIES ON THE SURVEY.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,328.2' WEST TO THE IRON PIN HE FOUND AT THE NORTH 1/8TH CORNER OF THE SW1/4 OF SECTION 9-19-11 AT 12TH AVENUE AND CHESTNUT STREET
 - 2) 2,656.0' WEST TO THE IRON PIN HE FOUND AT THE CENTER CORNER OF SECTION 9-19-11 AT 12TH AVENUE AND LINCOLN STREET
 - 3) 5,310.5' WEST TO THE IRON PIN HE FOUND AT THE WEST 1/4 CORNER OF SECTION 9-19-11
- 17) AI CHAMNESS, DEPUTY COUNTY SURVEYOR FROM 1906 TO 1946, IN A BOOK LABELED NATIONAL 158 A "T2" IN THE KRETSINGER COLLECTION, ON PAGE 1 FOR A SURVEY FOR SAM LONG DATED JULY 12, 1944, SAID THAT HE SET A FLAG AT THE **"GOVERNMENT CORNER IN WEST STREET AND 12TH STREET"**. HE DOES NOT IDENTIFY THE MONUMENT AT THIS CORNER AND THERE ARE NO TIES ON THE SURVEY.
- 18) AI CHAMNESS, DEPUTY COUNTY SURVEYOR, IN A BOOK LABELED "CHAMNESS BOOK Y" IN THE KRETSINGER COLLECTION, ON PAGES 54 TO 55 FOR A SURVEY FOR SAM LONG DATED JULY 15, 1944, SAID THAT **HE SET A FLAG AT THE GOVERNMENT CORNER IN THE INTERSECTION OF 12TH AVENUE AND WEST STREET "MARKED BY AN IRON PIN OR A GAS PIPE"** AT THE WEST 1/4 CORNER OF SECTION 10-19-11. THERE ARE NO TIES ON THE SURVEY.
- 19) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 19-11 SHOWS AN **IRON PIN** AT THE "E1/4 CORNER SECTION 09-19-11".
- 20) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F09109 IN THE SURVEY FILE FOR SECTION 9 IN TOWNSHIP 19-11 FOR A TRACT IN THE NORTHEAST QUARTER OF SECTION 9-19-11 BUT NOT DATED, SHOWS ON HIS SURVEY DRAWING A "**MONUMENT**" AT THE SOUTHEAST CORNER OF THE NORTHEAST 1/4 OF SECTION 9-19-11 IN THE INTERSECTION OF 12TH AVENUE & WEST STREET. HE DOES NOT IDENTIFY THE MONUMENT AT THIS CORNER AND THERE ARE NO TIES ON THE SURVEY.
- 21) LESLIE M. GOULD, L.S. 142, DEPUTY COUNTY SURVEYOR, IN A LEGAL SURVEY RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 37 DATED JUNE 15, 1960 TO LOCATE THE BOUNDARIES OF LOT 165 ON WALNUT STREET IN WHITCOMB'S ADDITION, SHOWS ON HIS SURVEY DRAWING A **"SPIKE & WASHER IN**

PAVEMENT” AT THE NORTHEAST CORNER OF THE NORTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 9-19-11 AT THE INTERSECTION OF 12TH AVENUE AND WEST STREET ON THIS **PERMANENT SURVEY**. THERE ARE NO TIES ON THE SURVEY.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,328.2’ WEST TO THE SPIKE & WASHER IN PAVEMENT AT THE NORTHWEST CORNER OF THE NE1/4 OF THE SE1/4 OF SECTION 9-19-11
 - 2) 1,323.7’ SOUTH TO THE SPIKE & WASHER IN PAVEMENT AT THE SOUTHEAST CORNER OF THE NE1/4 OF THE SE1/4 OF SECTION 9-19-11
- 22) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 29, 1992, SAID THAT **HE FOUND A 1/2” SQUARE IRON PIN IN A 1” PIPE IN A WATER VALVE BOX MARKED “SURVEY PIN”** AT THE EAST 1/4 CORNER OF SECTION 9-19-11.
- 1) 53.7’ SE TO THE NORTHEAST CORNER OF A BUILDING
 - 2) 33.9’ NW TO A PK NAIL & WASHER IN A POWER POLE
 - 3) 54.0’ SE TO THE TOP OF A FIRE HYDRANT
 - 4) 5.0’ EAST TO THE CENTERLINE TRAVELED WAY OF THE ROAD TO THE SOUTH
 - 5) 1.5’ SOUTH TO THE CENTERLINE TRAVELED WAY OF THE ROAD EAST-WEST
- 23) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN SURVEY F10147 IN THE SURVEY FILE FOR SECTION 10 IN TOWNSHIP 19-11 FOR A SURVEY OF TRACTS IN THE NORTHWEST QUARTER OF SECTION 19-19-11 FOR PROJECT NUMBER 00059-02 DATED MARCH 22, 2000, AND SURVEY F10148 DATED APRIL 15, 2000, SHOWS ON HER SURVEY DRAWINGS THAT **SHE FOUND A 5/8” REBAR INSIDE A 3/4” PIPE IN A VALVE BOX** AT THE SOUTHWEST CORNER OF THE NORTHWEST 1/4 OF SECTION 10-19-11 AT THE INTERSECTION OF WEST STREET AND 12TH AVENUE. HER TIES HAVE APPARENTLY BEEN REMOVED FROM THE SURVEY TIE FILES.
- HER SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,644.08’ NORTH TO THE 1/2” REBAR SHE FOUND AT THE NORTHWEST CORNER OF SECTION 10-19-11
 - 2) 2,637.59’ EAST TO THE STONE SHE FOUND AT THE SOUTHEAST CORNER OF THE NW1/4 OF SECTION 10-19-11 IN THE INTERSECTION OF COMMERCIAL STREET AND 12TH AVENUE
- 24) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE LAND SURVEY REFERENCE REPORT DATED DECEMBER 15, 2000, FOR JOB NUMBER 00222-02, SURVEY F09188 IN THE SURVEY FILE FOR SECTIONS 9 IN TOWNSHIP 19-11 FOR A TRACT IN THE NORTHEAST QUARTER OF SECTION 9-19-11, SAID THAT **HE FOUND THE SQUARE 1/2” REBAR IN A 1” PIPE IN A WATER VALVE BOX MARKED “SURVEY PIN”** AT THE EAST 1/4 CORNER OF SECTION 9-19-11 FROM HIS EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE.
- 1) 53.7’ SW TO THE NORTHEAST CORNER OF A BUILDING
 - 2) 2.0’ SOUTH TO THE CENTERLINE TRAVELED WAY OF THE ROAD EAST-WEST
 - 3) 5.0’ EAST TO THE CENTERLINE TRAVELED WAY OF THE ROAD TO THE SOUTH
 - 4) 33.9’ NW TO A PK NAIL & SHINER IN A POWER POLE
 - 5) 54.0’ SE TO THE TOP OF A FIRE HYDRANT
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 180.0’ NORTH TO THE SOUTHEAST CORNER OF THE SURVEYED TRACT, AS WITNESSED BY THE 1/2” REBAR WITH HIS “LS 752” CAP HE SET AT 30.00’ WEST
 - 2) 280.0’ NORTH TO THE NORTHEAST CORNER OF THE SURVEYED TRACT AS WITNESSED BY THE 1/2” REBAR WITH HIS “LS 752” CAP HE SET AT 30.00’ WEST
 - 3) 2,644.02’ NORTH TO A 1/2” REBAR HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 9-19-11 FROM A PREVIOUS SURVEY

CONTINUED ON PAGE 6

- 25) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MAY 24, 2011 FOR PROJECT NUMBER 09015-02, THE FINAL PLAT OF *ESU ADDITION TO THE CITY OF EMPORIA* IN SECTIONS 3, 10 & 11-19-11, SAID THAT **HE FOUND THE SQUARE #4 REBAR INSIDE A GAS PIPE INSIDE A MONUMENT WELL** AT THE WEST 1/4 CORNER OF SECTION 10-19-11 FROM HIS EXISTING REFERENCE TIES ON FILE AT THE COUNTY SURVEYOR'S OFFICE DATED DECEMBER 1992.
- 1) 53.70' SW TO THE NORTHEAST CORNER OF A BUILDING AT GROUND LEVEL
 - 2) 2.0' SOUTH TO THE CENTERLINE TRAVELED WAY FOR 12TH AVENUE TO THE EAST AND WEST
 - 3) 5.0' EAST TO THE CENTERLINE TRAVELED WAY FOR WEST STREET TO THE SOUTH EXTENDED
 - 4) IN THE CENTERLINE TRAVELED WAY FOR WEST STREET TO THE NORTH EXTENDED
 - 5) 33.75' NW TO A 40 D NAIL & WASHER IN A POWER POLE
 - 6) 54.35' NE TO THE SOUTHWEST CORNER OF THE WEST BRICK PILLAR AT THE GROUND

WEST QUARTER CORNER SECTION 10-19-11